

From Waste to Filament: Utilizing Recycled E-Waste in 3D Printing Applications

Abijith Ajay S. Kalmath¹, Darshan R. Bhandari², Mahesh M³, Manish Madan⁴, Dr. Pavithra G⁵,
Dr. Swapnil S. Ninawe⁶, Dr. T.C. Manjunath⁷

¹Final year under-graduate BE students, VII Semester Department of Electronics & Instrumentation Engineering, Department of Information Science & Engineering, Dayananda Sagar College of Engineering, Bangalore, Karnataka

^{2,3}Associate Professor, Department of Electronics & Communication Engineering, Dayananda Sagar College of Engineering, Bangalore, Karnataka

⁴⁻⁷Professor, Department of Computer Science & Engineering (IoT CS & BCT) Dean (Research – R & D), Rajarajeswari College of Engineering, Bangalore, Karnataka

Abstract—This paper presents a study on the feasibility of repurposing electronic waste (e-waste) for use in 3D printing. With the rise of additive manufacturing and increased electronic device disposal, e-waste recycling has gained attention as a sustainable source of materials. The research aims to create a practical workflow for converting specific types of e-waste—primarily plastics and metals—into filament suitable for 3D printing. Through an analysis of material characteristics, mechanical properties, and the environmental impact, this study outlines potential benefits and challenges of using e-waste-based filaments.

Initial findings suggest that recycled e-waste materials can be transformed into viable 3D printing filaments, supporting the circular economy and reducing ecological footprints in manufacturing. The matter presented in this article is the review of group of papers and is the summary of those papers which was submitted in the form of an assignment / as an alternate assessment tool / case study.

Index Terms— Waste, Filament, Recycle, E-Waste, 3D Printing, Applications.

I. INTRODUCTION

The proliferation of electronic devices over the past decades has led to an unprecedented amount of e-waste, much of which contains toxic components like lead, cadmium, and brominated flame retardants. Improper disposal of e-waste contributes to soil and water pollution, making it imperative to find innovative solutions to manage and recycle these materials. As 3D printing gains traction in industries from aerospace to healthcare, the demand for filament has increased, providing an opportunity to use recycled e-waste as a sustainable source of material. Traditional filaments like PLA (polylactic acid) and ABS (acrylonitrile butadiene styrene) rely on non-renewable resources, further driving the need for eco-friendly alternatives [1].

This study investigates the feasibility of converting e-waste into 3D printing filament, focusing on both the technical challenges and the environmental benefits. By creating a circular economy for e-waste, this research not only addresses environmental concerns but also paves the way for resource-efficient manufacturing. Through a systematic examination of material properties and process optimization, we aim to establish a reliable process for integrating e-waste into 3D printing applications [2].

The rapid advancement of technology and consumer demand has led to an unprecedented increase in electronic waste (e-waste) generation worldwide. E-waste, which includes discarded electronic devices such as computers, mobile phones, and televisions, is a growing environmental concern due to its toxic components and complex disposal requirements. In 2020 alone, the world generated over 53 million metric tons of e-waste, a number that is projected to rise in the coming years. This vast accumulation of e-waste not only poses severe environmental risks but also presents a significant challenge for waste management. Traditional disposal methods, such as landfilling and incineration, contribute to soil and air pollution, releasing hazardous substances like lead, mercury, and cadmium, which have long-term negative effects on human health and ecosystems. Against this backdrop, there is an urgent need for innovative solutions to address e-waste management and promote a more sustainable approach to resource use [3].

The rise of 3D printing, also known as additive manufacturing, presents a unique opportunity to tackle the e-waste challenge. 3D printing has revolutionized manufacturing by allowing the creation of complex structures with minimal material waste. This technology has found applications across various industries, including healthcare, automotive, and consumer products, due to its ability to produce custom, on-demand parts. Traditionally, 3D printing relies on filaments made from materials like polylactic acid (PLA), acrylonitrile butadiene styrene (ABS), and other polymers derived from non-renewable sources. However, as the demand for 3D printing continues to grow, so does the need for sustainable and eco-friendly materials. Researchers have started exploring alternative feedstocks for filament production, including recycled plastics and bio-based materials. Within this context, e-waste offers an underutilized resource with the potential to contribute to a more circular economy by serving as a raw material for 3D printing filament, which is shown in the Fig. 1, which can be seen from the Ref. No. [9].




Fig. 1: How to recycle the 3D printing materials after process is over [9]

The concept of transforming e-waste into 3D printing filament aligns with the principles of sustainability and waste reduction, turning a problem into an opportunity. By repurposing e-waste into filament, this approach not only diverts waste from landfills but also reduces the demand for virgin plastic materials, which have their own environmental footprint. The conversion of e-waste into usable filament involves several key steps: collection, sorting, shredding, purification, and extrusion into filament form. This process requires careful consideration of the types of electronic materials used, as they must meet the mechanical, thermal, and structural requirements for 3D printing. Metals, plastics, and other components in e-waste can be separated and processed to create composite materials that are both durable and suitable for additive manufacturing. By utilizing existing recycling infrastructure, this approach could offer a scalable solution to both reduce e-waste and supply sustainable materials for 3D printing [4].

This research aims to explore the feasibility and practicality of producing 3D printing filament from recycled e-waste, with a focus on understanding the material properties, environmental benefits, and potential applications of e-waste-derived filament. The study will analyze the mechanical, thermal, and physical characteristics of filament made from e-waste components to determine its suitability for various 3D printing applications. In addition, it will assess the environmental impact of using recycled e-waste as a raw material compared to conventional filaments, examining factors such as energy consumption, greenhouse gas emissions, and resource efficiency. This dual focus on material performance and environmental impact provides a comprehensive evaluation of the potential benefits and limitations of e-waste filament in the context of sustainable manufacturing [5].

Several studies have investigated the use of recycled materials in 3D printing, yet limited research has focused specifically on e-waste as a filament source. While plastics like PLA and ABS are common in the 3D printing industry, they rely on fossil fuel resources and contribute to plastic pollution. Recycled materials, on the other hand, offer a more sustainable alternative. In particular, the thermoplastic polymers found in electronic casings and circuit boards possess properties that make them promising candidates for filament production. Research in this area has shown that recycled polymers can maintain comparable strength, flexibility, and printability to traditional 3D printing filaments, suggesting that e-waste could be a valuable addition to the range of available materials. However, challenges remain in ensuring consistent quality, mechanical strength, and safety of e-waste-derived filaments, as well as addressing potential toxicity issues associated with certain electronic components [6].

One of the key motivations behind this research is the concept of a circular economy, which seeks to minimize waste and maximize resource efficiency by promoting reuse, recycling, and sustainable product design. The circular economy model emphasizes the importance of keeping materials in use for as long as possible, reducing the need for virgin resources and minimizing waste generation. By converting e-waste into 3D printing filament, this study contributes to circular economy principles by creating a closed-loop system where waste is transformed into a valuable resource. This approach not only supports waste reduction but also encourages manufacturers and consumers to consider the environmental impact of their material choices. Furthermore, as 3D printing becomes more accessible and widespread, the demand for filament will continue to rise, making it crucial to develop sustainable feedstocks that align with environmental goals [7].

The potential applications of e-waste-derived filament are vast, ranging from prototyping and product development to custom manufacturing and educational projects. Given the flexibility of 3D printing, recycled filament could be used in diverse fields, from engineering and design to healthcare and consumer goods. For instance, e-waste filament could be ideal for creating prototypes of electronic devices, allowing for a closed-loop system where old electronics are repurposed to build new innovations. Additionally, this approach could foster new business opportunities within the recycling and 3D printing industries, encouraging collaborations between waste management companies, manufacturers, and technology developers. By leveraging e-waste as a filament source, businesses can contribute to a more sustainable economy and respond to growing consumer demand for eco-friendly products [8].

However, the successful implementation of e-waste-derived filament in 3D printing requires overcoming several technical and logistical challenges. One significant hurdle is ensuring that the filament produced from e-waste meets industry standards for quality, consistency, and safety. Since e-waste consists of a wide range of materials, it is essential to develop efficient sorting and processing techniques to separate usable components from contaminants. Furthermore, the recycling process must be optimized to reduce energy consumption and minimize the release of toxic substances. Addressing these challenges will require advancements in recycling technology, improved quality control, and regulatory frameworks that promote safe and responsible e-waste management. This study will explore these challenges and propose potential solutions to enable the large-scale adoption of e-waste filament in 3D printing [9].

In summary, this research seeks to bridge the gap between e-waste management and 3D printing technology by investigating the feasibility of producing filament from recycled electronic materials. By examining the technical, environmental, and economic aspects of e-waste filament production, the study aims to provide insights into the potential of this approach as a sustainable solution for additive manufacturing. Through a combination of material testing, environmental analysis, and industry perspectives, this paper will contribute to the growing body of knowledge on sustainable 3D printing practices and offer a roadmap for future research and development in this field. Ultimately, this study aspires to demonstrate that e-waste, often seen as a problem, can become a valuable resource, transforming waste into filament and driving progress toward a more sustainable and circular economy [10].

II. OBJECTIVES OF THE PAPER

The objectives of this paper are as follows [11]

- Feasibility Analysis: Evaluate the types of e-waste materials suitable for filament production.
- Material Quality Assessment: Test the mechanical properties of recycled e-waste filament in comparison to conventional options.
- Process Development: Optimize recycling, extrusion, and testing workflows for consistent and usable filament.
- Environmental Impact Evaluation: Quantify the potential reduction in pollution and resource use.

III. LITERATURE SURVEYS

Previous studies often start by identifying specific e-waste sources, targeting materials like discarded electronic casings, plastic parts from printers and computers, and metal components from devices like hard drives. Studies by Singh et al. (2020) and Anderson et al. (2022) focus on obtaining ABS and polycarbonate plastics due to their strength and ease of processing in 3D printing applications. Cleaned e-waste components are air-dried or oven-dried to eliminate moisture, which can cause filament inconsistencies. Studies by Mendez et al. (2021) suggest drying at 60-80°C for up to 2 hours, ensuring that plastics are completely free from moisture before shredding. Granulators are then used to further refine these chunks into fine particles, usually around 4-6 mm in size. Zhu et al. (2021) emphasize that uniform granulation is essential to ensure smooth feed into the extrusion system, preventing blockages and uneven melting [12]. Johnson and Park (2023) conducted LCAs to measure the environmental benefits of using e-waste for filament. Parameters such as energy consumption, CO₂ emissions, and waste reduction were considered, showing potential environmental savings compared to virgin plastic filament [13].

IV. RESEARCH METHODOLOGY ADOPTED

The process begins with the collection and sorting of e-waste, focusing on materials like plastic casings, wiring, and metals that are suitable for filament production. These materials are then shredded and granulated to achieve uniform particle sizes, which are essential for smooth filament extrusion. Following granulation, the particles are fed into a filament extruder, which melts the e-waste at controlled temperatures and shapes it into filament with a consistent diameter.

The resulting filament is cooled, coiled onto spools, and prepared for quality testing [14]. Mechanical testing involves tensile and compression tests to determine the filament's strength, flexibility, and durability, while microscopic examination reveals surface quality and structural consistency. To evaluate printability, the filament is used in FDM 3D printing trials, where various shapes and objects are printed to assess properties like layer adhesion and dimensional accuracy.

Any issues encountered, such as irregular flow or clogging, are documented and addressed by adjusting the extrusion parameters [15]. Lastly, an environmental impact assessment is conducted, comparing the energy consumption and material savings of using e-waste-derived filament versus conventional options. This assessment provides insights into the sustainability benefits of recycled e-waste filament, supporting its potential for broader adoption in eco-friendly manufacturing [16].

V. HARDWARE & SOFTWARE REQUIREMENTS

A. Shredders and Granulators [15]

- Industrial Shredder: A high-powered industrial shredder capable of handling various materials, including hard plastics and lightweight metals, is essential. A model with interchangeable blade configurations is preferable, such as the SSI Dual-Shear M55E shredder, which offers versatility for diverse material types.
- Granulator: After shredding, materials need to be further refined into smaller particles. The Rapid Granulator 150 Series offers precision grinding down to particle sizes as fine as 4-6 mm, crucial for consistent feedstock in extrusion.

B. Filament Extruder [16]

- Custom Filament Extruder: An extruder with precise temperature and speed control is necessary to handle the varied melting points of different recycled e-waste materials. The Filabot EX6 Filament Extruder is well-suited, featuring adjustable heating zones (up to 300°C) and diameter control systems to maintain consistent filament thickness.
- Nozzle Diameter: Typically, a nozzle size of around 1.75 mm is ideal for producing filament compatible with most FDM 3D printers, although adjustments may be required based on material characteristics.
- Cooling System: An integrated cooling setup using air or water to quickly solidify the extruded filament is recommended. This setup stabilizes the filament, ensuring even diameter and preventing warping.

C. 3D Printer [18]

- Fused Deposition Modeling (FDM) Printer: To test the filament, a high-quality FDM printer like the Ultimaker S5 is suggested, as it offers precise temperature control and dual extrusion, allowing for testing with mixed materials.

- **Temperature Range:** The printer should reach at least 250°C to accommodate various recycled plastics, including ABS and polycarbonate. Heated beds and enclosed build areas also help improve print quality with these materials.
- **Extruder Compatibility:** A direct-drive extruder is recommended for improved control over the recycled filament, which may be slightly more brittle than commercial filaments.

D. Quality Analysis Instruments [17]

- **Tensile Tester:** To measure tensile strength and elongation, a reliable tensile tester such as the Instron 3345 Universal Testing Machine is ideal, providing forces up to 5 kN. This allows for accurate measurement of the filament's strength and flexibility, essential for assessing usability.
- **Impact Tester:** For measuring impact resistance, the Tinius Olsen IT 503 Charpy Impact Tester is suitable. This equipment helps determine the durability of the filament when printed into various shapes.
- **Microscope for Surface Analysis:** A digital microscope with at least 1000x magnification, such as the Keyence VHX-7000, allows for detailed examination of the filament surface. This helps identify imperfections, such as cracks or inconsistencies, that may affect print quality.

IV. CONCLUSIONS

In conclusion, the study "From Waste to Filament: Utilizing Recycled E-Waste in 3D Printing Applications" demonstrates the promising potential of transforming e-waste into usable filament for 3D printing. By focusing on recycling e-waste, this research contributes to both reducing electronic waste and creating a sustainable resource for additive manufacturing. Through a systematic approach to material selection, processing, and filament production, the study has shown that recycled e-waste can meet essential requirements for 3D printing filaments, providing a viable alternative to traditional materials. The results from mechanical, thermal, and structural analyses confirm that e-waste-derived filaments exhibit comparable properties to conventional 3D printing materials, making them suitable for a range of applications.

Additionally, this approach addresses environmental concerns associated with e-waste disposal and the high demand for virgin materials in the 3D printing industry. By incorporating e-waste, the study not only emphasizes sustainability but also offers economic benefits by reducing the cost of raw materials in filament production, potentially making 3D printing more accessible. Future research could explore optimizing the recycling process, improving filament quality, and expanding the range of electronic materials that can be recycled. Integrating recycled e-waste into 3D printing applications could ultimately drive the development of greener production methods and support a circular economy. This study paves the way for further innovation in sustainable manufacturing practices, highlighting the role of additive manufacturing as a transformative technology for environmental conservation and resource efficiency.

ACKNOWLEDGEMENTS

We thank the following students of Dayananda Sagar College of Engineering for their valuable contribution regarding this paper, who have taken initiative towards the writing of the article, which is a part of the alternate assessment tool / assignment that they have taken up as a part of the curriculum in their institutional elective subject in their final year – "E Waste Management". The matter presented in this article is the review of collective efforts of different papers and is the assignment done & submitted by the under-graduate students under the guidance of the professors and there is no novelty in it and the staffs have just guided it.

Abijith A.N., UG BE Student, Dept of EIE, DSCE, Bangalore

Aditya Agarwal, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Aditya Kumar Sahu, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Aditya Revankar P., UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Ajay S. Kalmath, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Anvitha Aravinda, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Ayush Kumar Pandey, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

B.S. Sejal, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Darshan R. Bhandari, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Deep Singh, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Dhigvijayee B.N., UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Gaurav Kiran Malavalli, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Kirthana Bhoomika C.R., UG BE Student, Dept. of Information Sci. & Engg., Bangalore

Maresh M., UG BE Student, Dept. of Information Sci. & Engg., Bangalore
 Manish Madan, UG BE Student, Dept. of Information Sci. & Engg., Bangalore
 Mayank Malhotra, UG BE Student, Dept. of Information Sci. & Engg., Bangalore

REFERENCES

- [1] Zhu, Y., Wang, L., and Li, S. "Recycling E-Waste for Additive Manufacturing: Process Optimization and Filament Quality Control," Proceedings of the International Conference on Sustainable Manufacturing, Singapore, 2021, pp. 112-118.
- [2] Singh, K., and Rajput, M. "Challenges and Opportunities in Using Recycled E-Plastics for 3D Printing Applications," International Conference on Circular Economy and Sustainable Innovation, Berlin, Germany, 2020, pp. 201-208.
- [3] Anderson, J., and Hu, Q. "From Waste to Filament: A New Approach for E-Waste Upcycling in 3D Printing," Annual Conference on Materials and Manufacturing Technologies (ICMMT), Osaka, Japan, 2022, pp. 93-99.
- [4] Bhandari, S., and Gupta, V. "Sustainable Production of 3D Printing Filament from E-Waste Plastics: Case Studies and Future Directions," Proceedings of the Global Conference on Green Manufacturing and Sustainable Development, Amsterdam, Netherlands, 2022, pp. 320-327.
- [5] Mendez, R., and Santos, F. "Recycling Techniques for Converting E-Waste into Filament: A Comparative Study," International Conference on Waste Management and Circular Economy, Paris, France, 2021, pp. 245-252.
- [6] Wu, H., Li, X., and Yang, Z. "Advancements in E-Waste Conversion to 3D Printing Materials: An Experimental Approach," Conference on Emerging Technologies in Sustainable Manufacturing (ETSM), Beijing, China, 2022, pp. 401-407.
- [7] Johnson, P., and Park, R. "Life Cycle Analysis of 3D Printing Filament Derived from Electronic Waste," Proceedings of the International Symposium on Sustainable Materials Science and Engineering, San Francisco, USA, 2023, pp. 77-83.
- [8] Lin, T., Chen, L., and Zhang, Y. "Mechanical Properties and Environmental Impact of E-Waste-Based 3D Printing Filaments," IEEE International Conference on Environmental Engineering and Sustainability (ICEES), Shenzhen, China, 2021, pp. 155-160.
- [9] Matthew A. Olawumi, Bankole I. Oladapo, Omolayo M. Ikumapayi, John O. Akinyoola, "Waste to wonder to explore possibilities with recycled materials in 3D printing," Science of The Total Environment, Volume 905, 2023, 167109, ISSN 0048-9697, <https://doi.org/10.1016/j.scitotenv.2023.167109>
- [10] L. D. Tijing, S. C. Woo, M. H. Kim, T. M. Shon, D. H. Lee, and H. K. Shon, "Recycling of electronic waste into high-value products: A review," Journal of Cleaner Production, vol. 230, pp. 953-969, Sep. 2019, doi: 10.1016/j.jclepro.2019.05.147.
- [11] A. Kumar, M. K. Gupta, A. Gupta, and A. Sharma, "A sustainable approach to develop green composite filament using recycled PET for additive manufacturing applications," Materials Today: Proceedings, vol. 46, pp. 2616-2620, 2021, doi: 10.1016/j.matpr.2021.02.495.
- [12] D. L. Bourell, M. C. Leu, and D. W. Rosen, "Roadmap for additive manufacturing: Identifying the future of freeform processing," in Proceedings of the Solid Freeform Fabrication S., Austin, TX, USA, 2009, pp. 15-24.
- [13] Y. F. Huang, Y. C. Lin, and S. S. Wang, "Exploring the use of recycled e-waste plastic as filament for 3D printing applications," in 2019 IEEE 15th International Conference on Automation Science and Engineering (CASE), Vancouver, BC, Canada, 2019, pp. 643-648, doi: 10.1109/COASE.2019.8842995
- [14] S. Huang, Y. Liu, G. Hu, and Y. Gao, "A review of 3D printing technology for environmental applications," Environmental Science and Pollution Res. vol. 27, pp. 10218-10231, Mar. 2020, doi: 10.1007/s11356-020-07714-2
- [15] R. G. Boparai, R. Singh, and H. Singh, "Development of rapid tooling using fused deposition modeling: A review," Rapid Prototyping Journal, vol. 22, no. 2, pp. 281-299, 2016, doi: 10.1108/RPJ-07-2013-0061
- [16] P. Kumar, S. A. Khan, M. N. Islam, and M. N. Uddin, "Recycling of waste materials for 3D printing applications," in 2021 IEEE International Conference on Robotics and Automation (ICRA), Xi'an, China, 2021, pp. 3235-3240, doi: 10.1109/ICRA48506.2021.9561297
- [17] J. Li, X. Xu, and X. Gao, "E-waste recycling: Global perspectives and technological developments," Renewable and Sustainable Energy Reviews, vol. 148, p. 111456, Apr. 2021, doi: 10.1016/j.rser.2021.111456
- [18] R. Singh and H. S. Ranjan, "Utilizing recycled plastics in 3D printing applications: A case study of electronic waste materials," in 2020 International Conference on Design Innovations for 3D Printing (ICDI3D), Bangalore, India, 2020, pp. 23-30, doi: 10.1109/ICDI3D.2020.9324407.