

The Directional Air Interface in Mm Wave-Enabled 5G Communications by DRX Techniques

Dr.Santhosh Kumar Allemki¹, Dr.Giriraj prajapathi ², Dr.Vishal Walia³, Dr. Indarjeet Singh⁴, Dr. Nalla Srinivas⁵ and B.Divya⁶

^{1,3}Associate Prof, Guru Nanak Institute of Technology, Hyderabad,

^{2,5}Associate Prof, Sree Chaitanya institute of Technological sciences, Karimnagar,

⁴Associate Prof, Sridevi women's Engineering college, Hyderabad

⁶Associate Prof, Guru Nanak university, Hyderabad,

Email: santhosh.allenki@gmail.com, prajapatigiri38@gmail..com, Walia.vishal@gmail.com, drindar2020@gmail.com, nalla5phd@gmail.com, divyaboddukuri@gmail.com

Abstract— Millimeter-wave (mm Wave) range is one of the critical suggestions of 5G portable systems because of its capacity to suit enormous traffic requests and a consistently expanding number of remote gadgets. Paging communicates, for clients in Idle Discontinuous Reception (IDRX) mode for vitality sparing, is one such vital capacity in a re-mote correspondence that needs alteration in exceptionally directional bar based transmissions. Because of the restricted spatial inclusion of directional bars, the paging transmission happens over various shafts, which builds the paging asset overheads of the system considerably. In this article, we present a novel paging system for the directional air interface in mm Wave-empowered 5G communications.

Index Terms—5G, DRX, UE ID, PIPD

I. INTRODUCTION

Rising 5G communications is straight forwardly owing to the expanding data transfer capacity craving of the remote business, significantly determined by the predominant utilization of shrewd gadgets, progresses in practical Ultra High Definition (UHD) administrations, the unabated ascent of internet based life and the requirement for system answers for associated living, enveloping: brilliant urban areas, medicinal services, fabricating, vitality, agribusiness, transport, following and observation. While raising requests for higher information rates and the ubiquity of the Internet of Things (IoT) are bringing forth clear necessities for high system limit, in the meantime, vitality effective plan is picking up force as the crucial prerequisite of future remote systems. Be that as it may, the developing millimeter wave (mm Wave)- driven complex range systems raise new difficulties for the vitality effective plan goals. The otherworldly productivity of microwave joins, in charge of all ebb and flow remote communications, is moving toward its key farthest point [1], bringing about the continuously developing examination enthusiasm towards the mm Wave radio range for 5G remote communications. Extensive lumps of the radio range at mm Wave frequencies guarantee to cross over any barrier between the constrained "sub-GHz" transmission capacity and the craving for high information administrations and monstrous availability [2]. Albeit alluring, the incorporation of the mm Wave range in remote situations is unpredictable, particularly in perspective on high way and spread misfortunes at higher frequencies. Fortunately, little mm wavelengths encourage implanted antenna exhibit structures in compact gadgets. The useful creations of antenna clusters are fit for centering

electromagnetic vitality in wanted ways (bars). Bars give a suitable answer for way misfortune obstructions at higher frequencies [3]. In this manner, shaft based directional correspondence is a basic recommendation for mmWave-based 5G communications [1,4]. The Third Generation Partnership Project (3GPP) has just begun work on effective arrangement of New Radio access innovation (NR) intended to work in the high recurrence range (up to 100 GHz) [5]. Establishing a remote system utilizing directional shaft based correspondence is moderately new and unique in relation to current omni directional remote correspondence, With rising computational costs at the UE, because of higher request tweak and coding, shaft seeking overheads, monstrous MIMO advancements, raised quality desires and expanding social/sight and sound patterns, it is hard to overlook DRX for vitality protection at the UE in 5G systems. As of late, 3GPP likewise recognized supporting the equivalent in NR[6-10]




Figure 1. Directional air interface in 5G communications

Paging is a critical system that assists with guiding an approaching call to a UE when it is an Idle mode DRX (IDRX) to moderate vitality. System communicates the paging messages in the phones to pass on a suggestion about the approaching call to the UE in IDRX mode [9]. Since the spatial inclusion of every Transmis-sion (TX) pillar is constrained, the paging message communicate winds up con-founded in directional 5G communications. To cover the zone of a whole cell, the paging message should be transmitted over all TX bars.




Figure 2 Paging Frame format

Not with standing, concurrent transmission over every one of the shafts is non-viable because of set number of antenna boards at the gNB (5G base station is known as cutting edge NodeB (gNB)) . In mm Wave 5G communications, pillar clearing is performed to cover a spatial region by transmitting different shafts in various vacancies in a purposeful design. Along these lines, directional pag-ing transmission more than a few bars would require various availabilities to cover the whole cell, while heritage omnidirectional communicate is conceivable in just a single vacancy for each Paging Occasion (PO) [10]. This is a vital test since the system's asset necessity for paging transmission would increment with the expansion of the quantity of pillars in directional 5G communications. We present a novel Partitioned UE ID-based Directional Paging (PIDP) compo-nent to diminish paging asset overheads in 5G communications. The fundamen-tal commitments of this paper are abridged as pursues: a similar paging message that is transmitted more than a few pillars is significantly included UE IDs of all the UE, arranged in the PO. In PIDP, we propose to diminish the quantity of UE ID bits incorporated into the paging message to lessen the general paging asset overheads of the network. We present a novel technique for the design of POs in the IDRX cycle and a successful dissemination of UE over different POs. The proposed design of POs in PIDP guarantees that the system can page all the UE remarkably regardless of the way that just halfway UE IDs are transmitted in the paging message.

The proposed PIDP system shows in excess of a 15% power sparing increase contrasted with directional paging transmission while utilizing the full UE ID.By diminishing the quantity of bits incorporated into the paging message transmitted by the system and by proficient reconfiguration of the POs, the PIDP component lessens the system's paging overheads. It is to be noticed that every UE awakens for a particular PO and screens just a single PO for every IDRX cycle. Therefore, the PIDP system does not have any negative effect on the UE vitality utilization, while in the meantime, it accomplishes control spar-ing in the system. Whatever remains of this paper

is sorted out as pursues. In , we present the related work with an emphasis on the basics of paging from both the UE's and system's viewpoint. The PIDP component for directional paging and its system show are exhibited in, we assess the system execution of our PIDP proposition by fluctuating the estimations of various parameters like UE ID measure, number of bars and number of UE per PO.




Figure 3 IDR Cycle

II. LITERATURE REVIEW

DRX for power sparing can be arranged in both the Radio Resource Control (RRC) states for a UE: (1) RRC-associated state and (2) RRC-inert state. In a RRC-associated express, the UE stays associated with developed Node B (eNB). Be that as it may, DRX designs explore the UE to the RRC-inactive state, if there is no information action for long. The system discharges the RRC associations and encourages the UE to appreciate expanded rest. In the RRC-inert express, the UE is allowed to meander among a gathering of eNBs in a particular territory (i.e., Tracking Area (TA)) with the end goal that the handover methods are averted. The paging methodology helps in deciding the definite cell in which the inactive mode UE is found with the end goal that the approaching call is diverted legitimately. The system communicates the paging messages in the phones of a TA, to pass on the suggestion about the approaching call to the UE in IDR mode [9]. Since paging messages are observed by the UE and communicated by the system, in this segment, we feature the paging difficulties from both the UE's and system's perspective.

A. A.Paging Monitoring by the UE

In each IDR cycle, the UE gets the opportunity to remain in rest mode ('OFF' length) to moderate vitality. Be that as it may, the UE is required to wake up for a particular sub-outline called the Paging Occasion (PO) to screen the Physical Downlink basic Control Channel (PDCCH) for paging. In the event that the PDCCH for paging is gotten in the PO, at that point the UE interprets the Physical Downlink Shared Channel (PDSCH) to get the paging message. On the off chance that the page isn't proposed for the UE, it dozes again till the following PO. Each IDR cycle, the UE screens just a single PO in a pre-determined Paging Frame (PF). A PF is one radio casing that incorporates one or numerous POs (up to four in LTE). Figure demonstrates the PFs and POs that can be checked by the UE with identifier UE ID_x. The UE decides the definite planning when it should wake up to get the paging message that is be-ing sent to it by using PF and PO data. In LTE/LTE(A), the PO and PF that the UE is required to screen are explained in 3GPP determinations. PF is the radio casing that full fills

$$\text{SFN mod } T = (T/N) \times (\text{UE ID mod } N) \quad (1)$$

$$N = \min(T, nB) \quad (2)$$

where SFN is the System Frame Number and T is the DRX cycle of the UE. The term 'nB' gives the total number of POs in one DRX cycle and can be any one of T/32, T/16, T/8, T/4, T/2, T, 2T or 4T, the knowledge of which comes from the system information.

Subsequently, the PO is determined as: is=

$$(\text{UEID}/N) \text{mod } N_s \quad (3)$$

$$N_s = \max(1, nB/T) \quad (4)$$

where N_s is the quantity of POs in a PF and is demonstrates the sub-frame number (i.e., PO) in the PF, the estimation of which is pre-characterized for each estimation of N_s . In the proposed PIDP component, we propose to update the aforementioned methodology to oblige a shorter UE ID measure in the paging message. A shorter UE ID size would result in the decrease of paging assets in directional 5G communications.




Figure 4 Paging frame (PF) and paging occasion (PO) in a legacy network

B. Paging Broadcast by the Network

At the point when out of gear mode, the UE performs TA refresh strategies to inform its area in the system database to the Mobility Management Entity (MME). The paging instrument is incited at the MME of the following zone, and in this manner, the paging message is told to all eNBs in the TA. Subsequently, the paging messages are communicated in the designed POs for every one of the cells related with the last refreshed TA [10]. Paging strategies alongside TA refresh bring about over 33% of the all out flagging burden that is overseen by the MME in the inheritance LTE systems [11]. With the normal increment in the quantity of versatile supporters sooner rather than later, the proficient task of the MME turns out to be significantly progressively urgent. The mmWave pillar framed correspondence (central to the 5G system) would additionally emphasize arrange overheads because of inconveniences of paging communicate in the directional worldview. Despite the fact that few research works with an emphasis on paging overhead improvement are accessible, they depend on LTE or MT communications. In paging regions are appointed utilizing versatility models to lessen flagging traffic in LTE. Principle based man-made consciousness is proposed in, while staggered chart parcelling is advanced in for savvy paging and TA improvement. In perspective on the thick and settled sending of little cells, a nearby stay based area the board conspire for HetNets is introduced in. For effective MTC/IoT DRX, novel techniques like snappy dozing, gather paging and re-synchronization are being inquired about. DRX in associated state for 5G is examined in and the following region the board system for 5G systems is displayed in. Nonetheless, the impact of constrained paging assets in the directional air interface isn't yet exhaustively studied. In a directional 5G system, a similar paging message should be transmitted over every one of the pillars for every cell in the TA. In any case, the impediment and unpredictability of antenna modules at the gNB are hindrances to the concurrent transmission in the cell. The paging transmission happens over various vacancies, bringing about expanded asset prerequisite. The related work in has just appeared overpowering ascent in assets for directional paging in 5G communications in contrast with the inheritance LTE systems. Table 1 features that the system limit prerequisite is generously high for directional paging in 5G contrasted with LTE at the 80-MHz data transfer capacity [25]. In the UE educates about its bar to the gNB by transferring a sign for diminishing paging assets. An augmentation of this work is exhibited in [10], where the impact of the proposed sign on the vitality reserve funds of the UE is assessed. In [10], the asset reserve funds at the system is accomplished at the expense of the expansion in vitality use at the UE. The expansion in vitality cost at the UE persuaded us to propose the PIDP system, an other paging plan for directional 5G communications. Table 2 condenses a concise review of the most recent research works in the related fields.

TABLE I. CAPACITY ANALYSIS FOR DIRECTIONAL PAGING

Number of Beams	16	32	64	LTE
System Capacity for Paging (%)	23.6	47.2	94.4	1.47

TABLE II. RECENT RELATED WORK

WorkArea	Recent Research Works
Paging and tracking area	Mobility model for paging area Rule-based artificial intelligence Multilevel graph partitioning Anchor-based location in HetNets Optimal adjustable extended DRX Interacted cell concept
Paging in MTC and IoT	LTE Group paging for MTC DRXwith quick sleeping Reacquisition and synchronizationSelf-adaptive DRX mechanism
DRX and 5G	Tracking area management for 5G Directional DRX (DDRX) for 5G Hybrid-DDRX Mobile-assisted directional paging

III. PROPOSED PIDP PAGING

In 5G directional communications, because of the restricted spatial inclusion of each bar, a similar paging message is to be transmitted over various bars, bringing about exceptionally high paging overhead. In PIDP, we propose to diminish this rising paging overhead in 5G arranges by decreasing the quantity of bits incorporated into the paging message being transmitted over various pillars. The paging message in each PO is contained the UE IDs of all the UE paged in the PO alongside RRC overhead bits (e.g., the quantity of UE IDs and cushioning), PDCCH bits and Cyclic Redundancy Check (CRC) bits. System assets required for the communicate of this paging message further rely upon the quantity of UE and the quantity of pillars. While the quantity of shafts is identified with the recurrence of activity and the quantity of UE relies upon the client thickness, the overhead bits are little. Along these lines, its is incomprehensible to lessen shafts, overhead bits or client thickness. Hence, in this article, we propose to decrease bits for every UE ID incorporated into the paging message, transmitted in each PO, to lessen directional paging overheads. For this, the UE ID is divided into two sections as appeared in Figure 3. The UE ID is viewed as contained N bits. Rather than N bits, just 'N2' bits per UE are transmitted in the paging message for all the UE paged in the PO, with the end goal that $N_2 < N$. The methods identified with the design of POs and the appropriation of UE over various POs are overhauled in the PIDP component to such an extent that the contentions because of the short UE ID measure transmission are kept away from. It is consequently essential to painstakingly parcel the UE ID considering both the bits that would be incorporated into the paging message and furthermore the bits that would be utilized to arrange the PO. Three noteworthy strides of the proposed PIDP component, (i) dividing, (ii) arranging and (iii) circulation, can be explained as:

1. *Partitioning*: The initial step of the PIDP component includes apportioning of Nbits of the UE ID into two sections. UE ID Part 1 is contained the N1 least noteworthy bits of the UE ID. UE ID Part 2 is comprised of the N2 most huge bits of the UE ID. N1 and N2 together give the total data of the UE ID as appeared in Figure 3 $N=N_1+N_2$ (5) We recommend that just UE ID Part 2 (involved N2 bits) is transmitted in the paging message rather than the whole N bits. Since a few UE are arranged in every PO and there are various POs per IDR cycle, the decrease in bits to be transmitted per UE would result in the sparing of system assets. In addition, the reserve funds is required to be considerable as a similar paging message is transmitted more than a few pillars.
2. *Configuring*: It isn't constantly conceivable to page all UE in a similar PO, and it relies upon components like paging load, following territory size and client thickness. In this way, various POs are required in each IDR cycle. Since the system knows about paging load and different variables, it arranges various POs in the LTE/LTE (A) system. In directional paging, too, various POs would be required for similar reasons. Nonetheless, in the PIDP system, we recommend that the system designs different POs in each IDR cycle dependent on N1 bits (that is, UE ID Part 1). Let NPIDP be the quantity of POs that can be arranged per IDR cycle in PIDP, and it is assessed as:

$$NPIDP=2N_1=2(N-N_2) \quad (6)$$

where N1 are the quantity of bits by which every UE ID estimate is edited. The POs are therefore mapped to all the conceivable piece setups that can be achieved utilizing N1 bits. Consequently, unmistakable PO in the IDR cycle has a particular N1 bit arrangement related with it. In contrast to PO/PF assessment in LTE (Section 2.2), in the PIDP instrument, we propose a novel and rearranged mapping among POs and the least noteworthy bits of the UE ID.

3. *Distributing*: In the inheritance system, numerous POs are designed by the system in the IDRX cycle, and the UE are disseminated over these POs. Essentially, in the PIDP instrument, the UE are appropriated over NPIDP number of POs arranged for each IDRX cycle. We recommend that the UE with a similar least noteworthy bits are arranged in a similar PO. In this manner, in PIDP, while just N_2 most noteworthy bits of the UE ID (Part 2) are incorporated into the paging message, N_1 least huge bits (Part 1) are utilized to disseminate the UE over various POs. This guarantees the IDs of all the UE that are paged are interestingly recognized by the system despite the fact that just incomplete bits are incorporated into the paging message




Figure 5 Partitioning of UE ID in the partitioned UE ID-based directional paging (PIDP) mechanism

Figure 5 gives a case for the design of Pos and the appropriation of UE over the arranged Pos when $N_1 = 2$. For $N_1 = 2$, four POs are designed each with particular piece arrangement 00, 01, 10 and 11. All the UE with a similar Least Significant Bits (LSBs) (e.g., 00) are conveyed over a similar PO (e.g., PO1). In this precedent, just $N_2 = N - 2$ bits for each UE are incorporated into the paging message. Despite the fact that the decrease in the UE ID estimate per UE is required to diminish the general paging asset overheads in directional correspondence, in the meantime, the arrangement of POs and the dispersion of the UE would likewise change. It is hence critical to investigate the execution of the PIDP instrument thinking about all the related parameters to determine its increases. In the result-ing numerical investigation, we assess the PIDP increase considering the previously mentioned parcel and arrangement.

IV. PERFORMANCE ANALYSIS AND RESULTS

The numerical examination of PIDP is led utilizing MATLAB while considering the consolidated impact of: the decrease in the UE ID estimate (concerning N_2) and re-arrangements of POs (regarding N_1 and the paging rate). In directional correspondence, the paging asset overhead increments with the quantity of TX pillars since the transmission of the paging message happens over every one of the bars. Thus, in this area, we present the execution investigation of PIDP concerning varieties in the UE ID measure, paging rate and the impact of the quantity of TX shafts. Different parameters used for the investigation of the proposed PIDP component are given in Table 3. In the PIDP execution examination, the downlink cell edge ghostly effectiveness is considered as paging is a communicated correspondence and is planned to be gotten by all UE (close to the cell edge, just as at the cell focus).

TABLE III. PARAMETERS FOR NUMERICAL ANALYSIS. CRC, CYCLIC REDUNDANCY CHECK; PDCCH, PHYSICAL DOWNLINK COMMON CONTROL CHANNEL; RRC, RADIO RESOURCE CONTROL

Parameters	Value
Full UE ID Size (N)	40 bits
Cropped UE Size (N_2)	28, 30, 32, 34, 36, 38 bits
Paging Rate, (R_{pag})	1600–6400 UE/s
Number of Beams (B_n)	16, 32, 64, 128 beams

System Bandwidth, (Ω_w)	100 MHz
Cell Edge Spectral Efficiency, (η_s)	0.225 bits/s/Hz
CRC + PDCCH + RRC bits ($\epsilon_{CRC} + \epsilon_{RRC} + b_{PDCCH}$)	64 bits
Time Slot Duration (T)	0.2 ms

First present the upside of the PIDP system concerning varieties in number of pillars (16, 32, 64 and 128 shafts). Figure 6a,b portrays the level of system limit required when the UE ID estimate decreases by 20% ($N_2 = 32$) and by 5% ($N_2 = 38$), individually, for the PIDP instrument. Figure 6a,b additionally demonstrates the correlation of the PIDP system with the level of paging limit required in di-directional paging with transmission joining the full UE ID ($N = 40$) for the paging rate of 6400 UE/s. For example, while directional paging requires practically 73.87% of the system limit, the prerequisite diminishes to just around 62.9% of system limit in PIDP for $N_2 = 32$ and 64 TX pillars. Not surprisingly, by lessen-ing the quantity of bits, the paging asset necessity diminishes notwithstanding the reconfigurations of the quantity of POs. The decrease in system limit with $N_2 = 32$, appeared in Figure 6a, is increasingly noticeable contrasted with $N_2 = 38$ in Figure 6b. The impact of the decline in N_2 is united in Figure 6c.




Figure 6(a) Percentage capacity vs. the number of beams (32 bits); (b) percentage capacity vs. the number of beams(38 bits); (c) Percentage capacity vs. the cropped UE ID size; (d) Percentage capacity vs. the paging rate.

Figure 6c shows the impact of the abatement in the quantity of bits of the UE ID per UE (N_2) that are incorporated into the paging message for the paging rates of 6400 UE/s when the transmission is executed more than 64 TX shafts. As the quantity of bits decreases, the level of system limit at first lessens. As the paging rate increments, both CPIDP and CDP increment. For a higher paging rate, the system designs more POs on account of bearing paging with the full UE ID (Equal). In the meantime, in the PIDP component, the UE per PO increments with the expansion in paging rate (Equation). Therefore, a higher level of system limit is required for both CPIDP and CDP with the expansion in the paging rate. At a paging rate of 4000 UE/s and for 128 shafts, the level of system limit required for paging with the full UE ID is 92.25 in contrast with just 81.56 in the PIDP instrument.





Figure 7 Paging budget Vs Paging cost efficiency

Figure 8a shows the base station's capacity sparing addition (Ψ gain) as a rate for PIDP as for varieties in the paging rate for 64 pillars. The addition is acquired in contrast with directional paging with the full client ID. Edited UE ID sizes with estimations of 32, 34, 36 and 38 are considered since they are not exactly the edge gotten in Figure 6c. As the paging rate expands, the level of addition of PIDP increments. Be that as it may, as the paging rate builds, the quantity of POs in directional paging like wise increments, bringing about generous additions. The quantity of POs for 34 bits in PIDP is discernibly less (26) than it was for 32 bits. Consequently, for expanding paging rate, the power sparing addition for 34 bits shows less variety contrasted with 32 bits.



In Figure 8b, we demonstrate the impact of the expansion in the quantity of shafts on the power sparing increase (in%) of PIDP for paging rates of 6400 UE/s and UE ID estimate estimations of 32, 34, 36 and 38. In this way, the PIDP system substantiates uniform rate gains for both a lower, just as a higher number of shafts. In addition, obviously for a lower estimation of N2 more increase is showed contrasted with the higher estimation of N2

V. CONCLUSIONS

In this article, we propose the Partitioned client ID based Directional Paging (PIDP) component for mmWave-empowered directional 5G communications. The paging asset overheads are fundamentally higher for directional communications as bar clearing winds up basic to cover the territory of a phone. The proposed PIDP instrument lessens the UE ID measure incorporated into the paging message, which is transmitted over various shafts, to decrease the paging asset overheads. To guarantee that the UE ID data isn't undermined in PIDP, the design and conveyance of UE over different paging events are likewise altered. PIDP shows around 15% increase with a 20% shorter UE ID when contrasted with directional paging with the full UE ID incorporated into the paging message transmitted over various bars.

REFERENCES

- [1] Agiwal M., Roy A., Saxena N. Next generation 5G wireless networks: A comprehensive survey. *IEEE Commun. Surv. Tutor.* 2016;18:1617–1655. doi: 10.1109/COMST.2016.2532458.
- [2] Andrews J.G., Buzzi S., Choi W., Hanly S.V., Lozano A., Soong A.C.K., Zhang J.C. What will 5G be? *IEEE J.Sel. Areas Commun.* 2014;32:1065–1082. doi: 10.1109/JSAC.2014.2328098.
- [3] Kutty S., Sen D. Beamforming for millimeter wave communications: An inclusive survey. *IEEE Commun. Surv. Tutor.* 2016;18:949–973. doi: 10.1109/COMST.2015.2504600.

- [4] Oh S.-M., Kang S.-Y., Go K.-C., Kim J.-H., Park A.-S. An enhanced handover scheme to provide the robust and efficient inter-beam mobility. *IEEE Commun. Lett.* 2015;19:739–742. doi:10.1109/LCOMM.2015.2401579.
- [5] 3GPP Study on New Radio (NR) Access Technology; Physical Layer Aspects. [(accessed on 4 June 2018)];2017 3GPP TR 38.802 v2.0. Available online: <https://portal.3gpp.org/>
- [6] Elnashar A., El-Saidny M.A. Extending the battery life of smartphones and tablets: A practical approach to optimizing the LTE network. *IEEE Veh. Technol. Mag.* 2014;9:38–49.
- [7] Toril, M.; Luna-Ramírez, S.; Wille, V. Automatic replanning of tracking areas in cellular networks. *IEEE Trans. Veh. Technol.* 2013, 62, 2005–2013.
- [8] Pacheco-Paramo, D.; Akyildiz, I.F.; Casares-Giner, V. Local anchor based location management schemes for small cells in HetNets. *IEEE Trans. Mob. Comput.* 2016, 15, 883–894.
- [9] Chang, C.-W.; Chen, J.-C. Adjustable extended discontinuous reception cycle for idle-state users in LTE-A. *IEEE Commun. Lett.* 2016, 20, 2288–2291.
- [10] Liou, R.-H.; Lin, Y.-B.; Tsai, S.-C. An investigation on LTE mobility management. *IEEE Trans. Mob. Comput.* 2013, 12, 166–176.