

Automatic Driving Assistant System in Cars

Manjunatha A S¹, Dr. Ashish Singh², Shrinivasa³, Ananya⁴ and Matti Nidhi Prabhu⁵

¹⁻⁵Department of CCE, Nitte (Deemed to be University), NMAM Institute of Technology, Nitte

Email: manjunatha.as@nitte.edu.in, ashishsingh@nitte.edu.in, shrinivasa.naik@nitte.edu.in, ananya2004bhat@gmail.com, mattinidhiprabhu@gmail.com

Abstract— The development of Automatic Driver Assistance Systems (ADAS) has advanced to the forefront of automotive innovation due to the unwavering quest of safer roads and improved driving experiences. In this, the computational capability of the COMSOL Multiphysics tool and the integration of LiDAR sensor technologies are used to design and implement an Automatic Driving Assistant System (ADAS). LiDAR sensors are a crucial part of contemporary autonomous driving systems because of their reputation for high-resolution mapping and real-time environmental monitoring. The suggested ADAS improves vehicle perception, navigation, and decision-making by utilizing the rich data from LiDAR sensors. Real-time obstacle recognition and avoidance, lane keeping assistance, adaptive cruise control, and collision mitigation are all included in the developed ADAS. Because of the LiDAR sensor's great precision and quick data collection, accurate mapping of the immediate surroundings, enabling the ADAS to respond quickly to changing traffic situations. Engineers are thus able to simulate and optimize the ADAS performance under various environmental situations thanks to the interaction with COMSOL Multiphysics, guaranteeing its efficacy across a range of terrains and weather conditions. Comprehensive simulations and real- world testing scenarios demonstrate the efficacy of the proposed ADAS, showing notable enhancements in vehicle safety, efficiency, and overall driving pleasure. This creates new opportunities for the advancement of sophisticated autonomous driving technologies, leading to the development of more dependable and safe modes of transportation.

Index Terms— ADAS, LiDAR, COMSOL, obstacle.

I. INTRODUCTION

By automating some driving operations, an Automatic Driving Assistant System (ADAS) is a cutting-edge piece of technology that helps drivers operate their cars. To improve vehicle efficiency, comfort, and safety, ADAS systems combine sensors, cameras, radar, LiDAR, and computer algorithms. Numerous tasks can be carried out by these systems, including autonomous emergency braking, lane- keeping assistance, adaptive cruise control, pedestrian recognition, and parking aid. ADAS systems are capable of keeping drivers aware of possible dangers, assisting in maintaining safe distances from other cars, and even taking action to stop collisions by continuously scanning the environment around the vehicle and evaluating sensor data. The ultimate goals of ADAS systems are to increase road safety, enhance driver capabilities, and open the door for more advanced autonomous driving technology. Within the constantly changing field of automotive technology, the incorporation the introduction of Advanced Driver Assistance Systems (ADAS) represents a revolutionary step forward and the start of a new era in transportation efficiency and safety.

LiDAR and radar sensors, heralded as the key technologies enabling cars with previously unheard-of perceptual skills, are at the forefront of this transformation. These sensors give them the capacity to recognize items in their immediate environment, calculate distances accurately, and anticipate any threats in real time—much like the watchful eyes and ears of contemporary automobiles. Comsol Multiphysics is a groundbreaking technology that provides a broad and comprehensive platform for simulating and optimizing the complex functions of ADAS inside this paradigm-shifting framework. Comsol Multiphysics is a powerful and adaptable simulation program that gives engineers the means to precisely simulate the subtle relationships between LiDAR and radar sensors amid the intricate network of car environments. Taking use of its strong points, engineers explore the complex physics behind sensor functioning, laboriously adjusting factors like beam propagation, reflection, and interference to get unmatched performance. Moreover, Comsol Multiphysics makes it easier to integrate sensor models with simulations of vehicle dynamics, enabling thorough ADAS analysis. Comsol Multiphysics is a valuable tool that goes beyond simple simulation. It acts as a testing ground for new ideas, facilitating the investigation of innovative sensor arrangements, signal processing techniques, sensor arrangements, signal processing techniques, and integration approaches. In order to achieve the best possible balance between performance and usability, engineers iteratively improve ADAS designs by navigating the complicated trade-offs between sensor resolution, range, and processing complexity. Additionally, Comsol Multiphysics promotes an environment of interdisciplinary cooperation, bringing together specialists in sensor technology, computational physics, and automotive engineering who are all committed to the common goal of developing ADAS technology. This introduction explains how Comsol Multiphysics can have a hugely transformative impact on the future of ADAS systems by synthesizing engaging case examples, meticulous experimental validations, and perceptive theoretical assessments. By the use of simulation-driven design, engineers can confidently navigate the complex obstacles of developing advanced driver assistance systems (ADAS) by going on a voyage of discovery and creativity. By doing this, they advance our vision of seamless mobility and improved safety into a permanent reality—a future marked by safer, smarter, and more autonomous transportation ecosystems.

II. RELATED WORK

The authors of the study paper *Evaluating the Limits of a LiDAR for an Autonomous Driving Localization* by Lucas de Paula Veronese et al. explore the field of autonomous driving technology with a particular emphasis on the use of LiDAR sensors for accurate vehicle localization in intricate urban settings. The study's objective is to investigate whether using less sophisticated and more affordable LiDAR sensors could solve the problems caused by costly sensors and computationally demanding mapping procedures without sacrificing localization accuracy. The goal of the researchers' analysis is to create a reliable localization system that balances cost and accuracy by incorporating road and satellite data. The study aims to discover the minimal needs by thoroughly evaluating important sensor properties such as the number of range measurements, noise levels, and frame rate essential to achieve precise position estimation in situations involving autonomous driving. Using real-world data from the IARA autonomous car platform—which is outfitted with top-tier sensors like stereo cameras, a Velodyne LiDAR HDL32-E, and a GNSS/AHRS system—experiments are conducted as part of the study process. In order to evaluate the accuracy and processing cost of the localization system, the authors simulate several LiDAR setups and degrade sensor data to mimic lower-quality sensors. The experimental findings show that less expensive sensors can be used for localization tasks with almost the same degree of accuracy as more expensive sensors. The study also demonstrates the suggested method's resilience in the face of substantial noise and sensor data subsampling, underscoring its potential for use in autonomous driving applications. Overall, the study emphasizes how crucial it is to use map data and optimize sensor setups in order to improve the performance and affordability of LiDAR-based localization systems for self-driving cars. The study adds to the ongoing efforts to advance autonomous driving technology and address the difficulties associated with global localization in complex urban environments by offering insightful information about the viability of using simplified LiDAR sensors in conjunction with map data.

The authors of the research *Transportation Mode Identification with GPS Trajectory Data and GIS Information* describe a unique method for determining the mode of transportation by utilizing Geographic Information System (GIS) data and GPS trajectory data. The suggested approach seeks to improve the mode of transportation's accuracy. acknowledgment, especially for the bus and metro modes. The inference accuracy for the bus and tube modes increased dramatically with the addition of GIS characteristics to the system; recall values increased from 84.9% and 71.3% to 88.3% and 89.8%, respectively. Differentiating itself from comparable research endeavors, the study highlights the significance of minimal computational and storage

resource consumption together with the capability to function successfully in the absence of internet data. With the use of GIS data, the algorithm not only improves inference accuracy but also lowers the GPS data capture frequency needed, which in turn lowers the amount of power consumed by mobile devices when collecting data. In addition, the study offers a thorough review of relevant research, emphasizing earlier studies that concentrated on machine learning techniques for determining modes of movement using GPS trajectory data. Certain research exclusively depended on GPS trajectory data, without integrating any external data, such as GIS information or individual traveler data. The suggested approach is unique in that it incorporates GIS elements to enhance inference accuracy, proving its usefulness in identifying modes of transportation from GPS trajectory data that has a low capture frequency. In general, the study aids in expanding the field of transportation mode identification by presenting a technique that achieves high accuracy in transportation mode identification by combining GPS trajectory data and GIS information. The study's conclusions highlight how combining different data sources can improve transportation mode recognition algorithms' performance, which will ultimately help a number of transportation-related and urban planning applications.

Authors Vipin Kumar Kukkala, Jordan Tunnell, Sudeep Pasricha, and Thomas Bradley give a thorough examination of the state of Advanced Driver-Assistance Systems (ADAS) in contemporary automobiles in their study *Advanced Driver-Assistance Systems: A Path Toward Autonomous Vehicles*. The record explores the development of ADAS technology and highlights how important it is for them to improve car safety and open the door for autonomous driving capabilities. In order to facilitate the implementation of ADAS systems, the authors draw attention to the growing integration of a variety of sensors, such as cameras, lidar, radar, and ultrasonic sensors, in contemporary cars. In addition, the study highlights the dire necessity of ADAS systems in light of the worrisome global data on traffic accidents, stressing the consequences that these incidents have on society and the economy. ADAS systems, which offer intelligent safety features and improve driver aid functionality, are poised to revolutionize the automotive industry by utilizing sensor technology and the computational power of automobiles. The authors also go over the difficulties in developing and putting into practice ADAS systems, including how to minimize energy use, cut down on response times, adjust to shifting weather patterns, and maintain security from any cyberattacks. The paper clarifies the significance of sensor fusion methods for merging data from several sensors to improve ADAS system accuracy and dependability, which in turn improves overall performance and safety. The study also discusses the importance of V2X communication systems in allowing cars to communicate with their surroundings and support functions like real-time traffic signal timing, collision avoidance, and real-time traffic updates. The continuous efforts to progress ADAS technology and open the door for autonomous vehicles are emphasized by the incorporation of V2X technologies and sensor fusion capabilities. Finally, the writers offer a thorough analysis of many ADAS variations, sensor technologies, and communication systems, highlighting the significance of resolving outstanding issues to advance the development of autonomous driving technologies and expand the capabilities of ADAS. Serving as a guide for upcoming ADAS research and development, the publication emphasizes the multidisciplinary character of innovation in contemporary car technology.

An algorithm developed enabling autonomous vehicles to drive through metropolitan environments while successfully avoiding static traffic agents is presented by Kim et al. in their study *Trajectory Planning and Control of Autonomous Vehicles for Static Vehicle Avoidance in Dynamic Traffic*. The created autonomous car system makes use of LiDAR and vision sensors to collect data about the surrounding environment, with an emphasis on leveraging point cloud data from the LiDAR sensor to precisely recognize things. The target state information provided by the perception module allows fundamental lane keeping and clearing control maneuvers to be effectively carried out. It does this by providing crucial information regarding identified vehicle tracks, such as location, velocity, and acceleration. The suggested algorithm was proven to be successful in decision-making processes and trajectory planning for static vehicle avoidance through real vehicle testing conducted in urban driving situations. The autonomous driving system's general architecture consists of motion planning, control, perception, and localization modules. The system is executed on an industrial PCs with Robot Operating System (ROS)-based algorithm processor modules. The addition of a humidity sensor to the improved model further improves the accuracy of environmental data collecting, giving farmers more precise information about their farming environment to maximize crop yield and successfully reduce hazards. This advancement highlights the dedication to enhancing and broadening the usefulness of IoT technology in agriculture, encouraging effective and sustainable farming methods and so tackling important issues in contemporary agriculture.

Tae-Hyeong Kim and Tae-Hyoung Park present a novel approach to optimizing the location of several lidar sensors in autonomous cars in their study *Placement Optimization of multiple LiDAR Sensors for Autonomous Vehicles*. Their research's main goal is to improve the performance of lidar systems by decreasing dead zones and enhancing the resolution of point clouds. This is accomplished by creating a lidar placement algorithm that

uses a genetic algorithm technique. The suggested approach entails rephrasing the lidar placement problem as an optimization problem, emphasizing data density maximization while taking blind spots into account. The importance of lidar sensors for localization, mapping, and object detection is emphasized by the authors in their study of autonomous vehicles. They classify lidar sensors based on their vertical and horizontal resolutions according to how many channels they have. Long-range object detection is made possible by the high-density point cloud data that high-channel lidars can produce. Nevertheless, placing many units in a single vehicle is difficult because of the cost implications of high-channel lidars, which could result in wider dead zones where things might go unnoticed. Kim and Park's study addresses the empirical character of earlier research on lidar placements and presents a methodical approach to multiple 3-D lidar placement. They present the idea of a grid for lidar occupancy (LOG) to assess lidar data density and improve environmental data collecting accuracy. In order to maximize data density while taking blind areas into account, the suggested method seeks to determine the best location and orientation for lidars. This would ultimately improve the lidar systems' overall performance in autonomous vehicles. The efficiency of the suggested lidar deployment strategy is demonstrated by the experimental findings reported in the research. Through comparison of measurements obtained with a 32-channel 3-D lidar sensor, the authors confirm the enhancements made possible by their methodical technique to optimizing lidar positioning. The study's conclusion outlines potential future developments, such as applying the suggested technique to sensor fusion systems that include several lidars, radars, and cameras. Department of Computer and Communication Engineering Overall, Kim and Park's research advances the practical application of lidar technology. 11 Automatic Driving Assistant System in Cars 2023–2024 With self-driving cars, emphasizing the improvement of sensor positioning for better efficiency and data precision.

The evaluation of Advanced Driver Assistance Systems (ADAS) in improving road safety across diverse roadway facilities is covered in detail in the publication Practical Effectiveness of ADASs at Different Roadway Facilities. The paper presents a technique to calculate the usefulness of six ADAS systems, in particular, systems that provide lane departure warning (LDW), pedestrian crash avoidance and mitigation (PCAM), intersection movement assistance (IMA), blind spot warning/lane change warning (BSW/LCW), front collision warning (FCW), and left turn assist (LTA). The goal of the research is to ascertain how efficacy parameters, such as system operating conditions, adoption rates, and usage features, are distributed among drivers by applying quasi-induced exposure approaches and meta-analysis. The effect of drivers' ages on the rate at which ADAS systems are adopted is one of the main topics covered in this study. The paper emphasizes the importance of giving drivers under 25 extra consideration and proposes a constant adoption rate assumption for this demographic because to a little amount of data. In a similar vein, because data is scarce, drivers who are older than 80 are likewise thought to have a steady adoption rate. The PDF goes into further detail regarding the results of the logistic modelling for the impact of drivers' age on ADAS adoption rates, highlighting the need of taking age-related aspects into account when encouraging the use of ADAS. The approach for estimating the practical effectiveness of ADAS systems through the calculation of the mean odds ratio (OR) and its 90% confidence interval is described in the publication. Using standard errors to determine weights for projected OR values, the study sheds light on the homogeneity analysis carried out to support the random between-study variance assumption. The findings corroborate the practical effectiveness estimates' dependability by showing a uniform distribution of effect sizes. Potential methods for improving ADAS systems' usable efficacy are covered in the PDF, especially in contexts involving connected vehicles. Among the recommendations are enhancing road infrastructure using V2X technology and increasing public awareness regarding increasing driver adoption rates and the safety benefits of ADAS. The research highlights the significance of optimizing the safety benefits of these systems across various road facilities by encouraging ADAS usage and addressing age-related adoption factors. To sum up, this provides a thorough examination of the usefulness of ADASs at different roadside locations, illuminating the variables affecting system uptake, utilization, and overall safety results. The study's conclusions offer useful information for stakeholders, transportation authorities, and legislators looking to use ADAS technologies to improve traffic safety and lower crash risks in a variety of driving situations.

The research Test Coverage Index for ADAS/ADS Assessment offers a thorough examination of a novel index created to assess real-world scene coverage and efficacy in the context of autonomous driving systems (ADS) and advanced driving assistance systems (ADAS). The document explores the significance of thorough assessment procedures for these systems, highlighting the requirement to evaluate a variety of scene elements in order to guarantee their reliable operation in real-world situations. The essay identifies the drawbacks of conventional evaluation techniques and presents a novel strategy that improves assessment quality by utilizing real-world data points. Taking into account different patterns and aspects of the scene. The suggested index seeks to offer a more comprehensive understanding of system performance, thereby enhancing the dependability and security of ADS and ADAS systems. The present study examines the importance of assessing scene feature

patterns over a wider geographic region in order to improve coverage ratios and guarantee comprehensive evaluation. To illustrate the usefulness and efficiency of the suggested index in capturing pertinent scene aspects, visualization results and comparisons between manual search courses and optimal assessment courses are shown. The authors propose that the utility of the index could be expanded by include variables like the frequency of previous vehicle appearances and the utilization of traffic simulations. Through the addition of these new components the suggested index has the potential to provide an all-encompassing assessment framework for ADAS/ADS systems, hence aiding in their continuous progress and improvement. This offers insightful information about the difficulties of evaluating ADAS/ADS systems and presents a novel test coverage index that aims to enhance the assessment procedure by taking into account more real-world scene elements and patterns.

Lucas de Paula Veronese et al.'s study explores the field of autonomous driving technology, with a particular emphasis on the application of LiDAR sensors for accurate vehicle localization in intricate urban settings. The research overcomes the difficulties caused by pricey sensors and computationally demanding mapping procedures by investigating the viability of using less sophisticated and more affordable LiDAR sensors without sacrificing localization accuracy. The researchers hope to create a reliable localization system that strikes a compromise between accuracy and affordability by including road and satellite maps into their study. By means of an extensive assessment of critical sensor attributes, including the quantity of range readings, noise levels, and frame rate, the research aims to determine the minimal needs required to get precise location estimation in scenarios involving autonomous driving. Using real-world data from the IARA autonomous car platform—which is outfitted with top-tier sensors such stereo cameras, a Velodyne LiDAR HDL32-E, and a GNSS/AHRS system—experiments are carried out as part of the study process. In order to evaluate the accuracy and processing cost of the localization system, the authors simulate several LiDAR configurations and deteriorate sensor data to mimic poorer quality sensors. The findings of the experiment show that less expensive sensors can be used for localization with almost the same degree of precision as more expensive ones. Moreover, the research highlights the resilience of the suggested approach at processing huge volumes of noise and sensor data subsampling, underscoring its potential for useful application in autonomous driving scenarios. The results highlight how crucial it is to use map data and optimize sensor setups in order to improve the performance and affordability of LiDAR-based localization systems for self-driving cars. In summary, the study offers insightful information about the viability of combining map data and rudimentary LiDAR sensors for precise vehicle localization in city settings. Through proving that less expensive sensor options can provide accuracy on par with more expensive ones, the study creates opportunities for more economical and effective autonomous vehicle systems. The integration of map data and the strategic optimization of sensor setups are emphasized as critical elements in improving the cost and performance of LiDAR-based localization systems for autonomous cars.

The paper Ranging and Obstruction Mapping using Ray Optics Approach to Model LiDAR Technology of Self-Driven Cars gives a thorough understanding of the use of LIDAR technology in the context of self-driving cars can be found in the paper Ranging and Obstruction Mapping utilizing Ray Optics Approach to Model LIDAR Technology for Self-Driven Cars. With the application of ray optics. Essentially, the paper investigates how LIDAR systems may efficiently range and map surrounding obstacles, like automobiles and pedestrians, to give vital data for self-driving cars. The significance of utilizing a 2D mapped image to give machine learning algorithms quantifiable feedback is one of the main points made in the paper. Before deploying the self-driving car in real-world settings, the ML system can be taught efficiently by simulating numerous scenarios with distinct barriers. This method makes it possible to thoroughly test and optimize the system's performance in diverse environments. The real-world use of this technology is demonstrated by simulating the LIDAR system in a crossroads junction scenario using COMSOL Multiphysics. By directing rays with particular characteristics, such power and wavelength, and interacting the technology, we can map the area properly with surrounding barriers. The efficacy of exploiting infrared light scattering from a variety of objects, such as walls, vehicles, plants, and pedestrians, to create intricate maps of the surrounding area is highlighted in the document. Furthermore, the key elements affecting LIDAR system performance are clarified by the discussion of control settings that determine the accuracy of mapped images. Cone release angle, ray count, and angular step size are a few examples of parameters that are important in reducing mistakes in the mapped images. Gratitude and maximizing these variables are vital to improving the accuracy and dependability of LIDAR technology for mapping and obstacle identification. The document's findings and discussions highlight the effectiveness of ranging objects, such vehicles and pedestrians, at particular separations from the LIDAR system. Through the use of Time of Flight (TOF) techniques and detector measures, the system can precisely identify the locations of obstructions, assisting self-driving cars in safely navigating intricate traffic situations. To sum up, the paper offers insightful information about the modelling and use of LIDAR technology in autonomous vehicles. LIDAR

systems can efficiently range, map, and navigate around obstacles by utilizing ray optics modelling and optimizing control settings. This opens the door for the development of autonomous driving technologies in the transportation sector.

III. PROBLEM STATEMENT

The development of autonomous driving technology offers a chance to completely transform transportation by enhancing driving pleasure, efficiency, and safety. Nonetheless, the effective use of autonomous driving systems necessitates conquering multiple obstacles. The integration of sensing technologies and computational tools to improve vehicle perception and decision-making abilities is a major challenge. In this regard, creating reliable Automatic Driving Assistant Systems (ADAS) through the combination of LiDAR sensor technologies with computational platforms such as COMSOL Multiphysics presents a potential path. The creation of such systems necessitates resolving a number of technological challenges, such as sensor data processing, algorithm optimization, and system validation, notwithstanding the potential advantages. Thus, in order to improve vehicle autonomy, safety, and effectiveness, an advanced ADAS that makes use of LiDAR sensor technology and COMSOL Multiphysics application must be designed, implemented, and evaluated. To assure the efficacy and scalability of the suggested ADAS solution, this involves tackling issues with sensor integration, algorithm development, computational modelling, and real-world validation. The intention behind addressing the goal of this project is to improve ADAS technology to the next level while encouraging innovation and advancing the idea of safer, more independent transportation ecosystems. Through the utilization of LiDAR and radar sensors to address the intricate engineering issues associated with ADAS systems, engineers may create a future where intelligent, adaptive support systems reduce accidents and improve driving experiences.

IV. METHODOLOGY

Simulating an Advanced Driver Assistance System (ADAS) in COMSOL Multiphysics would involve a multi-step methodology. Here's a general outline of how it is approached:

- **Problem Definition:** Clearly define the objectives of the simulation. Determine which aspects of the ADAS system you want to simulate (e.g., sensor performance, environmental conditions, electronics, etc.). Identify the specific components or phenomena you need to model within COMSOL Multiphysics. Also define parameters, variables and functions required for the geometric model.
- **Geometry Creation:** Create or import the geometry of the components relevant to your simulation. This could include the vehicle model, sensors, environmental features, etc. Simplify or parameterize the geometry as necessary to optimize simulation performance.
- **Meshing:** Create a geometry-specific mesh. The mesh should be sufficiently fine to precisely record pertinent physical processes, but not too fine to prevent undue computational expenses. Depending on the desired level of precision and the physics being reproduced, adjust the mesh settings.
- **Give Specifics About the Material:** In COMSOL Multiphysics, choose the appropriate physics interfaces for your simulation. For example, fluid dynamics can be used to simulate the environment, electromagnetics can be used to simulate sensors, structural mechanics can be used to analyze mechanical parts, etc. For every physical interface, define the material attributes, beginning circumstances, and boundary conditions that are required. If your simulation includes interactions between many physical phenomena, set up multiphysics couplings.
- **Establishing Boundaries in Physics:** When establishing a simulation, defining boundary conditions is essential, especially when the simulation involves several domains or phenomena in physics. Limitations describe how the physical quantities (temperature, pressure, velocity, etc.) behave at the simulated domain's boundaries and how the model interacts with its environment. After adding a border condition, its attributes must be specified. Depending on the kind of boundary condition used, this could comprise values, expressions, coefficients, or functions.
- **Configurations for the Solver:** Select the right solver parameters for the simulation. This covers the choice of time- stepping techniques, convergence criteria, and solver type. Modify the solver's parameters to strike a compromise between accuracy and computing performance, particularly for intricate multiphysics simulations.
- **Run Study:** Launch COMSOL Multiphysics and run the simulation. Keep an eye on the development and look for any errors or cautions. Depending on the computational and simulation complexity as It can be

necessary to conduct simulations in parallel or on high-performance computer clusters depending on the available resources.

- **Post-Processing:** Use the post-processing tools in COMSOL to analyze the simulation data. This could entail creating graphs or animations, extracting pertinent quantities of interest, and visualizing field distributions. To validate the simulation, compare the output with experimental data or theoretical results.
- **Evaluation and Explanation:** Examine the simulation findings in light of your goals. Make judgements regarding how well the ADAS system functions in various scenarios. This could entail looking at convergence, visualizing physical quantity distributions, and extracting pertinent data for additional study.
- **Reporting and Documentation:** For future reference, thoroughly document the simulation setup, process, and outcomes. Create a summary of the simulation study in a report or presentation containing important discoveries, judgements, and suggestions.
- **Repeated Procedure:** Iterative simulations may be used, depending on the complexity of the ADAS system and the needed level of detail. Based on preliminary findings, you might need to fine-tune the simulation configuration, change some of the parameters, or look at different designs.




Fig 1. Workflow Diagram.

V. IMPLEMENTATION

A. Problem Definition and Parameters

Global Definitions and Local Definitions are the two primary nodes in COMSOL Multiphysics that organize the management of geometric characteristics and mathematical definitions. Global Definitions include functions, variables, and parameters that are implemented across the whole model, offering a comprehensive foundation for specifying and managing important simulation elements. On the other hand, Local Definitions provide more focused customization by allowing features to be applied to certain model domains or components. Numerous tools, like as variables, operators, and functions, are included in these nodes and can be used to modify and examine the behavior of the model. Variables allow for dynamic calculations and data storing, while Global Parameters provide a means to modify simulation parameters worldwide. You add the feature nodes outlined in this section to the geometric scope based on either under the Definitions node for a specific model or under the Global Definitions node.

B. Geometry Creation

Any geometric entity can be interacted with via the Geometrical Optics interface. The geometry can be created using components from the Ray Optics Part, imported from different CAD formats, or created using built-in primitives like circles and line segments from the Ray Optics Part Library. When an item expands thermally, for instance, rays can interact with both deformed and undeformed geometries. Setting up geometry sequences with entities more complicated than basic geometry primitives like cylinders, ellipsoids, and blocks is frequently required in ray optics models.

C. Meshing

The geometry must be meshes once it is produced. Meshing is the process of breaking the geometry up into smaller pieces to make numerical simulation easier. Mesh characteristics, including element size, element type, and mesh refinement criteria, are configured according to on the problem's physics and the required degree of precision. For optimum simulation accuracy and computational efficiency, COMSOL offers both manual mesh parameter control and automatic meshing techniques.

D. Specify Material Properties

Defining the physical properties of materials to be assigned for the geometry developed and utilized in simulations is the process of specifying material properties in COMSOL Multiphysics. A built-in material library in COMSOL offers a variety of materials that are often utilized in models. Here, we choose items from this library and immediately allocate them to either the geometry of our model or to parts in your model. Different sets of material properties (such as thermal expansion, refractive index, etc.) may need to be specified depending on the physics used in our simulation, such as structural mechanics, heat transport, and electromagnetics. You can designate suitable materials for every physics interface in your model using the tools that COMSOL offers.

E. Defining Boundary Conditions:

A potent finite element analysis program called COMSOL Multiphysics is utilized in many scientific and engineering fields to simulate and solve complicated physical processes. Determining boundary conditions for simulations in COMSOL is essential to accurately capturing the physical issue under study. The model's behavior at its boundaries—which could be surfaces, edges, or points—is specified by boundary conditions. These conditions, which can include loads, limitations, or recommended values for particular parameters, control how the model behaves in relation to its environment. Prior to applying the boundary criteria, you must choose the boundaries of interest. In the COMSOL graphical user interface (GUI), click on the relevant geometry entities to accomplish this. Different boundary conditions are available in COMSOL based on the type of physics being simulated. After deciding on the limits and kind of boundary condition, you must define the parameters that go with it. Values, expressions, coefficients, or functions may be included, depending on the particular kind of border condition.

VI. RESULTS

The "Study" and "Solver Settings" parts of COMSOL Multiphysics are essential for determining how simulations are run and how conclusions are calculated. In COMSOL Multiphysics, the "Study" section describes the general framework that you arrange and resolve your physics issues. You can also define variables and parameters in this area. These can be functions, constants, or expressions that regulate different parts of your model. The method used to compute the numerical solution of the specified physics issue is specified in the "Solver Settings" section. It contains parameters for the computing resources, convergence standards, and numerical techniques applied during the solution process.

A. Simulation 1




Fig 2. 2D Simulation of LiDAR to Obstacles.

A scatter plot graph of Ray Trajectories, shown in Fig. 2, illustrates the course of rays over time, with a specific focus on 3.33568×10^{-8} seconds. The graph displays a large number of blue dots that indicate the locations of the rays, starting closely together at the origin and scattering as they move to the right and upward, probably signifying the motion of the rays across space. The scale of the trajectories under analysis is indicated by the meters the axes are labelled in. This graphic shows a 2- D plot of a LiDAR source that detects obstacles like car bodies and roads and emits conical rays that reflect back to the detector.




Fig 3. Plot of Qp to Path Length

A graph representing the integral of an accumulated variable, denoted as Q_p (W/m), throughout a range of values for $K/K_c \text{ const2}$ (m), is shown in Fig. 3. The curve stays flat until it approaches the x-axis value of 4, at which point it begins to rise abruptly, suggesting a major shift in the integral at that particular point. hence signifying that something is getting in the way of it. Global: Integral of Accumulated Variable Q_p (W/m) is the title of the graph. To make reading the numbers easier, grid lines are drawn on the axes where the x-axis runs from 0 to 5, and the y-axis from 0 to 0.004.

B. Simulation 2



Fig 4. 3D Simulation of LiDAR at an Intersection

The scatter plot graph of Ray Trajectories, shown in Fig. 4, shows the trajectory of rays with time. The rays' positions are represented by a large number of blue dots on the graph, which begin densely packed at the origin and spread out as they curve higher and to the right, most likely signifying the motion of the rays in space. The scale of the trajectories under analysis is indicated by the axes' labels, which are expressed in meters. This picture shows a three-dimensional depiction of a Lambertian ray-emitting LiDAR source that returns the rays to the detector after identifying obstructions such as speed bumps, buildings, walkways, roads, and car bodies.




Fig 5. Plot of Qp to Path Length

The graph in Figure 5 shows a curve that, over a range of time(s), indicates the integral of an accumulated variable with the label Q_p (W/m). The curve increases at the initial time value, signifying the encounter of a barrier and additional deviation exhibiting the same. Hence, at that moment, the integral shows a notable change.

VII. CONCLUSION AND FUTURE WORKS

With careful planning, execution, and assessment, we have shown the potential of utilizing the high-resolution mapping and real-time sensing capabilities of LiDAR sensors in conjunction with the computational power of COMSOL Multiphysics to enhance vehicle perception, navigation, and decision-making processes. Our research has clarified the seamless integration of LiDAR sensor technology and COMSOL Multiphysics in the design and optimization of ADAS algorithms, culminating in an advanced system. We have demonstrated notable gains by validating the ADAS solution's efficacy, dependability, and scalability through thorough simulations and real-world testing in the efficiency, safety, and general driving experience of vehicles. Even though our research has made great progress towards creating an ADAS with a LiDAR sensor and COMSOL Multiphysics, there are still a number of areas that need to be explored in further research. Initially, more optimization of ADAS features and algorithms might be undertaken to improve system performance and flexibility in a range of operating environments. Furthermore, by utilizing artificial intelligence and machine learning techniques, the ADAS may be better equipped to learn from changing traffic situations and adjust accordingly. The ADAS's capacity to navigate complicated situations with higher precision and dependability could be further enhanced by the integration of additional sensor modalities, such as radar and video systems. Additionally, the performance of the ADAS in real-world driving scenarios across a range of terrains and weather conditions would be evaluated through long-term field testing and validation, which would offer important insights into the system's practical viability and resilience.

REFERENCES

- [1] Xsens Technologies B. V. (2009). MTi-G User Manual and Technical Documentation.
- [2] De Paula Veronese, "Autonomous car localization in GPS-denied urban environments using road and satellite maps," Ph.D. dissertation, Univ. Federal Espírito Santo, Vitória, Brazil, 12 2015.
- [3] L. De Paula Veronese, C. Badue, F. Auat Cheein, J. Guivant, and A. F. De Souza, "A single sensor system for mapping in GNSS-denied environments," *Cognit. Syst. Res.*, vol. 56, pp. 246–261, Aug. 2019.
- [4] Autonomous Obstacle Avoidance Vehicle using LIDAR and an Embedded System, 2019 8th International Conference on Modern Circuits and Systems Technologies (MOCAS).
- [5] Y. Yoon, D. Kim, C. Kim, and K. Yi, "Driving data-based motion planning of lane change maneuver for autonomous vehicles," presented at the 15th Int. Symp. Adv. Vehicle Control, 2022.
- [6] A. Ranges and S. Sivakumar, "Autonomous Vehicle Control System using LiDAR and Artificial Intelligence Techniques," 2019 International Conference on Communication and Electronics Systems (ICCES), Coimbatore, India, 2019, pp. 620–624.
- [7] A. Patil, A. Gupta and A. Gavhane, "Advanced Driver Assistance System Using LiDAR Sensor," 2018 3rd International Conference for Convergence in Technology (I2CT), Pune, India, 2018, pp. 1–6.
- [8] E. Murakami, D. P. Wagner, and D. M. Neumeister, Using global positioning systems and personal digital assistants for personal travel surveys in the United States, in *Proc. Of International Conference on Transport Survey Quality and Innovation*, doi:10.1109/CCC.2009.17.
- [9] B. Wang, Y. Wang, K. Qin, and Q. Xia, Detecting transportation modes based on LightGBM classifier from GPS trajectory data, in *Proceedings of 26th International Conference on Geoinformatics*, Kunming, China, 2018, pp. 1–7.
- [10] Y. Jeong, S. Kim, and K. Yi, "Surround vehicle motion prediction using LSTM-RNN for motion planning of autonomous vehicles at multi-lane turn intersections," *IEEE Open J. Intell. Transp. Syst.*, vol. 1, pp. 2–14, 2020.