

Senior Citizen Care using Micro Expression Analysis on Live Elderly Video (MEA-LEV)

S.Rajasekaran¹ and Dr.G.Kousalya²

¹Assistant Professor, Department of Information Technology, KGISL Institute of Technology, Coimbatore, Tamilnadu, India
Email: proffraja@gmail.com

²Professor, Department of Computer Science and Engineering, Coimbatore Institute of Technology, Coimbatore, Tamilnadu, India
Email: kousalya.g@cit.edu.in

Abstract—The application of Collective Intelligence (CI) conception has produced Senior citizens require treatment and support to lead a healthier life without concern and distress. Old age is a sensible level . Failure to become conscious of the shifting behavioural trends of seniors at home leads to child violence. This work addresses the issues surrounding the lives of older people that find major mental and emotional difficulties much more difficult. Care judgments should be based on a sound and rational appraisal of the needs of each senior in terms of care, not on the ability to be supportive or guilty emotionally motivated. The practical capacities of the elder must be established individually and systematically in order to reach a practical awareness of the types of treatment they may receive. Any capability of the elder which is impaired will require treatment, depending on the vitality of each skill in conducting day-to-day tasks and retaining one's own welfare. If the welfare needs are not fulfilled, the amount of harm the aged person is subjected and the kinds of treatment that will restore the wellbeing of the elderly must be decided. Furthermore, any capacities which will in the near future be affected as a result of the progressive state of an Elder shall be therefore established and included in a care plan. During these inquiries, we report the live video monitoring of elders – a fast and rigorous tool for elderly micro expression recognition that analyses the subtle gestures of different behavioural trends in various areas, using distinct absolute frame variants and the key component analysis classificatory (PCA) in order to predict the most prominent facial and corpuscopol changes. The research indicates that automatic detection of the micro-expression produces better (97.34% True Positive and 0.02% False Positive) outcomes by using time and a fast learning algorithm.

Index Terms— Facial analysis; Image Analysis; Video Analysis; Expression Analysis.

I. INTRODUCTION

A significant decision a family needs to make is if the ageing parents or family members (e.g. grandparents) are cared for if these elders can no longer survive on their own. This nuanced and deeply burdened topic is answered in various ways by families. Any families find means of supplying older people with adequate resources so that they can stay at home comfortably. Some families transfer their elderly to provide for themselves. Other families still see the right option for those interested with putting their aged in a care home. It is very difficult to provide suitable and cost-effective senior care and resources. The time-consuming procedure that also includes

consulting with medical and elderly experts decides just what form of treatment will ideally suit the needs of elderly people. It also takes time to find cost-effective acceptable and trustworthy treatment choices. Various kinds of treatment are accessible in multiple areas, with broad differences in prices and quality. Recognizing and discovering adequate and accessible local Elderly Care services will become overwhelming for all participants in full-time jobs. Even managers and employees will be impacted if the elderly care planning burden affects the productivity of clinicians at work.

Elderliness is clinical nursing, also referred to as elder living, intended to fulfil the demands and needs of the elderly at different levels. Elderly care is also a relatively broad concept, as it covers everything from aided living and health services to day care, residential care or even hospice care for adults. While ageing itself is not a cause to seek elderly care, the numerous physical ailments and disabilities that follow old age typically contribute to debates regarding the treatment of elderly people. Elderly people should not necessarily need to afford housing in their present years. Aged care is also not a complete. Elder treatment, however, is also a concern when a loved one starts to have issues with day-to-day tasks (DLs), both healthy and self-employed. Cooking, washing, buying, dressing, bathing, driving, medication etc can require ADLs.

A general deterioration in health is typically the reason to implement elderly treatment, since it may imply a drop in the ability to perform everyday tasks individually. For example, dementia, which typically happens progressively, will make it very difficult for an individual who previously knew to take medicine on time. If your eyes malfunction, your loved one might lose the ability to navigate about your house comfortably, or progressive arthritis will make it difficult for him or her to into and out of the water. The need for elderly treatment can also take place rapidly, like in the case of a fractured spine or a stroke in a modern years where the emotional and/or physical impact is already encountered. However it is continuous that elderly treatment will be required if physical, neurological, or mental conditions hamper the capacity to conduct day-to-day tasks safely.

Severe health issues also arise as people grow older and cannot do much of the jobs they might once do. They can be delicate, more rigid, and less resilient in their bodies. Severe diseases can lead to take benefit and the emergence of new diseases.

Physical conditions linked to illness may be easily identified or subtler. Senior individuals with glaucoma do not look visually affected, for instance, but vision loss may lead to injuries and declines that can have a major effect on their health and also well. Since you have not reported any physical disability, the cousin does not mean that he or she needs treatment. A full physical assessment (including vision and hearing) is also a regular feature of an overall health plan. Cognitive challenges – While behavioural issues may be predicted when your beloved one gets older, at least in their tiniest form, developmental disabilities can affect the ability to function in safety and self-reliance. Cognitive disorders can cause cognitive issues, communication problems, judgement challenges, and emotional difficulties to mention a few. Mild impairment cannot require treatment of the aged, although it is important to treat any form of advanced dementia causing significant safety issues.

Emotional problems declining wellbeing, losing a partner, struggling to do activities once appreciated or feelings of value all can lead to emotional challenges for their beloved one. There are many aspects in which relational difficulties are manifest. For starters, your beloved may be retired socially, moody or irritable, or even have thoughts of suicide. Some older adults doubt that mental issues occur or are serious, which make the close monitoring of doctors and family members much more important.

This paper is intended as a reference for families in the procurement and location of suitable elder care facilities to address the numerous problems. The paper starts by explaining numerous problems that an elder might need treatment. It also addresses recommendations to choose a reasonable standard of treatment for a single elderly individual. The follows define the different forms of elderly treatment, which are commonly accessible and follow a review of the attributes of care facilities or care services that must be considered when assessing them. The paper continues with the discourse on problems which may occur during the transition to elderly treatment for households and seniors.

II. RELATED WORKS

M. Xi et al., Over the years, the ageing demographic and hospitals have been big concerns. Instead of primary care crossover facilities, the primary type of information provision has been. For overlap healthcare systems, a type of situation model (SBRM) is presented in this work. The model is often used to construct a DSL and a test framework. The parameters in our Model are WHO, what Situations are to do what Procedures and what RULES are to be met. In the actual case of the MEH convergence provider (Medical, Aged, Healthcare), we review our model. SBRM better serves our programmes and highlights reliability, quality and recyclability.

Mucchiani, C., This paper describes the tasks a sensor node might perform to support the autonomy of elderly people in a stable community residence and a set of measures that confirm the top ranking tasks. Previous installations were only known to be an autonomous robot base, tests were carried out with the assistance of hiking and oxygenation by the provision of fluids, all accompanied by an assessing pain. Present experiments have tested the feasibility of the mobile surveillance applications by applying to the same mobile manipulator a new low-cost telescopic automated arm, with forms of contact between the human and the robot being studied by communicating with elderly. Two observers as well as the article studies of older adults have assessed all movements to the All Integrated Treatment (PACE) Centre. Earlier work is discussed on Elderly Robotics. The findings and architecture recommendations of mobile exploitation implementations are discussed. The future research requires creating a new handheld swindler that can execute the activities under review in a more independent and effective manner.

O. A. Ibrahim, Non-wearable sensors are a potential alternative to the tracking of elderly patients to improve healthcare and minimise costs. Any resident activities may be associated with early symptoms of sickness with irregular sensors units. We deliver an unmonitored system for identifying irregular sensor patterns dependent on the sequence of clusters. We use a standard 30-days timeframe to construct an elderly person's simple model by grouping the existing operation sequences. Each cluster is a daily occurrence that takes place over the majority of (average days and correlates to normal routines. When there are less regular tasks in the new day, we mark the day as irregular and a likely sign of early sickness. A preliminary review was carried out of information gathered from our telemedicine at the TigerPlace elderly centre which promotes elderly care in the location (EHR). We met the average irregular event forecast of 0.75 on a pilot detector sample from triple tenants with a maximum of 1902 days.

M. Fischer, Appropriate strategies are needed to raise the quality of living of all patients and senior citizens throughout order to properly care for an increasingly aged population. Therefore it is critically important to obtain patient records and knowledge on use to improve these solutions. To allow smooth incorporation for use in hospitals and pension workplaces or private homes, such technical aids must be used and integrated easily, beforehand. For this reason we present a sensor mat which can be placed below the bed sheet for simple use and senses urinary and bed occupation by clinicians. It can then be used easily and confidently by nurses or caregivers. The focus of this article is on the external unit consisting of peripheral data acquisition and processing equipment as well as a proprietary radio frequency or wireless Internet communication module for wireless communication. Wetness is observed when the resistance of broken electrodes is measured when the capacitance of certain electrodes is calculated by the occupancy status. Three regular Battery packs can power the sensors, and the sensor mat can be worked for up to 2.8 years per day if its battery capacity is 1500 mAh. The electronic control and alarm system is introduced in this paper and is defined by sensory data gathered in a series of experiments. The provided detector mat is an excellent method to be used in different situations due to its low channel capacity and upkeep service, in addition to cleaning.

III. RESEARCH METHODOLOGY

A. Micro Expression Analysis applied video analytics to care elderly person

Micro-expression unwilling and brief facial gestures which show true emotions maintain useful information for contexts from protection and interviews to media review. It appears in different parts of the face, lasts a fraction of a second and is ubiquitous across communities. Micro pressure is highly delicate and virtually difficult to suppress or counterfeit in comparison to quantitative such as broad smiles and frowns. Because micro-expressions can show feelings which people can attempt and conceal, micro-expressions identifying them can help doctor forensics and mission capabilities by offering clues to anticipate and detect circumstances of threat. This newsletter, the latest study from the SEI Innovative New center, outlines our work to create a revolutionary software platform to detect micro signals in practically real time. Present methods to micro face detection use handmade functionality and consider each frame buffer as an individual file. This is a delicate, sluggish and limited-precision approach.

Genital gestures manifest feelings as well as related acts, attitudes and many valuable details in order to benefit sectors such as law enforcement, forensics etc. Obtained from data content creation, text analytics and other sophisticated solutions, video analytics can be accomplished. The foundation of video analytics is phrases such as "proud and happy," "incredibly sad," "upset and angry," "scared shitless," "totally surprised" and "completely neutral."




Fig 1: Elderly care by PCA –MEAAnalysis Flow of diagram

Our application utilizes machine-learning functions that treat the entire face as a platform, as opposed to instruments that use conventional manufactured features or techniques which seek predetermined areas of the face for facial action device. For this venture, one obstacle they encountered was to locate a repository with detailed data that confirms the ground reality. Few current datasets capture the concealed responses of individuals and still less capture them in the same quality (e.g., video resolution). They chose the Chinese Encyclopedia of Sciences (CASME) repository for this experiment which showed a series of youtube videos and were about to demonstrate no feeling. Five emotion groups are in the directory: pleasure, disappointment, disgust, suppression, and more. We normalized the videos by way of encoding to cope with differences in video length periods for various speech levels.

Our technique uses two neuronal (CNNs) concentration grids: a CNN on Competitions faces, in space that's been post, and a spatial CNN to test modifications over the period. They feed pre portioned image data into CNNs that collect spatial features using both pixel and optical flux data. The CNNs establish machine-learned characteristics and combine all video feeds into a special classification that determines the sentiment of the micro speech. Our approach to segments and sub identification is effective and on a level playing field.

Our job is a mission-practical concept underlying everything we do. We were researching continually improve and refine our outcomes in real life, including polygraph testing, medium study, manipulation and comment traumatic stress identification. Capable of treating recordings for the long term. It is important to be capable of managing inputs like extended videos as well as finally, real time details for the device we have to be able. Combine identification and identification. They aspire for precision in both micro-expression identification and recognition. At the moment we are focused on micro-expressions recognition. Micro expression identification is particularly useful for long run images, in which the presence of micro expressions can be signalled by subtle adjustments.

For better results, move to GPUs. By taking benefits of strong performance computer systems, we can speed up our tool performance. Integrate with the other modes to make emotional recognition more effective. By integrating identification by microexpression with observing other physiological data (e.g. cardiac rates), we can obtain a more comprehensive image of the psychological response of a subject. Spatially, our goal was to minimise the error when seeking the perfect fit for the points swarm, i.e. to minimise the distance from each point to the most fit line. This equates to optimising the variability of the scores even arithmetically $t_{i,1}$; In the correct triangle, note from mathematics that perhaps the cosine of angles is the ratio of the neighbour to the hypotenuse. However the coefficient of an angle is often used to describe the input image in linear algebra. Call for mathematics

Principal Component Analysis or PCA is a features extraction approach which is commonly used to minimise broad data set measurements by converting a wide variety of parameters, which also retains the bulk of the knowledge in a wide range.

Naturally, the drop in the number of different data will cost the precision, but a limited amount of accuracy will be the trick to minimise dimensionality. Since the discovery and viewing of smaller data sets are much simpler and quicker to test data for machine-learning applications without international variables. More precisely the reason why standardisation before PCA is important is because PCA is very susceptible to variances of the initial variables. In other words, if the original variables are somewhat different, certain variables with a greater range will overpower those of a small range (for example, variable varying from 0 to 100 will dominate the broader range of a variable between 0 and 1), resulting in skewed outcomes. This can then be avoided by translating the data into equivalent sizes.

$$\begin{aligned}\cos \theta &= \frac{\text{adjacent length}}{\text{hypotenuse}} = \frac{t_{i,1}}{\|x_i\|} \text{ and also } \cos \theta = \frac{x'_i p_1}{\|x_i\| \|p_1\|} \\ \frac{t_{i,1}}{\|x_i\|} &= \frac{x'_i p_1}{\|x_i\| \|p_1\|} \\ t_{i,1} &= x'_i p_1 \\ (1 \times 1) &= (1 \times K)(K \times 1)\end{aligned}$$

where $\|x_i\|$ Specifies the embedded variable length and the path vector size, p_1 is 1.0, by definition.

$t_{i,1} = x_{i,1} p_{1,1}$ is a linear mixture

$$t_{i,1} = x_{i,1} p_{1,1} + x_{i,2} p_{2,1} + \dots + x_{i,k} p_{k,1} + \dots + x_{i,K} p_{K,1}$$

Therefore $t_{i,1}$ is the performance value for a first element measurement and is a linear blend of the i th data row, $x_{i,1}$ and $p_{k,1}$ matrix path. Note that in the joint distribution there are K concepts: every K element leads to a significant ranking.

The secondary score value can be determined in a comparable pattern for the $t_{i,1}$ assertion:

$$t_{i,2} = x_{i,1} p_{1,2} + x_{i,2} p_{2,2} + \dots + x_{i,k} p_{k,2} + \dots + x_{i,K} p_{K,2}$$

And so forth for components three and following. For the provided inspiration, we can efficiently write in mathematical form:

$$\begin{aligned}t'_i &= x'_i P \\ (1 \times A) &= (1 \times K)(K \times A)\end{aligned}$$

that, for that instance, measures all A of certain in one go. This is precisely what we inferred from the $x'_i P$ temperature readings in the room in the previous case.

IV. EXPERIMENTS AND RESULTS AND DISCUSSIONS

Matrix computation covariance computation for video analysis ,the objective of this step is to consider how the source original data differs from end to mean, while in other phrases, and seeing how the connection occurs among them. Since variables are often heavily correlated and provide unnecessary features. Thus, we calculate the linear combination in order to define these associations. The covariance is a $x'_i P$ linear matrix (where p is the number of aspects) in which covariances are reported in the dependent data connected with all possible pairs. For instance, the correlation coefficient is three parameter matrix for a three dimensional set of data with three parameters (x, y, z) from:

$$\begin{bmatrix} \text{Cov}(x, x) & \text{Cov}(x, y) & \text{Cov}(x, z) \\ \text{Cov}(y, x) & \text{Cov}(y, y) & \text{Cov}(y, z) \\ \text{Cov}(z, x) & \text{Cov}(z, y) & \text{Cov}(z, z) \end{bmatrix}$$

Because of the correlation coefficients of a vector with itself ($\text{Cov}(a,a)=\text{Var}(a)$), we really have the differences of each interval scale in the real axis (top right to bottom right). As the coefficient of variation is commuta and COW), b and $= \text{Cov } b(a)$, the values of Covariance matrix correspond as opposed to the chief diagonal, this implies that top and bottom diagonal sections of two matures should be equivalent.

The next step calculate the eigenvectors and one cov matrix of the principal components to classify, Eigenvectors and eigenfunctions are the linear process algebra which we must calculate from the equation of correlation coefficients to evaluate the major elements of the results. Let us consider what they mean by the key components until we get to the clarification of these terms.



Fig 2: Facial analysis using PCA_MEA for elderly care

Main aspects are modern variables built to be linear or original variables mixtures. The control characters (i.e. primary variables) are highly correlated, so as to push much of the data into first elements inside the original variables. This concept is ten component data, which gives you ten key components, but PCA attempts to position as much detail as possible in the first component then as much rest in the second and so forth, until anything similar is seen in the following screen plot.




Fig 3: Elderly care analysis each frame with various time duration using PCA-MEA

An significant point to recognise here is that, because the main factors influencing are formed as covariance matrix of the estimated parameters, they are less subject to interpretation and have no particular significance. The main components are spatially the data path which describes a maximum degree of variation, i.e. lines which capture much of the required data. The relation among variability and knowledge here is that the higher the variance taken out by a line, the more data it holds, the greater the diffusion of the data sets in it and the greater the diffusion across a line.

To put all this clearly, consider the key elements only as new axes that include the best angle for viewing and analysing the data in order to better explain the variations between observations. The tests of the model showed us very good precision: after 340 periods, 97.32 percent of proper grading samples. The only downside was that I had to wait 12 minutes before the close of 14 eras (looking at the fact that I had a very small number of photos for training). I actually wondered about this: what if in fewer times it can produce almost the same likely result. We sought to construct two sections for this purpose. The first one exposes the reliance on the number of iterations on the assessment results. Extra data collection of 400 images is used to measure the precision of the assessment. The second plot illustrates the reliance on the amount of times during the research on their consistency and detection rate. On the first drawing it is obvious that after 12 epochs, the high precision (97.32 percent) is attained. The exactness of the plot does not increase at corresponding times (and also reduces in 20–35 intervals).

The second diagram illustrates the precision and reliability junction. The precision of testing sows the model's potential to generalise new information. The consists of a rigid comprises only the information which the template never uses throughout testing. They are potentially in an overlap scenario, that is the model essentially starts memorising the data if their training examples precision ('sad') tends to increase when your testing data precision ("happysad") worsens. This implies that the system will deliver the same outcome after the 12th epoch, but it won't be different. This model is therefore adequate in 12 epochs for preparation.

TABLE I. COMPARED WITH EXISTING ELDERLY MICRO EXPRESSION ANALYSIS BY VARIOUS VIDEO DURATION USING THE PROPOSED VIDEO DC-DBN

Methods	Video File Taken for Analysis			Classification True Positive Ratio(%)			Classification False Positive Detected			False Positive Ratio (%)		
M. Fischer	704	612	502	93.36	93.72	94.36	50	41	30	.06	.06	.05
O. A. Ibrahim	692	597	496	91.77	91.42	93.23	62	56	36	.08	.08	.06
Proposed PCA-MEA	735	641	521	97.48	98.16	97.93	19	12	11	.02	.01	.02

Number of video file taken 06 in minute's playable duration: 754

Number of video file taken 05 in minute's playable duration: 653

Number of video file taken 13 in minute's playable duration: 532

V. CONCLUSION

The most critical phases of a man's life are puberty, infancy, youth, maturity, and old age. Many of these processes have challenges and problems of their own. Every level increases the physical strength and the mental health deteriorates. More than 80 million older people are considered to be in India. As age increases, many medical complications typically occur, several of the specific diseases that are known include blood pressure, diabetes, heart health problems, arthritis. Elderly people with developmental disabilities are experiencing serious changes in behaviour; love and consideration are important at this moment. When unsupervised, the bulk of them are disproportionately dejected and unsustainable; some of them have become aggressive. Whereas all of us recognize that ageing is a normal development and has its own deficiencies, more of us prefer to forget this and turn to an alarming strategy.

REFERENCES

- [1] M. Xi et al., "A Scenario-Based Requirement Model for Crossover Healthcare Service," 2019 IEEE World Congress on Services (SERVICES), Milan, Italy, 2019, pp. 252-259, doi: 10.1109/SERVICES.2019.00075.
- [2] Mucchiani, C., Cacchione, P., Torres, W. et al. Exploring Low-Cost Mobile Manipulation for Elder Care Within a Community Based Setting. J Intell Robot Syst 98, 59–70 (2020). <https://doi.org/10.1007/s10846-019-01041-x>

- [3] O. A. Ibrahim, J. Keller and M. Popescu, "An Unsupervised Framework for Detecting Early Signs of Illness in Eldercare," 2019 IEEE International Conference on Bioinformatics and Biomedicine (BIBM), San Diego, CA, USA, 2019, pp. 1043-1050, doi: 10.1109/BIBM47256.2019.8983010.
- [4] M. Fischer, M. Renzler and T. Ussmueller, "Development of a Smart Bed Insert for Detection of Incontinence and Occupation in Elder Care," in IEEE Access, vol. 7, pp. 118498-118508, 2019, doi: 10.1109/ACCESS.2019.2931041.
- [5] ReneshBedre.(2020, July 29). reneshbedre/bioinfokit: Bioinformatics data analysis and visualization toolkit (Version v0.9). Zenodo. <http://doi.org/10.5281/zenodo.3965241>
- [6] J. Ueda and K. Okajima, "Face morphing using average face for subtle expression recognition," 2019 11th International Symposium on Image and Signal Processing and Analysis (ISPA), Dubrovnik, Croatia, 2019, pp. 187-192, doi: 10.1109/ISPA.2019.8868931.
- [7] G. Tharshini et al., "Expression neutralization based algorithm for expression-invariant face recognition for single training sample problem," 2017 IEEE International Conference on Industrial and Information Systems (ICIIS), Peradeniya, 2017, pp. 1-6, doi: 10.1109/ICIINFS.2017.8300370.
- [8] M. B. S. Divya and N. B. Prajwala, "Facial Expression Recognition by Calculating Euclidian Distance for Eigen Faces Using PCA," 2018 International Conference on Communication and Signal Processing (ICCSP), Chennai, 2018, pp. 0244-0248, doi: 10.1109/ICCSP.2018.8524332.
- [9] Y. Wang, H. Yu, J. Dong, M. Jian and H. Liu, "Cascade support vector regression-based facial expression-aware face frontalization," 2017 IEEE International Conference on Image Processing (ICIP), Beijing, 2017, pp. 2831-2835, doi: 10.1109/ICIP.2017.8296799.
- [10] H. Ni and J. Liu, "3D Face Dynamic Expression Synthesis System Based on DFFD," 2019 IEEE 3rd Information Technology, Networking, Electronic and Automation Control Conference (ITNEC), Chengdu, China, 2019, pp. 1125-1128, doi: 10.1109/ITNEC.2019.8729434.
- [11] C. M. Grewe, G. Le Roux, S. Pilz and S. Zachow, "Spotting the Details: The Various Facets of Facial Expressions," 2018 13th IEEE International Conference on Automatic Face & Gesture Recognition (FG 2018), Xi'an, 2018, pp. 286-293, doi: 10.1109/FG.2018.00049.
- [12] M. Azimi, "Effects of Facial Mood Expressions on Face Biometric Recognition System's Reliability," 2018 1st International Conference on Advanced Research in Engineering Sciences (ARES), Dubai, United Arab Emirates, 2018, pp. 1-5, doi: 10.1109/AREX.2018.8723292.
- [13] H. Sadeghi and A. Raie, "Approximated Chi-square distance for histogram matching in facial image analysis: Face and expression recognition," 2017 10th Iranian Conference on Machine Vision and Image Processing (MVIP), Isfahan, 2017, pp. 188-191, doi: 10.1109/IranianMVIP.2017.8342346.
- [14] V. Singh Tomar, N. Gupta and U. Singh, "Expressions Recognition Based on Human Face," 2019 3rd International Conference on Computing Methodologies and Communication (ICCMC), Erode, India, 2019, pp. 590-595, doi: 10.1109/ICCMC.2019.8819714.
- [15] P. P. Mankar, P. R. Hajare, P. T. Agarkar, S. G. Bondre and N. P. Giradkar, "An efficient Deep Learning of scarce and diverse faces for Face recognition," 2019 9th International Conference on Emerging Trends in Engineering and Technology - Signal and Information Processing (ICETET-SIP-19), Nagpur, India, 2019, pp. 1-6, doi: 10.1109/ICETET-SIP-1946815.2019.9092324.
- [16] P. Nair and S. V., "Facial Expression Analysis for Distress Detection," 2018 Second International Conference on Electronics, Communication and Aerospace Technology (ICECA), Coimbatore, 2018, pp. 1652-1655, doi: 10.1109/ICECA.2018.8474761.
- [17] T. B. Patel and J. T. Patel, "Occlusion detection and recognizing human face using neural network," 2017 International Conference on Intelligent Computing and Control (I2C2), Coimbatore, 2017, pp. 1-4, doi: 10.1109/I2C2.2017.8321959.
- [18] R. Shinwari, A. Jalali Balooch, A. A. Alariki and S. Abduljalil Abdulhak, "A Comparative Study of Face Recognition Algorithms under Facial Expression and Illumination," 2019 21st International Conference on Advanced Communication Technology (ICACT), PyeongChang Kwangwoon_Do, Korea (South), 2019, pp. 390-394, doi: 10.23919/ICACT.2019.8702002
- [19] M. Phankokkrud and P. Jaturawat, "Influence of facial expression and viewpoint variations on face recognition accuracy by different face recognition algorithms," 2017 18th IEEE/ACIS International Conference on Software Engineering, Artificial Intelligence, Networking and Parallel/Distributed Computing (SNPD), Kanazawa, 2017, pp. 231-237, doi: 10.1109/SNPD.2017.8022727.
- [20] Raouzaoui, Amaryllis & Ioannou, S & Karpouzis, Kostas & Kollias, Stefanos & Cowie, Roddy. (2020). FACIAL EXPRESSION ANALYSIS.
- [21] Weber, Raphaël & Soladié, Catherine & Segurier, Renaud. (2018). A Survey on Databases for Facial Expression Analysis. 10.5220/0006553900730084.
- [22] Tahir, Faryal & Ullah, Fath U Min & Nasir, Mansoor & Sajjad, Muhammad. (2017). Facial Expression Analysis of group photo.
- [23] Singh, Hemanth & Patel, Raman & Shah, Vipul. (2020). Facial Expression Analysis using Deep Learning. 2395-0056.
- [24] <https://careinc.com/care-blog/importance-of-elderly-care-services>
- [25] https://www.seniorcare.org/elder-care/https://www.centersite.net/poc/view_doc.php?type=doc&id=7729&cn=171
- [26] https://www.centersite.net/poc/view_doc.php?type=doc&id=7735&cn=171
- [27] <https://www.seniorcare.org/elder-care/>

- [28] <https://www.longtermcarelink.net/eldercare/caregiving.htm>
- [29] <https://careinc.com/care-blog/importance-of-elderly-care-services>
- [30] <https://builtin.com/data-science/step-step-explanation-principal-component-analysis>
- [31] <https://learnche.org/pid/latent-variable-modelling/principal-component-analysis/mathematical-derivation-for-pca>
- [32] <https://www.einfochips.com/blog/top-3-emerging-trends-in-video-analytics-artificial-intelligence-tracking-micro-expressions/>
- [33] <https://learnche.org/pid/latent-variable-modelling/principal-component-analysis/mathematical-derivation-for-pca>
- [34] <https://builtin.com/data-science/step-step-explanation-principal-component-analysis>
- [35] <https://medium.com/@ksusorokina/image-classification-with-convolutional-neural-networks-496815db12a8>
- [36] https://insights.sei.cmu.edu/sei_blog/2018/01/revealing-true-emotions-through-micro-expressions-a-machine-learning-approach.html