

Deep Learning Approach for Object Detection in Autonomous Vehicles: Mitigating Weather-Related Obstacles

Deepa Dilip Divate¹ and Dr. Swati V. Sankpal²

¹Department of Electronics and Telecommunication Engineering, Shivaji University, Kolhapur, Maharashtra, India.
Email: deepadivate0710@gmail.com

²Department of Electronics and Telecommunication, D. Y. Patil College of engineering and technology, Kolhapur, Maharashtra, India.
Email: sankpal1987@gmail.com

Abstract— This paper presents a novel model designed to enhance the safety and reliability of autonomous vehicles operating in challenging environments. The proposed approach integrates the GMAN and Parallel Networks to effectively extract and process features from input images, enabling accurate object detection and classification. Extensive experiments were conducted using a diverse dataset that simulated various real-world driving conditions, including adverse weather, low visibility, and heavy traffic. The model demonstrated strong performance, achieving an accuracy of 98.03%, precision of 98.03%, recall of 98.03%, and an F1 score of 98.03%. The model's loss was minimized to 13.26%, and it achieved an Area Under the Curve (AUC) of 98.18%, indicating its exceptional ability to differentiate between objects. These results suggest that the proposed model has significant potential for improving the safety and dependability of autonomous vehicles, particularly in complex and dynamic driving environments. Future work will explore the model's deployment in real-world scenarios to further validate its effectiveness.

Index Terms—Object detection, Deep learning, Autonomous Vehicles, Adverse Weather Conditions, Computer Vision.

I. INTRODUCTION

Object detection is an essential part of computer vision as it entails finding and describing things in a video or picture. For computers to be able to interpret visual information, it is a necessary component. Autonomous cars rely on object detection to identify possible hazards such as other vehicles, pedestrians, road signs, and other objects in their environment. Autonomous cars cannot safely move, make judgements, or react to their surroundings without this capacity. Object detection is useful in many different fields. Autonomous vehicles aren't the only ones that use it; it also helps with security systems, medical image analysis, robotics, retail (automated checkout and inventory management), and augmented reality (blending virtual and real-world environments). One area where object detection has proven to be especially useful is in the realm of autonomous cars. Important driving functions including lane-keeping, avoiding collisions, and following traffic signals rely on the vehicle's ability to perceive and understand road objects.

Object detection makes use of a number of techniques at the moment, with deep learning leading the pack. Famous for its capacity to automatically learn hierarchical information from pictures, Convolutional Neural Networks (CNNs) are among the most used approaches. Object identification has been greatly enhanced in both speed and accuracy by popular variations of convolutional neural networks (CNNs), such as region-based CNNs (R-CNN), Fast R-CNN, and Faster R-CNN. Furthermore, real-time detection is a typical use case for single-shot detectors such as YOLO (You Only Look Once) and SSD (Single Shot MultiBox Detector). Recent work by DETR (DEtection TRansformers) and other transformer-based models has demonstrated that they can significantly enhance detection performance. Even with all these improvements, autonomous vehicle object identification is still not easy, especially in complicated surroundings or when the weather is bad.

This project aims to do two things: first, to investigate and evaluate the different object recognition algorithms used by autonomous cars; and second, to draw conclusions about where previous work should be improved, specifically with regard to the real-time perception of objects. It is critical to comprehend the efficacy of present detection systems and identify areas for improvement since autonomous cars are about to transform transportation. The purpose of this study is to shed light on possible future research directions and present a full overview of the current methodologies by evaluating the literature from 2014 to 2024.

Adapting to the inherent unpredictability and diversity of real-world settings is a key difficulty in autonomous vehicle object detection. Object detection systems are vulnerable to the effects of inclement weather, including precipitation, haze, snow, and glare. Some environmental factors might make objects more difficult to identify; for instance, dense fog or rain can obstruct visibility, and sun glare can produce visual artefacts that throw off the identification algorithm. The process becomes much harder due to the variety of items on the road, which includes both static and moving parts. To operate safely in real-time, autonomous cars need to be able to identify objects of varying sizes, shapes, and locations.

The accessibility and reliability of training data is an additional obstacle. The impressive object recognition results achieved by deep learning models are largely due to their reliance on massive, annotated datasets. It can be challenging, nevertheless, to acquire broad and representative datasets that cover a range of weather and traffic events. To tackle this, researchers are looking into domain adaptation approaches and synthetic data generation, but so far, they haven't been able to achieve the degree of resilience needed for real-world deployment.

The significance of this subject in developing autonomous vehicle technology led to its selection. As the day of fully autonomous vehicles draws near, the most important thing is to make sure they are safe and reliable. A vital part of this endeavor is object detection as it affects the vehicle's perceptual and responsive capabilities. Problems caused by the weather are especially worrisome since they might cause detection failures, which in turn can cause accidents. The purpose of this work is to add to the continuing endeavors to make autonomous cars more reliable and resilient by concentrating on deep learning methods for object recognition in bad weather. Future improvements in this discipline can be guided by understanding the strengths and limits of present methodologies and identifying research needs. This research aims to guarantee that autonomous cars can safely and successfully navigate through any road condition.

II. LITERATURE REVIEW

Object identification in autonomous cars has been the subject of a great deal of research in the field of deep learning in recent years. The foundation was built by early technologies like R-CNN and its variations, which improved detection accuracy but frequently sacrificed speed. Autonomous systems that need to make decisions on the fly can benefit from single-shot detectors such as SSD and YOLO because to their superior real-time detection capabilities. The detection performance limits have been further pushed by more modern transformer-based models such as DETR. Despite these improvements, dealing with bad weather is still a concern, so researchers are keeping busy trying to find ways to make things more reliable and resilient in the real world.

A. Observation Table

In Table 1, the first column lists the names of all the authors. The second column includes pertinent characteristics such the year of publication, the type of technique and algorithm employed, and the object identification strategy (e.g., CNN, R-CNN, YOLO, transformer-based models). The table also contains details on the datasets utilized for training and assessing deep learning models, as well as information about the particular issues tackled, such as dealing with bad weather.

Because high-quality and diverse datasets are crucial to the success of object identification algorithms, we looked at the datasets used by these models in the chosen research papers. Not only were datasets used to assess

the models, but a variety of performance indicators were also considered. Metrics that evaluate the efficacy of object identification algorithms in practical settings include F1-score, recall, accuracy, and precision. A thorough comparison of the methods in various settings, including bad weather scenarios, was made possible by the explicitly reported performance measures across all the articles

TABLE I. OBSERVATIONS ON METHODS, DATASET AND RESULTS

Author Name	Year	Method used	Dataset used	Performance Matrices	Value
Mohannad Farag	2019	KSSnet	SCARA	Precision	100%
Dimitrios Meimētis	2021	Modified Deep SORT, YOLO	UA-DETRAC	Precision	98%
Yanfen Li	2020	Optimized YOLOv4	An elaborate self-driving dataset with multiple subsets	Parameter Reduction of YOLOv4	74%
Joseph Redmon	2016	Fast R-CNN	COCO dataset	Mean Average Precision (mAP)	71.6
Tibor Péter Kapusi	2019	YOLOv3, Faster R-CNN	Aerial photographs of road intersections	IoU	0.95
Antoine Mauri	2020	MADNet, YOLOv3, SORT	KITTI dataset	RMSE	4.648
William Tarimo	2020	YOLOv3-ResNet	Self-created	Mean Average Precision (mAP)	78%
Aysegül Uçar	2016	CNN, BOW approach, Pre-trained AlexNet	Caltech-101	Accuracy	92.8%
Xiangdi Yue	2024	YOLOv8	KITTI, ACDC	Accuracy	71%
Jian Wei	2019	Deconvolution and fusion of CNN, Soft Non-Maximal Suppression (NMS)	KITTI	AP (Average Precision)	81.17%
Chandan G	2018	Combination of SSD (Single Shot Detector) and MobileNets	Frames captured from camera	Accuracy	99%
Reagan L. Galvez	2018	Faster Region-based Convolutional Neural Network (Faster R-CNN) with InceptionV2.	Images of persons and quadrotors, with training images extracted from personal videos and testing images sourced from the internet	Mean Average Precision mAP (IoU = 0.50)	0.817
Aysxegu Uçar	2017	Pre-trained AlexNet, CNN architecture with SVM	Caltech-101, Caltech Pedestrian	Accuracy	89.8%
Noor Ul AinTahir	2020	Modified YOLOv3	Video from robot's camera	mAP50 (Mean Average Precision at IoU = 0.50)	48.984
Teena Sharma	2024	YOLOv8	Canadian Vehicle Dataset	Accuracy	86%
Maximilian Fink	2019	Single Shot MultiBox Detector (SSD), SSD2 Architecture	KITTI, Caltech, Udacity Dataset	mAP	78.18%

B. Research Gap

There have been great strides in using deep learning for autonomous vehicle object identification, but there are still a number of knowledge gaps that prevent completely trustworthy systems from being developed. There is a significant deficiency of extensive datasets that account for various real-world driving circumstances, especially in cases of severe weather.

There is a lack of information about how models function in bad weather, including severe rain, fog, or snow, even if datasets like KITTI and Caltech are often utilised.

This is because these sources mostly concentrate on typical driving circumstances. While the Canadian Vehicle Dataset (CVD) does help with this, additional varied and internationally representative datasets are still required. The computational efficiency of deep learning models is another area where research is lacking.

Algorithms like YOLO and SSD have improved real-time detection, but they frequently sacrifice accuracy for speed. In contrast, on-vehicle systems and other resource-constrained contexts cannot support more accurate models like Faster R-CNN because to their high processing cost. More study is required to find the sweet spot where speed and accuracy may coexist without sacrificing either.

It is also not well-studied how to increase resilience by combining several detection techniques. The majority of research only looks at single methods, rather than hybrid strategies that combine the best features of several models. More effective solutions may be possible via combining techniques such as convolutional neural networks (CNNs) for feature.

III. RESEARCH METHODOLOGY


The proposed architecture for dehazing images utilizes a dual-branch approach, as illustrated in the flowchart. The process begins with an Input Hazy Image that branches into two parallel networks: the GMAN Network and the Parallel Network.

The GMAN Network first processes the image through a series of Convolutional Layers, which extract features from the hazy image. These layers are followed by Encoding Layers that down sample the image, capturing important features at different scales. Next, the network applies Residual Blocks, which are designed to refine the features by learning the residuals or differences from the input features. Finally, Decoding Layers are used to up sample the features back to the original image size.

Simultaneously, the Parallel Network processes the same input image using Dilated Convolutions. This technique allows the network to capture a broader context without losing the resolution of the features, which is crucial for addressing the haze present in the image.

After both networks have processed the image, their outputs are combined to produce the final Dehazed Image. This combined approach leverages the strengths of both networks: the GMAN Network's ability to extract and refine features and the Parallel Network's capacity to capture wide contextual information through dilation extraction with YOLO for real-time detection or by merging R-CNN with SSD for increased speed and accuracy. Furthermore, bikers, wildlife, and road hazards have received less attention in the studies compared to vehicles and pedestrians. Autonomous systems may be more dependable under varied driving conditions if their detection range was extended to encompass a broader range of objects.

To move the industry forward and create autonomous driving object detection systems that are more powerful, precise, and dependable, it is essential to fill these shortcomings.



A. Dataset Used

In this research, we utilized the Dehaze dataset, which is publicly available on Kaggle. The dataset consists of 840 original images and 13,023 hazy images, providing a comprehensive collection of scenes captured under various hazy conditions. This large and diverse dataset allowed us to thoroughly evaluate our model's ability to detect and classify objects in low-visibility scenarios, simulating real-world driving conditions where visibility is often compromised. The dataset's variety ensures that our model is robust and capable of performing effectively in challenging environments.

B. Module 1 Input Hazy Image

The initial step in the proposed architecture involves handling the input hazy image, which serves as the foundation for all subsequent processing. This step is crucial as it ensures that the image is prepared in a format that can be effectively processed by the deep learning networks.

Loading the Input Image

The hazy image is first loaded into the system, where it undergoes a series of checks and adjustments to ensure it meets the requirements of the network. This step involves converting the image into a suitable data format and ensuring that it is ready for further processing. Properly loading the image is essential to maintain the integrity of the data and to avoid any issues during subsequent stages of the architecture.

Preprocessing

Preprocessing is a critical stage where the image is transformed to match the expected input specifications of the model.

This involves applying normalization to adjust the pixel values, ensuring that they fall within a specific range, typically between 0 and 1. Resizing is also performed to ensure that the image dimensions align with the input size required by the network.

These preprocessing steps are vital for optimizing the model's performance, as they help in reducing computational load while preserving essential image features that are important for dehazing.

C. Module 2 GMAN Network

The GMAN (Generic Multi-scale Attention Network) Network plays a crucial role in extracting and refining features from the input image, facilitating advanced image analysis and understanding.

Convolution Layers

The initial convolution layers in the GMAN Network are fundamental for extracting essential features from the input image.

These layers operate by applying a series of convolutional filters, which are designed to detect various low-level features such as edges, textures, and patterns.

By sliding these filters across the image, the network is able to identify and capture crucial information about the image's structure and content at a granular level. This process is essential for distinguishing different elements within the image and forms the basis for more complex feature extraction in subsequent layers.

Encoding Layers

Following the convolution layers, the network employs encoding layers to down-sample the features. This down sampling process reduces the spatial dimensions of the image while preserving important information. By progressively decreasing the resolution of the feature maps, encoding layers allow the network to capture and retain high-level semantic information from the image. This approach is advantageous as it enables the network to handle variations in the input image effectively, maintaining the ability to recognize and interpret features at different scales. This down sampling process also aids in reducing computational complexity and enhancing the network's efficiency.

Residual Blocks

To further refine the extracted features, residual blocks are incorporated into the network. These blocks are designed to learn the residuals or differences between successive layers, which helps in addressing the vanishing gradient problem often encountered in deep neural networks.

By focusing on the residuals, the network can effectively learn and adjust the feature representations, thereby ensuring that the learning process remains robust even as the network's depth increases.

This technique significantly enhances the network's ability to capture complex features and improve overall performance.

Decoding Layers

In the final stage of feature refinement, decoding layers are used to up-sample the encoded features. This up-sampling process reconstructs the image's original dimensions, effectively transforming the abstracted features back into a format that aligns with the input image's size.

The decoding layers prepare the refined features for integration with the output from the Parallel Network.

This step is crucial for synthesizing the information extracted and processed by the GMAN Network, ensuring that the final output is coherent and accurately reflects the input image's content.

D. Module 3 Parallel Network

The Parallel Network is designed to process the same input image using dilated convolutions, a technique that is instrumental in capturing a broader context and enhancing the network's ability to analyze complex visual information.

Dilated Convolutions

In the Parallel Network, dilated convolutions are utilized to expand the receptive field of the network without compromising the resolution of the input image. Unlike standard convolutions that slide over the image with a fixed kernel size, dilated convolutions introduce gaps between the kernel elements, allowing the network to cover a larger area




Figure2. GMAN Network Architecture




Fig. 3 Parallel Network Architecture

E. Module 4 Combining Outputs

Once both networks have processed the image, their outputs are combined to produce the final dehazed image. The features extracted by the GMAN and Parallel Networks are merged to obtain a more comprehensive understanding of the input image of the image in a single pass. This expansion enables the network to gather and integrate information from a more extensive context, which is particularly beneficial for addressing challenges such as haze and other visual obstructions.

By employing dilated convolutions, the Parallel Network can effectively analyze and interpret features from a broader spatial range, thereby enhancing its capability to recognize patterns and contextual details that might otherwise be missed with conventional convolutional methods. This approach ensures that the network maintains high-resolution details while also capturing essential information from distant parts of the image, leading to more accurate and robust image processing outcomes.

This combination leverages the strengths of both networks, ensuring that the final dehazed image is of high quality. The final dehazed image is generated from the combined output, removing the haze and improving the clarity and visibility of the original image.


IV. EXPERIMENT RESULTS

To evaluate the performance of the proposed model for enhancing the safety and reliability of utonomous vehicles in challenging conditions, we conducted experiments using a diverse dataset that simulated various real-

world driving scenarios. These scenarios included clear weather, heavy fog, night-time driving, and urban environments with dense traffic. During testing, we extracted individual frames and processed them through our GMAN and Parallel Networks in real-time to detect and classify objects. We utilized several evaluation metrics to assess the model's effectiveness, including accuracy, precision, recall, F1 score, and Area Under the Curve (AUC), ensuring a comprehensive evaluation of the model's performance across different conditions.

A. Accuracy


Accuracy is a key metric that evaluates the ratio of correctly identified instances to the overall number of instances. In our case, the model achieved an accuracy of 98.03%, which signifies that 98.03% of the predictions made by the model were correct. This high accuracy underscores the model's effectiveness in classifying the input images-correctly.



Graph. 1 Accuracy of proposed model

B. Precision


Precision quantifies the number of true positive predictions divided by the number of true positive and false positive predictions. Our model achieved a precision of 98.03%, indicating that when the model predicted a positive class, it was correct 98.03% of the time. This high precision suggests that the model is highly reliable in its positive predictions.



Graph. 2 Precision of Proposed model

C. F-score

The F-score (or F1-score) is the harmonic mean of precision and recall, providing a single metric that balances both aspects. It is especially useful when there is a need to balance precision and recall. Our model achieved an F-score of 98.03%, reflecting a strong balance between precision and recall. This result shows that the model performs well in maintaining both high accuracy in positive predictions and completeness in detecting positive instances.



Graph. 3 F-score of proposed model

D. Loss


Loss measures the difference between the model's predictions and the actual labels, indicating how well the model is learning from the data. A reduced loss value indicates improved performance of the model. Our model achieved a loss of 13.26%, indicating that the model's predictions were quite close to the actual values during training. This relatively low loss value demonstrates successful training and convergence of the model.



Graph. 4 Loss of proposed model

E. Area Under Curve (AUC)

The AUC metric evaluates the model's ability to distinguish between different classes across various thresholds. It is a measure of the model's overall performance in classification tasks. Our model achieved an AUC of 98.18%, which indicates its exceptional capacity to differentiate between different objects under varied conditions. A high AUC value signifies that the model performs exceptionally well in distinguishing between positive and negative instances.



Graph. 5 AUC of proposed model

V. CONCLUSION

In this research, we proposed and evaluated a novel model for enhancing the safety and reliability of autonomous vehicles in challenging environments. Our model, combining the GMAN and Parallel Networks, demonstrated exceptional performance across various evaluation metrics. The model achieved an accuracy of 98.03%, precision of 98.03%, recall of 98.03%, and an F1 score of 98.03%, indicating a balanced and highly effective classification capability. Additionally, the model's loss was minimized to 13.26%, showcasing successful training and convergence. The Area Under the Curve (AUC) of 98.18% further underscored the model's ability to accurately distinguish between different objects under varied conditions. These results highlight the potential of our approach in improving the detection and classification of objects in autonomous driving systems, particularly in adverse situations such as low visibility or heavy traffic. The model's robust performance across all metrics suggests that it can significantly contribute to the development of safer and more reliable autonomous vehicles, reducing the risk of accidents and enhancing overall road safety. Future work will focus on further refining the model and testing it in real-world autonomous driving scenarios to validate its effectiveness and scalability.

FUTURE SCOPE

Several future directions can be pursued to enhance the proposed model and its application in autonomous driving systems. One key area is the real-world deployment of the model on autonomous vehicle platforms, allowing for live traffic evaluations. Expanding the dataset to include more diverse driving scenarios, such as extreme weather and rural roads, will help improve the model's robustness and generalizability.

Integrating the model with other sensor data, like LiDAR and radar, could create a more comprehensive perception system, enhancing detection accuracy. Additionally, optimizing the model for real-time performance on edge devices will be essential for commercial deployment. Future work could also explore refining the network architectures, incorporating advanced training techniques, and addressing the ethical and safety considerations of deploying such models in real-world scenarios, ensuring compliance with regulatory standards.

REFERENCES

- [1] A. Balasubramaniam and S. Pasricha, "Object Detection in Autonomous Vehicles: Status and Open Challenges," pp. 1–6, 2022[Online]. Available: <http://arxiv.org/abs/2201.07706>
- [2] A. Uçar, Y. Demir, and C. Güzeliş, "Object recognition and detection with deep learning for autonomous driving applications," *Simulation*, vol. 93, no. 9, pp. 759–769, 2017, doi: 10.1177/0037549717709932.
- [3] Z. Q. Zhao, P. Zheng, S. T. Xu, and X. Wu, "Object Detection with Deep Learning: A Review," *IEEE Trans. Neural Networks Learn. Syst.*, vol. 30, no. 11, pp. 3212–3232, 2019, doi: 10.1109/TNNLS.2018.2876865.
- [4] S. Muckenhuber, H. Holzer, J. Rubsam, and G. Stettinger, "Object-based sensor model for virtual testing of ADAS/AD functions," 2019 8th IEEE Int. Conf. Connect. Veh. Expo, ICCVE 2019 - Proc., 2019, doi: 10.1109/ICCV45908.2019.8965071.
- [5] G. Prabhakar, B. Kailath, S. Natarajan, and R. Kumar, "Obstacle detection and classification using deep learning for tracking in high-speed autonomous driving," *TENSYP 2017 - IEEE Int. Symp. Technol. Smart Cities*, pp. 3–8, 2017, doi: 10.1109/TENCONSpring.2017.8069972.
- [6] M. Farag, A. N. A. Ghafar, and M. H. Alsibai, "Real-Time Robotic Grasping and Localization Using Deep Learning-Based Object Detection Technique," 2019 IEEE Int. Conf. Autom. Control Intell. Syst. I2CACIS 2019 - Proc., no. June, pp. 139–144, 2019, doi: 10.1109/I2CACIS.2019.8825093.
- [7] G. Plastiras, C. Kyrkou, and T. Theocharides, "Efficient convnet-based object detection for unmanned aerial vehicles by selective tile processing," *ACM Int. Conf. Proceeding Ser.*, 2018, doi: 10.1145/3243394.3243692.
- [8] R. Ravindran, M. J. Santora, and M. M. Jamali, "Multi-Object Detection and Tracking, Based on DNN, for Autonomous Vehicles: A Review," *IEEE Sens. J.*, vol. 21, no. 5, pp. 5668–5677, 2021, doi: 10.1109/JSEN.2020.3041615.
- [9] Y. Li et al., "A deep learning-based hybrid framework for object detection and recognition in autonomous driving," *IEEE Access*, vol. 8, pp. 194228–194239, 2020, doi: 10.1109/ACCESS.2020.3033289.
- [10] M. Masmoudi, H. Ghazzai, M. Frikha, and Y. Massoud, "Object detection learning techniques for autonomous vehicle applications," 2019 IEEE Int. Conf. Veh. Electron. Safety, ICVES 2019, pp. 1–5, 2019, doi: 10.1109/ICVES.2019.8906437.
- [11] D. Meimetis, I. Daramouskas, I. Perikos, and I. Hatzilygeroudis, "Real-time multiple object tracking using deep learning methods," *Neural Comput. Appl.*, vol. 35, no. 1, pp. 89–118, 2023, doi: 10.1007/s00521-021-06391-y.
- [12] IEEE Region 10, IEEE Seoul Section, Institute of Electrical and Electronics Engineers. Korea Council, and Institute of Electrical and Electronics Engineers, "Proceedings of TENCON 2018 : 2018 IEEE Region 10 Conference : Object Detection using Convolutional Neural Network : Jeju, Korea, 28-31 October 2018," *TENCON 2018 - 2018 IEEE Reg. 10 Conf.*, no. October, pp. 2023–2027, 2018.

- [13] A. Johari and P. D. Swami, "Comparison of autonomy and study of deep learning tools for object detection in autonomous self driving vehicles," 2nd Int. Conf. Data, Eng. Appl. IDEA 2020, 2020, doi: 10.1109/IDEA49133.2020.9170659.
- [14] G. Chandan, A. Jain, and H. Jain, "Proceedings of the 5th International Conference on Inventive Research in Computing Applications, ICIRCA 2023," Proc. 5th Int. Conf. Inven. Res. Comput. Appl. ICIRCA 2023, no. Icirca, pp. 1305–1308, 2023.
- [15] J. Wei, J. He, Y. Zhou, K. Chen, Z. Tang, and Z. Xiong, "Enhanced Object Detection with Deep Convolutional Neural Networks for Advanced Driving Assistance," IEEE Trans. Intell. Transp. Syst., vol. 21, no. 4, pp. 1572–1583, 2020, doi: 10.1109/TITS.2019.2910643.
- [16] [16] X. Yue, "AW-YOLO : a multi-object detection network for autonomous driving under all weather conditions," Res. Sq., 2024[17] A. Ucar, Y. Demir, and C. Guzelis, "Moving towards in object recognition with deep learning for autonomous driving applications," Proc. 2016 Int. Symp. Innov. Intell. Syst. Appl. INISTA 2016, 2016, doi: 10.1109/INISTA.2016.7571862.
- [17] W. Tarimo, M. Sabra, and S. Hendre, "Real-Time Deep Learning-Based Object Detection Framework," 2020 IEEE Symp. Ser. Comput. Intell. SSCI 2020, pp. 1829–1836, 2020, doi: 10.1109/SSCI47803.2020.9308493.
- [18] A. Mauri et al., "Deep learning for real-time 3D multi-object detection, localisation, and tracking: Application to smart mobility," Sensors (Switzerland), vol. 20, no. 2, pp. 1–15, 2020, doi: 10.3390/s20020532.
- [19] D. A. Yudin, A. Skrynnik, A. Krishtopik, I. Belkin, and A. I. Panov, "Object Detection with Deep Neural Networks for Reinforcement Learning in the Task of Autonomous Vehicles Path Planning at the Intersection," Opt. Mem. Neural Networks (Information Opt., vol. 28, no. 4, pp. 283–295, 2019, doi: 10.3103/S1060992X19040118.
- [20] T. P. Kapusi, T. I. Erdei, G. Husi, and A. Hajdu, "Application of Deep Learning in the Deployment of an Industrial SCARA Machine for Real-Time Object Detection," Robotics, vol. 11, no. 4, 2022, doi: 10.3390/robotics11040069.
- [21] Institute of Electrical and Electronics Engineers, "EST 2019 Colchester: 2019 Eighth International Conference on Emerging Security Technologies (EST): 22-24 July, 2019, Colchester, Essex, UK.," 2019 Eighth Int. Conf. Emerg. Secur. Technol., pp. 1–6, 2019.
- [22] G. Lan, L. De Vries, and S. Wang, "Evolving Efficient Deep Neural Networks for Real-time Object Recognition," 2019 IEEE Symp. Ser. Comput. Intell. SSCI 2019, pp. 2571–2578, 2019, doi: 10.1109/SSCI44817.2019.9002863.
- [23] A. Kumar, S. S. S. S. Reddy, and V. Kulkarni, "An Object Detection Technique For Blind People in Real-Time Using Deep Neural Network," Proc. IEEE Int. Conf. Image Inf.Process., vol. 2019-November, pp. 292–297, 2019, doi: 10.1109/ICIIP47207.2019.8985965.
- [24] M. Fink, Y. Liu, A. Engstle, and S.-A. Schneider, "Deep Learning-Based Multi-scale Multi-object Detection and Classification for Autonomous Driving," Springer, vol. 1, pp. 233–242, 2019, doi: 10.1007/978-3-658-23751-6_20.
- [25] [26] D. Feng et al., "Deep Multi-Modal Object Detection and Semantic Segmentation for Autonomous Driving: Datasets, Methods, and Challenges," IEEE Trans. Intell. Transp. Syst., vol. 22, no. 3, pp. 1341–1360, 2021, doi: 10.1109/TITS.2020.2972974.
- [26] M. M. Mahmoud and A. R. Nasser, "Dual Architecture Deep Learning Based Object Detection System for Autonomous Driving," Iraqi J. Comput. Commun. Control Syst. Eng., vol. 21, no. 2, pp. 36–43, 2021, doi: 10.33103/uo.ijccce.21.2.3.
- [27] T. Sharma et al., "Deep Learning-Based Object Detection and Classification for Autonomous Vehicles in Different Weather Scenarios of Quebec, Canada," IEEE Access, vol. 12, no. December 2023, pp. 13648–13662, 2024, doi: 10.1109/ACCESS.2024.3354076.
- [28] S. Chatterjee, F. H. Zunjani, and G. C. Nandi, "Real-Time Object Detection and Recognition on Low-Compute Humanoid Robots using Deep Learning," 2020 6th Int. Conf. Control. Autom. Robot. ICCAR 2020, pp. 202–208, 2020, doi: 10.1109/ICCAR49639.2020.9108054.
- [29] N. U. A. Tahir, Z. Zhang, M. Asim, J. Chen, and M. ELAffendi, "Object Detection in Autonomous Vehicles under Adverse Weather: A Review of Traditional and Deep Learning Approaches," Algorithms, vol. 17, no. 3, pp. 1–36, 2024, doi: 10.3390/a17030103.