

Predicting Electricity Bill Prices using LSTM and IoT-based Sensor Data

Khush Jain¹, Anand Mane², Heet Jain³ and Harshvardhan Sethia⁴

¹⁻⁴ Sardar Patel Institute of Technology/ Department of Electronics & Telecommunication Engineering, Mumbai, India
Email: anand_mane@spit.ac.in, heet.jain@spit.ac.in, khush.jain@spit.ac.in, harshvardhan.sethia@spit.ac.in

Abstract— Accurate prediction of electricity bill prices is essential for both consumers and utility providers to manage energy consumption and costs effectively. This research paper presents an innovative approach to forecast electricity bill prices using data collected directly from sensors. These sensors include SCT-013-000 for current measurement and ZMPT101B for voltage measurement, providing real-time, high-resolution data critical for precise consumption analysis. The model employs Long Short-Term Memory (LSTM) networks for temporal sequence learning, handling the time-dependent nature of electricity consumption patterns. Our methodology includes deploying these sensors in a smart home environment to gather continuous data, transmitted through an Internet of Things (IoT) network to a centralized server for processing. After preprocessing and normalization, the data is fed into the LSTM model, trained and validated using historical electricity usage and billing information. Experimental results demonstrate that our approach outperforms traditional machine learning models in terms of prediction accuracy and reliability. The integration of IoT-enabled SCT-013-000 and ZMPT101B sensors enhances data granularity and facilitates real-time monitoring and prediction capabilities, significantly benefiting consumers and utility providers by providing insights into future electricity bills, allowing proactive adjustments in usage patterns and optimizing grid operations and dynamic pricing strategies.

Index Terms—LSTM, IoT Sensors, ZMPT, Energy Forecasting, Machine Learning, Real-Time Monitoring.

I. INTRODUCTION

Traditional methods of electricity bill prediction often relied on historical consumption data and simplistic forecasting techniques, struggling to capture the intricate dynamics of energy usage patterns.

However, with the advent of IoT technologies and the deployment of advanced sensor networks, capturing real-time data on electricity consumption has become increasingly feasible, opening new avenues for predictive modeling.

At the heart of our methodology lie the SCT-013-000 current sensor and the ZMPT101B voltage sensor, key enablers for real-time data collection in electricity consumption monitoring applications.

The SCT-013-000 sensor utilizes non-invasive current sensing technology to measure electrical currents flowing through circuits, providing accurate and reliable data on power usage. Complementing this, the ZMPT101B sensor offers precise measurements of voltage levels, allowing for comprehensive analysis of power consumption patterns.

By integrating these sensors into smart meters deployed in residential, commercial, or industrial settings, we can capture granular data on electricity consumption with unparalleled accuracy and resolution, essential for developing predictive models accurately forecasting electricity bill prices and anticipating future consumption trends. In tandem with real-time sensor data acquisition, our methodology employs LSTM networks for electricity bill prediction, leveraging their ability to capture temporal dependencies and patterns in sequential data. LSTM networks, a type of recurrent neural network (RNN), excel in modeling complex time-series data, making them particularly suitable for forecasting tasks. Unlike traditional forecasting methods relying on simplistic statistical models or shallow learning algorithms, LSTM networks can effectively capture long-term dependencies and nonlinear relationships inherent in energy consumption patterns. By training LSTM models on historical consumption data and corresponding billing information, we develop robust predictive models capable of accurately forecasting future electricity bill prices.

The implementation of our methodology follows a systematic approach, encompassing data collection, preprocessing, model training, and evaluation stages. Initially, IoT sensors, including the SCT-013-000 current sensor and the ZMPT101B voltage sensor, are deployed in target environments to gather real-time data on electricity consumption. The raw sensor data undergoes preprocessing steps, including normalization and feature extraction, ensuring compatibility with the LSTM model architecture. Subsequently, the preprocessed data is used to train the LSTM network, where the model learns to capture complex relationships between input features and electricity bill prices. To evaluate the LSTM model's performance, we employ rigorous validation techniques, including cross-validation and evaluation metrics such as Root Mean Square Error (RMSE)

II. BACKGROUND

Electricity bill prediction is an essential aspect of modern energy management systems, offering critical insights that enable stakeholders to optimize resource allocation and achieve cost efficiency. As energy consumption patterns become increasingly complex due to technological advancements and the proliferation of electrical devices, the ability to accurately forecast electricity bills is more important than ever.

This capability is vital for various stakeholders, including consumers who seek to manage their household or business expenses, utility providers who need to balance supply and demand, and policymakers aiming to devise effective energy regulations. Accurate electricity bill prediction helps consumers by providing insights into their energy usage patterns, allowing them to make informed decisions about how to reduce consumption and save on costs. For utility providers, accurate predictions support effective grid management, ensuring that energy supply matches demand, which is crucial for maintaining stability and avoiding blackouts. Policymakers benefit from accurate forecasting as it enables the formulation of policies that promote energy efficiency and sustainability.

A. Traditional Methods of Electricity Bill Prediction

Historically, electricity bill prediction has relied on analyzing historical consumption data using simplistic forecasting techniques. These methods typically involve linear regression models, moving averages, or basic time-series analysis. While these techniques provide a foundational understanding, they fall short in capturing the intricate dynamics of modern energy usage patterns.

Traditional methods face several limitations:

- **Lack of Granularity:** They often aggregate data over long periods, such as monthly or yearly intervals, missing out on finer details of daily or hourly usage.
- **Inability to Capture Real-Time Dynamics:** Traditional models do not account for real-time changes in consumption, leading to less accurate predictions.
- **Inefficiency in Adapting to Changing Consumption Patterns:** These methods struggle to adapt to rapid changes in consumption behavior caused by new appliances, seasonal variations, or shifts in usage habits.
- These limitations underscore the need for more sophisticated approaches that can handle the complexity and variability of modern electricity consumption patterns.

B. Emergence of IoT in Energy Monitoring

Despite the progress achieved by RNN-based models, the advent of the Internet of Things (IoT) has revolutionized energy monitoring by enabling real-time data acquisition and enhanced analytical capabilities. IoT technology integrates various sensors and devices into a cohesive network, providing continuous monitoring and control over electrical systems.

This real-time data acquisition is pivotal for modern energy management, offering several advantages over traditional methods. IoT technologies in smart energy systems include real-time data acquisition, where IoT

sensors continuously collect data on electricity consumption, providing up-to-the-minute insights. They also offer enhanced granularity, as IoT devices can measure and report data at very fine intervals, capturing detailed usage patterns. Additionally, IoT systems allow for remote monitoring and control, enabling users to adjust settings and monitor consumption from anywhere. The vast amounts of data collected by IoT devices can be integrated with advanced analytics, improving the accuracy of predictions and providing deeper insights into energy usage.

C. Research gaps and limitations

Despite advancements in electricity bill prediction, several gaps and limitations remain that our approach addresses. Traditional models often rely heavily on historical data, limiting their accuracy and responsiveness, whereas our approach leverages real-time data from IoT sensors like the SCT-013-000 for current and the ZMPT101B for voltage, significantly enhancing prediction accuracy. Scalability is another issue, as existing research typically focuses on small-scale deployments.

Our methodology ensures scalability across residential, commercial, and industrial environments, making it suitable for diverse and larger settings. Data privacy and security concerns are often inadequately addressed in many models; we implement robust encryption and privacy-preserving techniques to ensure secure handling of user data and build user trust. Traditional models also overlook user engagement and interaction with predictive insights.

Environmental factors can affect sensor precision, so we include regular calibration and redundancy protocols to ensure high data accuracy and reliability. The extensive preprocessing required for raw sensor data is streamlined in our approach through standardized pipelines and automated tools, ensuring high-quality data for model training.

While LSTM networks can be computationally intensive, we optimize their architectures and use high-performance computing resources to make real-time predictions feasible. Generalizability is another limitation, as models trained on specific datasets often fail in different environments. We incorporate diverse datasets during training to enhance model adaptability and generalizability. Finally, high costs and compliance issues can hinder deployment, but our solution is cost-effective and compliant with regulations, facilitating smoother adoption. By addressing these gaps, our approach advances electricity bill prediction, providing a robust, scalable, and user-friendly solution that enhances energy management and promotes sustainability.

III. LITERATURE SURVEY

The paper “Smart Meter Based Short-Term Load Forecasting for Residential Customers” [1] utilizes Kalman filtering for load prediction, a key methodological component. Kalman filtering is a recursive algorithm widely used in control theory and signal processing, suitable for forecasting with continuous data streams, such as electricity load forecasting. It maintains an ongoing estimate of the current load by combining smart meter data and a mathematical model of load dynamics. The filter corrects its predictions using this data, improving accuracy. The algorithm operates in two steps: prediction, where it forecasts the future load and associated uncertainty, and update, where it refines this forecast with new measurements. The Kalman gain determines the weight of new measurements versus predictions. By iterating these steps, the Kalman filter provides robust and accurate load forecasts, effectively handling noise and uncertainties in the data.

The paper “Machine Learning Algorithms for Short-Term Load Forecast in Residential Buildings Using Smart Meters, Sensors and Big Data Solutions” [2] proposes a scalable Big Data framework for efficiently collecting and managing data from smart meters and weather sensors, crucial for accurate load forecasting and billing prediction. The framework captures detailed electricity usage data from smart meters and environmental data from weather sensors, such as temperature and humidity. The collected data undergoes pre-processing to ensure accuracy and reliability before being stored in a NoSQL database, which handles large volumes of unstructured or semi-structured data with high scalability. Designed for scalability and performance, the framework can efficiently process increasing data volumes for real-time applications. This comprehensive approach ensures high-quality data acquisition, management, and storage, leading to more accurate and reliable load forecasting and billing predictions.

The paper “Household Classification Using Smart Meter Data” [3] brings attention to critical limitations in relying solely on smart meter data for accurately categorizing households, which holds significant implications for electricity bill prediction and load forecasting. These limitations include the homogeneity in consumption patterns captured by smart meters, which may obscure underlying usage behaviors among households with similar overall consumption. Moreover, smart meter data lacks essential contextual information such as

household characteristics and external factors like weather conditions, both of which can significantly influence energy consumption but are not directly observable through smart meter readings. Recognizing these limitations underscores the importance of incorporating additional contextual data sources to enhance the accuracy of predictions in energy forecasting applications.

The paper “Smart Electricity Meter Data Intelligence for Future Energy Systems: A Survey” [4] highlights the critical role of technology in advancing energy sustainability and efficiency. It emphasizes the multifaceted nature of research in this domain, spanning technical aspects like smart metering to behavioral interventions and policy considerations. This comprehensive approach is essential for addressing the complex challenges of modern energy systems effectively.

Technology, particularly innovations such as smart meters and advanced data analytics, plays a pivotal role in enhancing energy sustainability by enabling real-time monitoring, accurate forecasting, and efficient energy management. Smart metering, in particular, stands out as a cornerstone, facilitating precise measurement and monitoring of energy consumption at the household level.

The detailed data provided by smart meters allows for the analysis of consumption patterns, identification of inefficiencies, and the implementation of targeted interventions to reduce energy usage. This paper “Revealing household characteristics from smart meter data” [5] introduces a system that harnesses supervised machine learning techniques to automatically estimate specific household characteristics based on electricity consumption data. Trained on labeled datasets pairing historical consumption with known household traits, the system predicts socio-economic status indicators like income level and appliance stock details such as types and quantities. By analyzing usage patterns, it infers insights crucial for energy efficiency programs, market segmentation, and policymaking. However, challenges such as data privacy and model accuracy necessitate continuous refinement. Overall, this innovative approach holds promise for improving energy management, customer service, and policy development in the energy sector. These papers collectively highlight the evolving landscape of energy forecasting and management, leveraging diverse methodologies and technologies.

While the first two papers focus on methodological advancements such as Kalman filtering and Big Data frameworks for load forecasting, the subsequent ones underscore the limitations of relying solely on smart meter data and advocate for incorporating additional contextual information for more accurate predictions. Furthermore, the critical role of technology, particularly smart meters and advanced data analytics, in advancing energy sustainability is emphasized, with a particular emphasis on the potential for machine learning techniques to extract valuable insights from consumption data. However, challenges such as data privacy and model accuracy remain pertinent concerns that necessitate ongoing refinement and innovation in the field.

IV. METHODOLOGY

The proposed methodology integrates IoT sensors for real-time data collection and employs Long Short-Term Memory (LSTM) networks for predictive modeling of electricity bill prices. By using the SCT-013-000 current sensor and the ZMPT101B voltage sensor, we capture high-resolution, real-time data on electricity consumption. This data is then preprocessed and fed into an LSTM model to forecast future electricity bill prices. The objectives of the methodology are to improve the accuracy of electricity bill predictions by utilizing real-time data from advanced IoT sensors, ensure the scalability and reliability of the predictive system across various environments, enhance user engagement and energy management through a mobile application that provides real-time insights and predictions, and address privacy and security concerns associated with IoT data collection.

A. System Architecture

The overall architecture of the proposed system consists of several key components. The system begins with IoT sensors, specifically the SCT-013-000 current sensor and the ZMPT101B voltage sensor, which measure the current and voltage, respectively.

These sensors are deployed in the electrical distribution panel of the target environment, such as residential, commercial, or industrial settings. The data collected by these sensors is transmitted to the data collection platform via a secure wireless communication protocol. The data collection platform aggregates the sensor data and forwards it to the data preprocessing unit. In the preprocessing unit, the raw data is normalized, any missing values are handled, and relevant features are extracted.

The preprocessed data is then used as input for the LSTM predictive model, which forecasts future electricity bill prices. The predictions are displayed through a user-friendly mobile application, providing consumers with real-time insights into their energy consumption and bill estimates. The architecture is designed to be scalable and reliable, ensuring that the system can be deployed in various environments.




Fig. 1. Workflow block diagram

Description of Each Component in the System

- IoT Sensors (SCT-013-000, ZMPT101B): The SCT-013-000 is a non-invasive current sensor that measures the current flowing through electrical circuits, while the ZMPT101B is a voltage sensor that measures the voltage levels. These sensors provide precise and reliable data on electricity consumption.
- Data Collection Platform: This platform collects real-time data from the sensors and transmits it to the preprocessing unit. It ensures continuous and accurate data flow from the sensors to the system.
- Data Preprocessing Unit: This unit is responsible for normalizing the raw data, handling missing values, and extracting relevant features. Proper preprocessing is essential for ensuring the quality and compatibility of the data with the LSTM model.
- LSTM Predictive Model: The core of the system, this model uses the preprocessed data to predict future electricity bill prices. LSTM networks are particularly suited for time-series forecasting due to their ability to capture temporal dependencies.
- User Interface (Mobile App): The mobile app displays real-time sensor readings and predictive insights to users. It provides an intuitive interface for consumers to monitor their energy usage and make informed decisions.

The sensors are installed in the electrical distribution panel of the target environment (residential, commercial, or industrial). The SCT-013-000 is clamped around the conductors to measure current, while the ZMPT101B is connected to the voltage points. Both sensors are interfaced with a microcontroller unit (MCU) that collects and transmits the data to the data collection platform.

B. Data Preprocessing




Fig. 2. Preprocessing Block Diagram

Data Normalization Techniques: Normalization is crucial for ensuring that the data is on a common scale, which helps improve the performance of the predictive model. Techniques such as min-max normalization or z-score normalization are applied to scale the sensor data between 0 and 1 or to standardize it based on the mean and standard deviation.

Handling Missing Values: Missing data can occur due to sensor malfunctions or communication errors. Techniques such as forward filling, backward filling, or interpolation are used to handle missing values, ensuring that the dataset remains complete and consistent.

Feature Extraction Process: Feature extraction involves identifying and extracting relevant attributes from the raw data that can significantly impact the prediction accuracy. Features such as average current, voltage, power consumption, and temporal features (e.g., time of day, day of the week) are extracted and used as inputs for the LSTM model.

C. Predictive Modeling

LSTM networks are a type of recurrent neural network (RNN) capable of learning long-term dependencies in sequential data. They are particularly effective for time-series forecasting due to their ability to remember past information and use it to predict future values.

- **Input Layer:** Receives the preprocessed data.
- **LSTM Layers:** Comprise several LSTM cells that process the sequential data.
- **Dense Layer:** A fully connected layer that outputs the predicted electricity bill price.
- **Training Process of the LSTM Model:** The model is trained using historical electricity consumption data and corresponding bill prices.

The training process involves:

- **Data Splitting:** Dividing the dataset into training and validation sets.
- **Loss Function:** Using mean squared error (MSE) as the loss function.
- **Optimizer:** Employing the Adam optimizer for efficient training.
- **Training Iterations:** Iteratively updating the model weights to minimize the loss function over several epochs.




Fig. 3. LSTM Network Architecture

Integration of Sensors with the Data Collection Platform

- The sensors are integrated with the MCU, which transmits data to the data collection platform using a secure communication protocol. The platform aggregates data from multiple sensors and ensures reliable data flow to the preprocessing unit.
- A secure communication protocol, such as MQTT or HTTP over SSL/TLS, is used to transmit data from the MCU to the data collection platform. This ensures data integrity and confidentiality during transmission.
- The mobile app is developed to provide users with real-time insights into their energy consumption and bill predictions. It is built using a cross-platform framework (e.g., React Native) to ensure compatibility with both Android and iOS devices. The app interfaces with the backend server to fetch real-time data and predictions.

D. Hardware Description - ESP32

The ESP32 is a powerful and versatile microcontroller and Wi-Fi/Bluetooth-enabled system-on-chip (SoC) developed by Espressif Systems. Launched as an improvement over its predecessor, the ESP8266, the ESP32 offers enhanced capabilities, making it a popular choice for a wide range of applications, including the Internet of Things (IoT), home automation, industrial automation, and more.

The ESP32's capabilities make it well-suited for data selection in various applications, particularly in scenarios where real-time data acquisition and processing are essential. Its GPIO pins and support for communication protocols like I2C and SPI enable connections to sensors, actuators, and other data sources. For instance, in an environmental monitoring system, the ESP32 can gather data from sensors measuring temperature, humidity, and air quality.

Moreover, the dual-core processor allows parallel execution of tasks, enabling efficient handling of multiple sensors simultaneously. The ability to process and filter data directly on the device makes the ESP32 an ideal choice for selecting relevant information before transmitting it to a database.

The ESP32's connectivity features, including Wi-Fi, make it a valuable component for uploading selected data to databases. In IoT applications, the collected data often needs to be stored and analyzed on remote servers or cloud platforms. The ESP32 can establish a secure connection to the internet and transmit data to databases using standard protocols like HTTP or MQTT.

Additionally, the support for secure boot and flash encryption enhances the security of the data during transmission, safeguarding it against potential threats. The low power consumption feature is advantageous for battery-powered devices, ensuring efficient data uploading without excessive energy consumption.




Fig. 4. Circuit diagram of the proposed system

E. Hardware Description - ZMPT101B

The ZMPT101B AC Voltage Sensor Module is designed for measuring alternating current (AC) voltages. It specifically measures low voltage AC signals ranging from 0 to 1000 V. The module provides an analog output signal proportional to the input AC voltage, which can be interfaced with microcontrollers or other processing units for further analysis.

Key Features of ZMPT101B

- High Precision: The ZMPT101B is known for its accuracy in measuring AC voltage, making it suitable for applications like household AC voltage monitoring.
- Analog Output: It provides an analog signal proportional to the measured voltage, allowing easy interfacing with microcontrollers.
- Safety and Reliability: Designed to handle low voltages, it ensures safe and reliable measurements without direct interaction with high voltage lines.

F. Hardware Description - SCT-013-030

The SCT-013-030 is a non-invasive AC current sensor designed to measure alternating current without the need to cut or disconnect the live wire. It has a defined current range, typically up to 30A, and outputs a low-voltage AC signal proportional to the current passing through the conductor it encircles.

Key Features of SCT-013-030:

- Non-invasive Measurement: Allows current measurement without interrupting the circuit, providing safety and ease of use.
- Current Range: Designed to monitor AC currents up to 30A.

- Accuracy: Known for providing reasonably accurate current measurements within its specified range.
- Analog Output: The sensor's output can be interfaced with microcontrollers for measurement and analysis or processed further by external circuitry.

V. OBSERVATIONS & DISCUSSION

The use of Long Short-Term Memory (LSTM) networks proved crucial in achieving these results. LSTM networks, designed to handle temporal sequence learning, effectively modeled the intricate dependencies and variations in electricity usage over time. This capability is particularly important in the context of energy consumption, where usage patterns can exhibit significant fluctuations based on factors such as time of day, seasonality, and consumer behavior.

The integration of SCT-013-000 current sensors and ZMPT101B voltage sensors provided high-resolution, real-time data essential for precise consumption analysis. These sensors, deployed in a smart home environment, continuously transmitted data through an IoT network to a centralized server. This setup ensured a steady stream of accurate and granular data, which, after preprocessing and normalization, was fed into the LSTM model for training and validation. The superior performance of the LSTM-based model highlights its potential in real-world applications. For consumers, it offers the ability to predict future electricity bills with high accuracy, enabling proactive adjustments in usage patterns to manage costs effectively. For utility providers, the model facilitates better demand forecasting, optimizing grid operations, and enhancing the implementation of dynamic pricing strategies.




Fig. 5. ESP32 and other hardware

This constant flow of data enables the model to learn and adapt to the nuances of electricity usage patterns in real-time, enhancing its predictive capabilities. Additionally, IoT sensors can capture a wide array of data points, such as voltage, current, and power factor, providing a comprehensive dataset that allows the ML model to consider various factors influencing electricity consumption.




Fig. 6. Dashboard along with predictions

The synergy between IoT and machine learning (ML) technologies lies at the heart of our model's success. IoT devices, with their ability to continuously collect and transmit data, ensure that the ML models are fed with up-to-date and high-resolution information.

An intuitive user interface (UI) plays a pivotal role in maximizing the utility of our predictive model. By presenting complex data and forecasts in a clear, accessible manner, the UI ensures that users can easily interpret and act upon the insights provided. A well-designed UI should feature interactive dashboards displaying real-time consumption data, predictive analytics, and personalized recommendations for energy savings. These visualizations can help users quickly understand their consumption patterns, identify peak usage times, and assess the potential impact of different behaviors on their future bills.

Moreover, incorporating user-friendly features such as notifications and alerts for unusual consumption patterns, tips for energy efficiency, and scenario analysis tools can further enhance user engagement and satisfaction. For instance, consumers could receive alerts when their usage is significantly higher than usual, prompting them to investigate potential causes and take corrective actions. Scenario analysis tools could allow users to simulate changes in their usage habits and see the projected impact on their bills, empowering them to make informed decisions about their energy consumption.

For utility providers, an intuitive UI can facilitate better communication and engagement with customers, fostering a collaborative approach to energy management. By providing transparent and accessible information, utility companies can build trust with their customers and encourage participation in demand response programs and other energy-saving initiatives.

VI. RESULTS

Our experimental results showcase the effectiveness of employing IoT-enabled sensors and LSTM networks for forecasting electricity bill prices. The model was implemented using the Keras Sequential API and LSTM layers, achieving a test Root Mean Square Error (RMSE) of 0.675. This low RMSE value indicates a high level of prediction accuracy, demonstrating the model's ability to closely approximate actual electricity consumption patterns and billing amounts.

The use of Long Short-Term Memory (LSTM) networks was pivotal in attaining these results. LSTMs are specifically designed to handle temporal sequence data, making them exceptionally well-suited for time-series forecasting tasks such as electricity consumption prediction. The key advantage of LSTMs lies in their ability to capture long-range dependencies and temporal correlations within the data. Unlike traditional recurrent neural networks (RNNs), LSTMs mitigate the vanishing gradient problem, allowing them to retain information over longer periods. This capability is crucial for accurately modeling the complex, time-dependent patterns inherent in electricity usage data, where consumption can vary significantly based on the time of day, day of the week, and seasonal factors.




Fig. 7. Loss graph for the ML Model (convergence at lower value, divergence as number of epochs increase)

The training and validation loss graphs for our LSTM model exhibit a smooth and steady decline, indicating effective learning and convergence of the model. During the training process, the model's loss function, which measures the difference between predicted and actual values, consistently decreased, demonstrating the model's

ability to learn from the data. The convergence of training and validation losses towards lower values confirms the robustness and reliability of the model in making accurate predictions.




Fig. 8. Predicted vs Actual values

The comparison between predicted and actual electricity bill values further underscores the model's accuracy. The predictions made by the LSTM model exhibit a low variance from the actual values, indicating precise forecasting capabilities. This minimal difference is critical for practical applications, as it ensures that consumers and utility providers can rely on the model's predictions for effective energy management and cost optimization. However, it's important to acknowledge that exceptions can be observed in edge cases where there is a significant delta between predicted and actual values. These discrepancies typically arise during periods of unusual consumption patterns or unexpected events that are not well-represented in the training data. For instance, sudden spikes in electricity usage due to extreme weather conditions, appliance malfunctions, or atypical household activities can lead to deviations from predicted values.

These edge cases, while infrequent, highlight potential limitations in the model's predictive capabilities under highly variable conditions. Significant deltas in these scenarios can cause issues, such as inaccurate billing forecasts, which may impact consumer trust and utility provider operations. To mitigate these issues, it is essential to incorporate additional data sources and context-aware algorithms that can dynamically adjust to such anomalies.

VII. CONCLUSION

In conclusion, the integration of IoT-enabled sensors with LSTM networks for electricity bill forecasting showcases a significant leap forward in energy management and cost optimization. Our model achieves an impressive accuracy rate of 92%, with a minimal Root Mean Square Error (RMSE) of 0.675, highlighting its efficacy in accurately predicting future electricity bills. This success owes much to the robust learning capabilities inherent in LSTM networks, adept at capturing the intricate temporal dependencies within electricity consumption data. Coupled with the real-time, high-resolution data provided by IoT sensors, this approach offers unparalleled insights into consumption patterns, empowering consumers to make proactive adjustments in their usage behavior and aiding utility providers in optimizing grid operations and implementing dynamic pricing strategies.

However, while our results demonstrate promising accuracy and reliability, challenges persist, particularly in handling edge cases where significant deviations between predicted and actual values occur. Addressing these outliers requires further research into advanced anomaly detection mechanisms and the incorporation of additional diverse datasets. Moreover, ensuring data privacy and security in IoT deployments remains paramount for widespread adoption. Future research endeavors must focus on developing robust encryption and secure data transmission protocols to safeguard sensitive consumer information. By overcoming these challenges and embracing emerging technologies, we can propel the development of more accurate, reliable, and user-friendly electricity bill forecasting systems, ushering in a new era of smart energy management and optimization.

VIII. FUTURE SCOPE

Building on the promising results of integrating IoT-enabled sensors with LSTM networks for electricity bill forecasting, future research can explore several key areas to enhance the model's robustness and applicability. Firstly, incorporating additional and diverse sensor data, such as environmental factors and appliance-specific usage, could improve the model's accuracy, particularly in edge cases.

Expanding the dataset to include more varied and extensive real-world consumption patterns will also help in better generalizing the model. Additionally, developing advanced anomaly detection mechanisms can identify and adjust for unusual consumption spikes, ensuring more reliable predictions. Exploring hybrid models that combine LSTM with other machine learning or statistical techniques could further enhance predictive capabilities. Furthermore, addressing data privacy and security in IoT deployments will be crucial for widespread adoption, necessitating robust encryption and secure data transmission protocols.

Finally, enhancing the user interface to provide more intuitive and actionable insights can improve user engagement and empower consumers to make informed decisions about their energy usage. These advancements will contribute to more accurate, reliable, and user-friendly electricity bill forecasting systems, benefiting both consumers and utility providers in optimizing energy consumption and cost management.

REFERENCES

- [1] M. Ghofrani, M. Hassanzadeh, M. Etezadi-Amoli and M. S. Fadali, "Smart meter based short-term load forecasting for residential customers," 2011 North American Power Symposium, Boston, MA, USA, 2011, pp. 1-5, doi: 10.1109/NAPS.2011.6025124.
- [2] S. -V. Oprea and A. Bâra, "Machine Learning Algorithms for Short-Term Load Forecast in Residential Buildings Using Smart Meters, Sensors and Big Data Solutions," in IEEE Access, vol. 7, pp. 177874-177889, 2019, doi: 10.1109/ACCESS.2019.2958383.
- [3] .Carroll, Paula & Murphy, Tadhg & Hanley, Michale & Dempsey, Daniel & Dunne, John. (2018). "Household Classification Using Smart Meter Data." Journal of official statistics. 34. 10.1515/jos-2018-0001.
- [4] D. Alahakoon and X. Yu, "Smart Electricity Meter Data Intelligence for Future Energy Systems: A Survey," in IEEE Transactions on Industrial Informatics, vol. 12, no. 1, pp. 425-436, Feb. 2016, doi: 10.1109/TII.2015.2414355.
- [5] Beckel, Christian & Sadamori, Leyna & Staake, Thorsten & Santini, Silvia. (2014). Revealing Household Characteristics from Smart Meter Data. Energy. 78. 397-410. 10.1016/j.energy.2014.10.025.
- [6] M. R. K K, M. N. M, R. Zidan, I. Alsarraj and B. Hasan, "IOT-Based Wireless Patient Monitor Using ESP32 Microcontroller," 2023 24th International Arab Conference on Information Technology (ACIT), Ajman, United Arab Emirates, 2023, pp. 1-6, doi: 10.1109/ACIT58888.2023.10453847.
- [7] A. Othman and N. H. Zakaria, "Energy Meter based Wireless Monitoring System using Blynk Application via smartphone," 2020 IEEE 2nd International Conference on Artificial Intelligence in Engineering and Technology (IICAET), Kota Kinabalu, Malaysia, 2020, pp. 1-5, doi: 10.1109/IICAET49801.2020.9257827.
- [8] Espressif Systems, "ESP32 - ESP32 - Dual-Core Wi-Fi BT BLE SoC - Low Power IoT." espressif.com. <https://www.espressif.com/en/products/socs/esp32>
- [9] InnovatorsGuru, "ZMPT101B AC Voltage Sensor." innovatorsGuru.com. <https://innovatorsGuru.com/wp-content/uploads/2019/02/ZMPT101B.pdf>
- [10] BC Robotics, "YHDC SCT-013-000 Non-Invasive AC Current Sensor." bc-robotics.com. <https://bc-robotics.com/datasheets/yhdc.pdf>
- [11] Keras, "Guide to the Sequential Model." keras.io. https://keras.io/guides/sequential_model/
- [12] TensorFlow, "tf.keras.Sequential API Documentation." tensorflow.org. https://www.tensorflow.org/api_docs/python/tf/keras/Sequential