

AI Enabled and Deep Learning-based Integrated Approach for Early Detection of Breast Cancer

Dr. Pritesh Patil¹, Abhiraj Bondre², Gauri Dighe³ and Kiran Mangde⁴

¹⁻⁴Department of Information Technology, AISSMS Institute of Information Technology, Pune, India

Email: pritesht.patil@aissmsioit.org, abhirajbondre077@gmail.com, gaurisdighe@gmail.com, kiranmangde001@gmail.com

Abstract— The ongoing global health crisis of breast cancer needs prompt and precise diagnostic measures in order to improve outcomes. The routine practice of swiftly interpreting clinical images manually involves considerable time and variability in diagnostic accuracy owing to dissimilar observers. This work describes a fully integrated approach in which cancer detection and diagnostic reporting are automatically performed by AI systems from MRI video sequences. Our proposed system architecture includes client-side frame extraction, deep learning-based classification, distributed backend processing with parallel AI inference, and report generation in PDF format. The performance of our AI systems is clinically viable due to the achievement of clinically high-performance metrics (i.e., accuracy, sensitivity, and specificity). The same AI systems, linked with advanced Web technologies, present a highly scalable, transparent, and, above all, executable system incorporating explainable AI principles. The time taken to analyze data decreased markedly compared to manual interpretation while preserving clinically acceptable diagnostic reliability. Hence, time efficiency and diagnostic accuracy render the system clinically deployable.

Index Terms— Breast cancer detection, deep learning, MRI analysis, diagnostic automation, clinical decision support, explainable AI, report generation.

I. INTRODUCTION

Breast cancer is the most commonly diagnosed cancer in women around the world, posing a special problem to global health. It is estimated that globally, there are approximately 2.3 million breast cancer cases that are attributed each year. This takes up about 11 diagnoses. The application of mammograms, ultrasounds, and MRIs in identifying breast cancer at its initial stages has been established to lead to a significant increase in survival rates as well as the success of the subsequent treatments. Regrettably, the time and skills that image interpretation will necessitate on the part of the physicians, especially during periods of heavy waiting time, are an extra challenge. The opportunities of artificial intelligence operating to conduct complex image recognition tasks present unparalleled opportunities in the area of automated medical diagnostics. In some tasks, AI can solve issues on the same level as radiologists and at times even better. Despite the fact that the published AI research findings are rather encouraging, a number of challenges need to be addressed to put AI to practical use, such as making sure that working processes are not interrupted, delivering the necessary paperwork that will be required when AI is involved, and the healthcare system requires that it should be explainable. The paper introduces an elaborate system that seeks to address the issues of breast cancer detection and the provision of diagnostic reports.

It has a convenient web interface that accepts MRI video inputs and processes the imaging data using state-of-the-art deep learning models deployed on cloud infrastructure and automatically generates detailed diagnostic reports that can be used in the clinic. The system is scale based, leverages parallel processing, and fits well with existing clinical processes to facilitate seamless integration and transparency via explainable AI processes. The main contributions of the work are as follows: (1) cloud-based architecture to improve the efficiency of processing based on parallel frame analysis, (2) an automated workflow to produce diagnostic reports transforming AI findings into real-world clinical records, (3) the critical assessment using standard metrics of medical imaging performance, and (4) a practical implementation demonstrating the viability of clinical implementation in the medical contexts.

II. RELATED WORK

The latest advances in machine learning have proven to be the difference in the way we detect breast cancer. We used to use manually engineered features and the traditional classifiers in the past, which were not always able to generalize across different datasets. However, the introduction of deep convolutional networks has made it possible to automatically learn features directly out of imaging data, and this has really changed the way medical images are analyzed. Khater et al. [1] have developed an explainable AI model that is particularly used to classify breast cancer and uses the Wisconsin Breast Cancer datasets. Their best performing model achieved an impressive 97.7% accuracy on clinical tabular data. They also applied explainable AI methods to identify bare nuclei and area features as the most significant ones in the identification of malignancy. The research was exceptionally focused on model interpretability, employing such approaches as permutation importance, partial dependence plots, and SHAP values. Nevertheless, it is notable that their study primarily focused on the structured clinical data, which in part restricts its usage in the workflows involving image-based diagnostics. Nayak et al. [2] took a further examination of the CNN based techniques of breast cancer detection by infrared imaging. Their model achieved a whopping accuracy of 91.3% on thermal imaging sensors. RFID patient information logging. They used the data provided by the DDSM, TCGA, and UCI repositories and implemented the basic preprocessing methods such as normalization, resizing, and augmentation. Although their results on infrared images were rather encouraging, the study was unsatisfactory in the aspects of the explainability mechanisms and was limited by the variety of the datasets. Another point is that Yang et al. [3] presented a deep learning approach that combines mammography and ultrasound images to estimate malignancy in BI-RADS 4A lesions in women with dense breasts. Their multi-modal fusion method demonstrated an improved diagnostic performance when compared to single modality approaches. Nevertheless, the study was founded on one center, which may limit its applicability, and it did not address automated report generation or the integration into clinical workflows. On the more recent front of MRI-based detection, researchers have been exploring 3D networks and 3D convolutional networks. They are using volumetric data to model spatial correlation and contrast enhancement patterns, which indicate malignancy. Transfer learning based on large-scale data has proved to be rather beneficial, and it is possible to demonstrate a competitive performance even with small amounts of medical imaging data. Although there has been some exciting research, there remains a vast gap between what we are experimenting with and what we can actually use in clinics. Many of the methods available are primarily interested in their classification capabilities, but fail to take into account other valuable practical considerations, such as their efficiency in processing information, their integration with current clinical processes, the necessity of automated documentation, and the ease of understanding the models. Also, a high number of these systems require either special hardware or significant modifications to infrastructure. This study will provide answers to those gaps by developing a system that is simple to access and scale, which can be deployed with little disruption of clinical operations, and at the same time provide comprehensive diagnostic support, such as automated and user-friendly report generation.

III. PROPOSED SYSTEM

Our designed system employs a distributed microservices architecture that assists in isolating various concerns to distinct layers of services and maintaining the services together. The general design of the system and the flow of data in the system are depicted in Figure 1.

A. Frontend Layer

The front end provides the radiologists with an easy-to-use web interface to interface with the system. It is developed using the current JavaScript libraries, which give the possibility to upload MRI videos, track the processing status in real-time, and access the generated reports. The client-side frame extraction is one of its

outstanding features that divides video sequences into single frames and transmits them to the backend. Not only does this reduce network bandwidth, but it is also possible to perform preprocessing via a browser without straining the server and provide users with immediate visual feedback. Frame extraction uses the HTML5 Canvas API to decode video streams and capture frames at a given frequency. The frames captured are then clustered into batches to transmit them efficiently, and the size of the batches is adjusted according to the network conditions and the capabilities of the servers. This batching system assists in evenly distributing the load and avoiding the server being overloaded during peak periods.




Fig. 1. End-to-end system architecture showing the pipeline from MRI video upload to diagnostic report generation and storage

B. API Gateway Layer

The API gateway based on Node.js is the key point of all interactions in the system, which performs the functions of authentication, routing of requests, load balancing, and aggregation of responses. The gateway intelligently allocates the batched frames to a number of AI service instances when it receives batched frames sent by the frontend, using intelligent load balancing algorithms, thus enabling it to be horizontally scaled. Asynchronous processing patterns are also employed in this gateway in order to maximize throughput. It does not wait until the entire frame analysis is complete and then sends a response, but maintains persistent connections open, sending partial results to the frontend as they arrive. The perceived responsiveness with this method is significantly improved and allows radiologists to view initial results even when the processing continues.

C. AI Service Layer

Python-based Flask microservices, which host deep learning models, contain core analytical capabilities. The instances of the service are independent instances and thus they can be scaled horizontally with respect to demand. The AI service consists of three major modules: frame preprocessing, model inference, and result aggregation. The preprocessing module normalizes the incoming frames, resizes, and augments them using a set of operations that conform to the training data distributions. Such transformations make sure that the model is fed with a consistent input regardless of the differences in the MRI equipment. Inference module loads the pre-trained weights of a convolutional neural network and uses forward propagation to make classification predictions and confidence values of each frame. Result aggregation aggregates the predictions of each frame into patient diagnoses via a voting system, which considers the similarity of predictions across frames with their associated confidence scores. This technique reduces the effect of false positives or negatives that may be a result of motion artefact or quality variations within a single frame.

D. Data Management Layer

The Data Management Layer manages patient metadata and previous records in MongoDB. Such a structure provides dynamic schema management and quick queries. Such sensitive information as patient demographics, examination data, processing time, and links to reports is stored in the database. It is also easy to separate the structured metadata and binary documents, and index and retrieve data more efficiently. The generated diagnostic reports in PDF format are stored in the Azure Blob storage. The solution offers permanent and

scalable, and affordable object storage. The integration with Blob storage also includes the versioning feature, and it enables us to track the history of reports and access the previous versions of a report in case of need. Such reports are limited to time-limited signed URLs, which are secure, but can be easily downloaded at the frontend.

E. E- Report Generation Module

Moving on to the Report Generation Module, we automate the creation of reports that turn AI outputs into detailed clinical documents using the jsPDF library. Our report templates adhere to standardized radiological guidelines, which guarantee consistency and thoroughness. Each report features patient information, examination details, AI-finding, classification results with confidence metrics, and clinical recommendations based on any abnormalities detected. The logic behind report generation is designed to adapt to document structure based on the findings. If there's a suspicion of malignancy, the reports will include extra sections that describe the characteristics of the lesion, suggest follow-up procedures, and compare with prior examinations if available. This flexible approach ensures that every report delivers relevant and actionable information tailored to the specific case at hand.

IV. METHODOLOGY

A. Dataset and Preprocessing

The algorithm was developed based on a well-chosen collection of breast MRI examination cases that represent a large diversity of cases, such as benign, malignant lesions of various stages, and normal studies. A sequence of MRI sequence consists of a series of temporal phases, recorded during the administration of a contrast agent, which gives invaluable dynamic improvement data needed in the description of lesions. Preprocessing operations are used to normalize the imaging data in order to prepare the data for the model. The frames are resized to a standardized resolution that is compatible with the input demands of the pre-trained network structure. Additionally, the intensity normalization by z-score standardization makes sure that the ranges of the values are similar.

$$I_{normalized} = \frac{I - \mu}{\sigma} \quad (1)$$

where I represent original intensity values, μ is mean intensity, and σ is standard deviation computed across the dataset.

Training is performed with the help of data augmentation techniques such as random rotations, translations, and brightness adjustments to improve the robustness of a model and reduce overfitting. This method aids in simulating the natural variation in patient position and the various acquisition parameters that are generally observed in clinical practice.

B. Deep Learning Model

The detection model is based on transfer learning, which is based on the well-established CNN architectures that have demonstrated impressive performance in image classification problems. The underlying network, which has been trained on large datasets, provides very rich feature representations, which are well adapted to the medical imaging domain. In the case of model adaptation, we replace the last fully connected layers with classification heads that are specific to tasks. This new architecture has the capability of categorizing a variety of classes, such as normal, benign, and malignant. The training process is in phases as follows: the first phase is the initial frozen training phase, where the classification layers only are adjusted, and the second phase is the fine-tuning, where all the layers are trained at a lower learning rate. Optimization aims at reducing the categorical cross-entropy.

$$L = -\frac{1}{N} \sum_{i=1}^N \sum_{c=1}^C y_{ic} \log(\hat{y}_{ic}) \quad (2)$$

where N is sample count, C is class count, y_{ic} is true label indicator, and $\hat{y}_{ic}$ is predicted probability for class c and sample i . training employs adaptive optimizers with a learning rate scheduling and early stopping based on validation performance to prevent overfitting.

C. Parallel Processing Strategy

The processing of MRI videos is efficient, which implies that hundreds of frames may need to be sifted through to process an exam. To address this, the system employs multi-level parallel processing to maintain the latency to a minimum. It spreads frames batches among multiple cloud-based AI service instances, where each instance can process the frames assigned to it. With the aid of GPU acceleration, such instances can execute several frames simultaneously using batch inference. The aggregation results strategy considers the necessity of

temporal coherence. It achieves this by using smoothing filters on the predictions at the frame level, which would help reduce flickering that may be caused by one frame to another, and eventually help in more stable measurements of patients. The ultimate diagnosis is made based on:

$$D = \arg \max_c \sum_{f=1}^F w_f \cdot p_{fc} \quad (3)$$

where D is predicted diagnosis, F is total frames, w_f is weight assigned to frame f based on quality and confidence, and p_{fc} is predicted probability for class c in frame f .

D. Explainable AI Integration

The system is based on explainable AI to build trust and clarify things in clinical settings. In predictions, the model provides attention maps, which are pictorial and which depict what parts of the images contributed significantly to the process of making the classification. This level of transparency will allow the radiologists to confirm that the AI is rational in a way that is consistent with their clinical experience, which will raise their confidence in automated judgments and help to detect inaccuracies.

V. RESULTS AND EVALUATION

The proposed model demonstrated high diagnostic accuracy across multiple categories. Receiver Operating Characteristic (ROC) analysis yielded a high Area Under the Curve (AUC), confirming the model's ability to differentiate between normal, benign, and malignant cases. These findings indicate that the system can be reliably used in clinical decision-making.

A. Classification Performance

In regard to classification performance, our model has proven to be remarkably accurate when compared with several diagnostic categories. The metrics are specific and sensitive, and this is relevant in the clinical setting where false negatives (underdiagnosed cancers) and false positives (unnecessary procedures) can be harmful. We also conducted receiver operating characteristic analysis, which gave a high area under the curve, which represents the high ability of the model to differentiate between normal, benign, and malignant cases. In the Table I, These findings indicate that the model can be relied on when making clinical decisions.

B. Efficiency Metrics

Processing speed plays a vital role on the efficiency front in terms of publicity of the system in a clinical setting. We have now gone far beyond our system compared with the old manual interpretation methods. The duration of time which is spent on a full MRI running analysis and uploading to the report generation is around 45-60 seconds, a radical contrast to the 15-20 minutes it normally takes to have a radiologist conduct a manual review. In addition, the parallel processing architecture can be expanded to accommodate more instances of services. Our distributed architecture has been demonstrated to be able to cope with more clinical workloads effectively, with almost linear performance increase with the addition of computational resources, and load testing has confirmed that our architecture has the capacity to meet its performance targets.

TABLE I. PERFORMANCE METRICS OF THE PROPOSED MODEL

Metrics	Value (%)
Accuracy	94.6
Sensitivity	93.2
Specificity	95.8
Precision	92.7
F1 Score	93.0
AUC(ROC)	0.96

C. Report Quality Assessment

In our quality assessment of reports, the experienced radiologists were closely examining the reports that were generated with the aim of determining their completeness, accuracy, and usefulness in clinical settings. The responses that we got indicated that the reports contained all the necessary information, which was arranged in a manner that can be considered to comply with professional standards. The automated recommendations provided useful advice that aligned with clinical protocols most of the time, which showed that the system can be used in the actual clinical setting.

VI. DISCUSSION

The experimental results demonstrate that the proposed AI-enabled and deep learning-based integrated system is capable of delivering reliable and clinically meaningful breast cancer detection from MRI video sequences. The achieved classification performance, with an accuracy of 94.6%, sensitivity of 93.2%, and specificity of 95.8%, indicates that the system effectively balances the trade-off between false positives and false negatives, which is critical in clinical diagnostic settings. High sensitivity ensures that malignant cases are rarely missed, while strong specificity minimizes unnecessary follow-up procedures for benign cases. When compared with existing deep learning-based breast cancer detection approaches reported in the literature, the proposed system exhibits competitive or superior performance while addressing several practical limitations of prior works. Many existing studies focus primarily on classification accuracy using static images or single modalities and often neglect real-time deployment considerations, automated documentation, and clinical workflow integration. In contrast, the proposed framework emphasizes an end-to-end pipeline that not only performs accurate classification but also supports scalable cloud-based deployment, parallel processing of MRI frames, and automated generation of structured diagnostic reports. This holistic design significantly enhances the applicability of the system in real clinical environments. The adoption of a distributed microservices architecture and parallel frame-level inference plays a crucial role in improving system efficiency. The reduction in total analysis time from approximately 15–20 minutes in manual interpretation to 45–60 seconds using the proposed system demonstrates its potential to reduce radiologist workload and increase patient throughput. Such time efficiency is particularly valuable in high-volume diagnostic centers, where delays in image interpretation can adversely affect patient outcomes. Moreover, the near-linear scalability observed during load testing suggests that the system can accommodate increasing clinical demand with minimal architectural changes. Another notable aspect of the proposed approach is the integration of explainable AI mechanisms. By providing attention maps that highlight diagnostically relevant regions in MRI frames, the system enhances transparency and fosters trust among clinicians. Explainability is a key requirement for clinical adoption of AI systems, as it allows radiologists to verify model decisions and align AI-driven insights with their domain expertise. This interpretability also supports error analysis and model refinement, contributing to safer deployment in medical settings. Despite its strengths, the proposed system has certain limitations that should be acknowledged. The current implementation is primarily validated on breast MRI data, which may limit generalizability across other imaging modalities such as mammography or ultrasound. Additionally, while the dataset used includes a diverse range of cases, further validation on multi-center and larger-scale datasets is necessary to ensure robustness across different scanners, acquisition protocols, and patient populations. The system also relies on pre-trained deep learning models, which, although effective, may benefit from further customization using institution-specific data. Overall, the discussion of results indicates that the proposed system successfully bridges the gap between AI research and practical clinical deployment. By combining high diagnostic performance, efficient processing, automated reporting, and explainability, the framework presents a balanced and clinically relevant solution for early breast cancer detection. These characteristics position the system as a promising decision-support tool that can assist radiologists in improving diagnostic accuracy, efficiency, and consistency in routine clinical practice.

VII. CONCLUSION

This paper presented a detailed system that was designed to support AI-based breast cancer detection and the generation of diagnostic reports based on the MRI video sequences. The cloud-based architecture is a good combination of state of the-art web technologies and deep learning, which creates a practical and scalable solution that can be used in clinics. The results of the evaluation present impressive performance in classification with high accuracy, sensitivity, and specificity of the different diagnostic categories. The system addresses the major issues of closing the gap between AI research and clinical practice since it is able to provide continuous automation, starting with image acquisition and up to detailed report generation. The parallel processing architecture ensures that the throughput is efficient, whereas the automated report generation ensures that the documentation is of the clinical standards. With explainable AI, we are able to improve transparency and establish trust in the clinical setting. All these features make the system a valuable resource in the optimization of radiological processes and diagnostic performance. There are several improvements that we are going to work on in the future. To improve the clinical utility of the system, we may incorporate state-of-the-art explainability techniques that indicate some areas in the system that are of interest to facilitate the process of training. Other imaging modalities including mammography and ultrasound, will be added to its applicability. Moreover, the history of the patients and the tracking options will also be included, and this will allow for the full risk

assessment and monitoring of the treatment. Further validation in other clinical environments will give the required feedback, which can be fine-tuned. By collaborating with the healthcare institutions, we will be able to ensure that the system will be developed as per the clinical and regulatory requirements. It is anticipated that the long-term goal is to transform AI-aided diagnostic systems into a mainstream aspect of contemporary radiology practice, improving patient outcomes because of their earlier identification and higher quality of diagnostic outcomes.

ACKNOWLEDGMENT

The authors would like to express their sincere gratitude to the Department of Information Technology, AISSMS Institute of Information Technology, Pune, for providing the necessary infrastructure and support to carry out this research work. The authors also extend their heartfelt thanks to Dr. Pritesh Patil, Assistant Professor of the Department of Information Technology, for his constant guidance, encouragement, and valuable insights throughout the course of this study.

REFERENCES

- [1] T. Khater, A. Hussain, R. Bendardaf, I. M. Talaat, H. Tawfik, S. Ansari, and S. Mahmoud, "An explainable artificial intelligence model for the classification of breast cancer," *IEEE Access*, vol. 11, pp. 5618–5633, 2023.
- [2] N. Nayak, D. Kumar, and A. Malhotra, "A CNN-based approach for early detection of breast cancer using infrared imaging," in *Proc. Int. Conf. Intell. Syst. Adv. Appl. (ICISAA)*, Pune, India, Oct. 2024, pp. 1–4.
- [3] Y. Yang, Y. Zhong, J. Li, J. Feng, C. Gong, Y. Yu, and Y. Hu, "Deep learning combining mammography and ultrasound images to predict the malignancy of BI-RADS US 4A lesions in women with dense breasts: A diagnostic study," *Eur. Radiol.*, vol. 33, no. 11, pp. 8406–8414, 2023.
- [4] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conf. Compute. Vis. Pattern Recognition*, 2016, pp. 770–778.
- [5] L. Shen et al., "Deep learning to improve breast cancer detection on screening mammography," *Sci. Rep.*, vol. 9, no. 1, pp. 1–12, 2019.
- [6] W. Cao, H. Chen, Y. Yu, N. Li, and W. Chen, "Changing profiles of cancer burden worldwide and in China: A secondary analysis of the global cancer statistics 2020," *Chin. Med. J.*, vol. 134, no. 7, pp. 783–791, 2021.
- [7] D. Sheth and M. L. Giger, "Artificial intelligence in the interpretation of breast cancer on MRI," *J. Magn. Reason. Imaging*, vol. 51, no. 5, pp. 1310–1324, 2020.
- [8] S. G. Kandlikar et al., "Infrared imaging technology for breast cancer detection—Current status, protocols and new directions," *Int. J. Heat Mass Transf.*, vol. 108, pp. 2303–2320, 2017.
- [9] National Cancer Institute, "SEER Stat Fact Sheets: All Cancer Sites," 2024.
- [10] World Health Organization, "Breast Cancer Data," 2024.
- [11] National Cancer Institute, "SEER Stat Fact Sheets: Breast Cancer Stats," 2024.
- [12] T. Mahmood, A. Rehman, T. Saba, L. Nadeem and S. A. O. Bahaj, "Recent advancements and future prospects in active deep learning for medical image segmentation and classification," *IEEE Access*, 2023.
- [13] G. Meena, K. K. Mohbey, M. Acharya and K. Lokesh, "An improved convolutional neural network-based model for detecting brain tumors from augmented MRI images," *Journal of Autonomous Intelligence*, vol. 6, 2023.
- [14] G. Meena, K. K. Mohbey and S. Kumar, "Monkeypox recognition and prediction from visuals using deep transfer learning-based neural networks," *Multimedia Tools and Applications*, pp. 1–25, 2024.
- [15] G. Meena, A. Indian, K. K. Mohbey and K. Jangid, "Point of interest recommendation system using sentiment analysis," *Journal of Information Science Theory and Practice*, vol. 12, pp. 64–78, 2024.
- [16] T. Mahmood, A. Rehman, T. Saba, Y. Wang and F. S. Alamri,
- [17] "Alzheimer's disease unveiled: Multi-modal neuroimaging and computational methods for enhanced diagnosis," *Biomedical Signal Processing and Control*, vol. 97, p. 106721, 2024.
- [18] H. W. Loh et al., "Application of deep learning models for automated identification of Parkinson's disease: a review (2011–2021)," *Sensors*, vol. 21, p. 7034, 2021.
- [19] T. Mahmood et al., "A brief survey on breast cancer diagnostic with deep learning schemes using multi-image modalities," *IEEE Access*, vol. 8, pp. 165779–165809, 2020.
- [20] M. Torabi, A. H. Rasouli, Q. J. Wu, W. Cao and F. Pourpanah, "Self supervised adversarial adaptation network for breast cancer detection," *Engineering Applications of Artificial Intelligence*, vol. 133, p. 108489, 2024.
- [21] N. Qian et al., "Lesion attention guided neural network for contrast enhanced mammography-based biomarker status prediction in breast cancer," *Computer Methods and Programs in Biomedicine*, p. 108194, 2024.
- [22] T. Mahmood et al., "Harnessing the power of radiomics and deep learning for improved breast cancer diagnosis," *Expert Systems with Applications*, vol. 249, p. 123747, 2024.
- [23] T. Mahmood et al., "Breast lesions classifications of mammographic images using a deep convolutional neural network-based approach," *PLoS One*, vol. 17, p. e0263126, 2022.

- [24] S. Prusty, S. Patnaik, S. K. Dash and S. G. P. Prusty, "SEMELLR: A meta-learning approach to classify breast cancer," *Engineering Applications of Artificial Intelligence*, vol. 129, p. 107630, 2024.
- [25] I. Nissar, S. Alam, S. Masood and M. Kashif, "MOB-CBAM: Dual channel attention-based deep learning model for breast cancer subtype prediction," *Computer Methods and Programs in Biomedicine*, vol. 248, p. 108121, 2024.
- [26] K. M. M. Uddin, N. Biswas, S. T. Rikta and S. K. Dey, "Machine learning-based diagnosis of breast cancer utilizing feature optimization," *Computer Methods and Programs in Biomedicine Update*, vol. 3, p. 100098, 2023.
- [27] G. Manzo et al., "Breast cancer survival analysis agents for clinical decision support," *Computer Methods and Programs in Biomedicine*, vol. 231, p. 107373, 2023.
- [28] H. Yuan and H. Xu, "Deep multi-modal fusion network for breast cancer survival prediction," *Computer Methods in Biomechanics and Biomedical Engineering*, pp. 1–14, 2023.
- [29] B. Györfy, "Survival analysis across transcriptome identifies biomarkers" in breast cancer," *Computational and Structural Biotechnology Journal*, vol. 19, pp. 4101–4109, 2021.
- [30] T. Mahmood, J. Li, Y. Pei and F. Akhtar, "Deep transfer learning for breast abnormality prognosis," *Biology*, vol. 10, p. 859, 2021.
- [31] J. Varghese, "Artificial intelligence in medicine: chances and challenges," *Visceral Medicine*, vol. 36, pp. 443–449, 2020.
- [32] A. B. Arrieta et al., "Explainable AI: Concepts and opportunities," *Information Fusion*, vol. 58, pp. 82–115, 2020.
- [33] N. A. Wani, R. Kumar, J. Bedi and I. Rida, "Explainable AI-driven IoMT fusion," *Information Fusion*, p. 102472, 2024.
- [34] L. K. Singh, M. Khanna and R. Singh, "Soft-computing feature selection for breast cancer prediction," *Multimedia Tools and Applications*, pp. 1–66, 2024.
- [35] P. Manikandan, U. Durga and C. Ponnuraja, "An integrative ML framework for classifying SEER breast cancer," *Scientific Reports*, vol. 13, p. 5362, 2023. UCI Machine Learning Repository, "Breast Cancer Wisconsin Diagnostic Dataset," 2024
- [36] S. Lundberg, "A unified approach to interpreting model predictions," arXiv:1705.07874, 2017.
- [37] R. Setiono, "Extracting rules from pruned neural networks," *Artificial Intelligence in Medicine*, vol. 8, pp. 37–51, 1996.
- [38] H. Koyuncu and R. Ceylan, "ANN based on rotation forest for biomedical classification," in *TSP 2013*, pp. 581–585, IEEE, 2013.
- [39] S. Aalaei et al., "Feature selection using genetic algorithm for breast cancer diagnosis," *Iranian Journal of Basic Medical Sciences*, vol. 19, p. 476, 2016.
- [40] A. K. Naik, V. Kuppli and D. R. Edla, "Efficient feature selection using generalized classifier and bat algorithm," *Soft Computing*, vol. 24, pp. 4575–4587, 2020.
- [41] T. Kıyan and T. Yıldırım, "Breast cancer diagnosis using statistical neural networks," *IU-J. Electron. Eng.*, vol. 4, pp. 1149–1153, 2004.
- [42] M. Karabatak and M. C. Ince, "Expert system for breast cancer detection," *Expert Systems with Applications*, vol. 36, pp. 3465–3469, 2009.
- [43] J. A. Sidey-Gibbons and C. J. Sidey-Gibbons, "Machine learning in medicine," *BMC Medical Research Methodology*, vol. 19, pp. 1–18, 2019.
- [44] O. I. Obaid et al., "Performance evaluation of ML in breast cancer classification," *International Journal of Engineering and Technology*, vol. 7, pp. 160–166, 2018.
- [45] M. M. Hassan et al., "Comparative assessment of ML algorithms for breast cancer detection," *Decision Analytics Journal*, p. 100245, 2023.
- [46] N. A. Wani, R. Kumar and J. Bedi, "Fusion modeling for enhanced breast cancer classification," *Engineering Applications of Artificial Intelligence*, vol. 136, p. 108939, 2024.
- [47] V. Chaurasia and S. Pal, "Applications of machine learning to diagnose breast cancer," *SN Computer Science*, vol. 1, p. 270, 2020.
- [48] N. Liu et al., "Novel intelligent model for breast cancer diagnosis," *Information Processing and Management*, vol. 56, pp. 609–623, 2019.
- [49] M. Abdar et al., "Nested ensemble technique for breast cancer diagnosis," *Pattern Recognition Letters*, vol. 132, pp. 123–131, 2020.
- [50] B. Sahu, S. Mohanty and S. Rout, "Hybrid breast cancer classification approach," *EAI Endorsed Transactions on Scalable Information Systems*, vol. 6, 2019.

AUTHOR BIOGRAPHIES

First Author– Dr. Pritesh Patil is the Assistant Professor of the Department of Information Technology at AISSMS Institute of Information Technology, Pune, India. He holds extensive academic and research experience in the field of information technology and has guided numerous undergraduate projects. His areas of interest include Databases, Computer Network, Mobile Computing, Cloud Computing, Machine Learning.

Second Author– Abhiraj Bondre is a final-year undergraduate student in the Department of Information Technology at AISSMS Institute of Information Technology, Pune, India. His areas of interest include artificial intelligence, machine learning, and cloud computing.

Third Author– Gauri Dighe is a final-year undergraduate student in the Department of Information Technology at AISSMS Institute of Information Technology, Pune, India. His areas of interest include full stack development, data science.

Fourth Author– Kiran Mangde is a final-year undergraduate student in the Department of Information Technology at AISSMS Institute of Information Technology, Pune, India. His areas of interest include web technologies, cybersecurity and machine learning.