

Automated Construction Defect Monitoring using Image Processing

Shubhada Pradeep Deshmukh¹, Karthik Nagarajan², Raju Narwade³ and Kiran Arjun Deshmukh⁴

¹⁻³Department of Civil Engineering, Pillai HOC College of Engineering and Technology Mumbai, India

Email: shubhadakd95@gmail.com, knagarajan@mes.ac.in, marwade@mes.ac.in, kdeshmukh@pvppcoe.ac.in

⁴Department of Information Technology, Vasantdada Patil College of engineering and Visual Arts, Mumbai, India

Abstract— The construction industry frequently faces challenges in maintaining quality control during various phases of construction, which can lead to costly rework and delays. To overcome this issue, this paper presents an Automated Construction Defect Monitoring System Using Image Processing, a technology-driven solution designed to monitor and ensure the quality of construction processes in real-time. By harnessing advanced image processing techniques, such as object recognition, edge detection, and pattern analysis, the proposed system automatically inspects construction elements such as concrete surfaces, bricklaying, and overall structural integrity. The system captures images via high- resolution cameras and processes them using algorithms to detect defects, irregularities, and non-compliance with construction standards. The results are then provided to site managers and construction engineers in the form of real-time feedback, enabling timely corrective actions. The integration of this automated system improves accuracy, reduces human error, and accelerates the overall quality assurance process in construction projects.

Index Terms— Automated quality control, image processing, construction quality assurance, real-time monitoring, defect detection, object recognition, construction defects, machine learning, construction inspection.

I. INTRODUCTION

The construction industry is inherently complex, involving multiple phases that require stringent quality control to ensure the durability, safety, and compliance of structures with design specifications. Traditionally, construction quality control (CQC) has relied heavily on manual inspection, which can be subjective and prone to human error. Manual inspections are time- consuming, and the possibility of overlooking defects can lead to long-term structural issues, increased costs, and safety concerns. Consequently, there is a growing need for more efficient and accurate quality control methods.

In recent years, advancements in image processing and machine learning have opened up new avenues for automating quality control processes in construction. The Automated Construction Defect Monitoring System utilizes image processing algorithms to analyze images captured at various stages of construction. The system can identify and categorize defects in construction materials, detect deviations from design standards, and even assess the overall integrity of a structure [2].

The integration of artificial intelligence (AI) and machine learning in image processing enables the system to continually learn and improve its defect detection capabilities.

Additionally, the system can provide historical data for analysis, offering valuable insights into the construction process and helping to predict potential quality issues before they become major problems [3]. In summary, the Automated Construction Quality Control System provides an innovative solution to enhance construction quality, streamline inspections, and ensure compliance with standards, all while reducing reliance on manual labor and human judgment. The system is poised to revolutionize the construction industry by integrating cutting-edge image processing technology for efficient, real-time quality assurance [4][5].

II. LITERATURE REVIEW

A. Wei Xu et al. (2023)

This paper presents an innovative system for construction quality control that integrates automated image analysis with real-time monitoring. Using advanced image segmentation and defect recognition algorithms. The paper also discusses the integration of this system with IoT devices for enhanced monitoring and reporting.

B. Kunal S. Sharma et al. (2023)

This paper presents an automated quality control system for construction that utilizes deep learning and image processing techniques. The authors use deep neural networks (DNNs) to identify and classify defects in construction based on images taken during construction. The study demonstrates the system's high accuracy in detecting defects, making it a promising tool for improving construction quality control processes.

C. Hongjun Liu et al. (2022)

This study combines deep learning with image processing techniques to detect defects in construction images automatically. The authors utilize convolutional neural networks (CNNs) to improve the accuracy of defect detection, particularly in detecting subtle cracks and surface irregularities.

D. Harish S. Raj et al. (2022)

This paper discusses the integration of machine learning and image processing to highlight the benefits of using training data to teach the system to recognize various defects in construction materials. The approach is shown to significantly reduce manual inspection time and improve defect detection accuracy.

E. R. Srinivasan et al. (2021)

This paper focuses on developing a real-time quality assurance system that uses computer vision to monitor the quality of work on construction sites. The results are displayed in real time, allowing quick corrective action to be taken.

F. John L. Williams et al. (2021)

This research explores the use of image processing for assessing structural integrity during construction. The authors focus on the detection of deformations, cracks, and surface defects in load-bearing structures using image analysis.

Gap Analysis

Defect Detection in Construction Challenges and Solutions

- Limited Real-time Implementation: Current studies mainly use theoretical models or offline analysis.
- Inconsistent Accuracy in Diverse Conditions: Image processing models struggle with varying lighting, shadows, and environmental factors.
- Lack of Standardized Datasets: No widely accepted benchmark dataset for training and evaluating defect detection models.
- Limited Research on Integrating with BIM and IoT: Limited research on image-based quality control integration with BIM and IoT sensors.
- Difficulty Detecting Subtle Defects: Current image processing techniques struggle with fine cracks, surface roughness variations, and material inconsistencies.

Goal of Dissertation: "To enhance quality control in construction through automated image analysis."

Objectives:

- To collect images of construction work at various stages for analysis and defect detection.
- To build image processing algorithms suitable of identifying and analyzing defects in construction materials and structures.

- To create a user interface for efficient reporting of detected quality issues and providing real-time feedback to construction teams.
- To evaluate the system's effectiveness in enhancing construction quality by comparing the results with manual inspection methods.

Problem statement

“Quality control in construction can be labour-intensive and prone to errors. This project aims to automate the process using image analysis.”

III. RESEARCH METHODOLOGY

A. Research Framework

- Conduct a literature review on quality control techniques.
- Gather images of construction work for analysis.
- Create image processing algorithms for defect detection.
- Implement a user-friendly interface for quality reporting.
- Validate the system's effectiveness on-site.

B. Dataset and Tool information: - Tools

- AR Development Tools Overview
- OpenCV: chiefly used for computer vision tasks.
- Python: High-level programming language ideal for AR applications.
- Git/GitHub: Essential for managing project's source code.
- Integrated Development Environment (IDE): Tools like PyCharm, Visual Studio Code, Jupyter Notebooks.
- 3D Modeling Software (Optional): Blender or Unity.

Dataset

- AR Application Algorithm Training and Testing
- COCO: Over 300,000 images with 2.5 million labelled instances, covering 80 object categories.
- Augmented Reality Datasets: Specific datasets designed for AR applications, enhancing system performance.
- Custom Datasets: Custom datasets tailored to specific objects or scenarios.

C. Study area

This research was applied to a construction project of G+11 residential building located at Wagholi, Pune, Maharashtra, India as shown in Fig. 2 Shows study area.




Figure 1. System Architecture




Figure 2. Study Area

(Source: <https://maps.app.goo.gl/2mbXqeMYfeu26juH6>)

D. Data Collection and Implementation

Data Collection

The first step in data collection is to gather a diverse dataset of images from construction sites. The following types of images need to be collected:

- Oblique Cracks: These cracks run diagonally across the surface, typically caused by shear stresses or structural issues.
- Horizontal Cracks: These cracks occur horizontally along the surface, often indicating issues such as settlement or poor construction materials.
- Transverse Cracks: These cracks appear perpendicular to the structural elements and are commonly associated with shrinkage or temperature changes.




Figure 3: Oblique Cracks Images




Figure 4. Horizontal Cracks

Figure 5. Transverse Crack

No-Crack Images: These images represent surfaces that are free of cracks, providing the necessary background data for the model to differentiate between defect and non-defect scenarios.

To obtain the most accurate and comprehensive data, these images should be collected under various conditions such as Lighting Variability, Angle and Distance

Implementation of Image Preprocessing

Afterwards data collection, preprocessing is executed to prepare the images for training the CNN model. The preprocessing steps include: Image Resizing, Image Normalization, Data Augmentation, Rotation, Flipping, Zooming and Cropping

These augmentation techniques ensure the model can generalize better and learn from a wide range of scenarios, improving its performance when integrated in real-world environments.

Implementation of the CNN Model

The central part of the system is the implementation of a Convolutional Neural Network (CNN), which is capable of analyzing the collected images to detect and classify cracks and non-cracks. The model is designed with numerous layers that allow it to automatically learn the trait of the images, such as edges, textures, and crack patterns. The steps involved in implementing the CNN model are Model Architecture, Model Training, Loss Functions.




Figure 6. CNN Architecture

Real-Time Implementation

After training the model, it is deployed in a real-time system that can process images from construction sites:

- Image Capture: Real-time images are captured through cameras or drones placed strategically around the construction site.
- Defect Detection: The captured images are input into the trained CNN model to detect the type of crack defect or no crack
- Alerting: When a defect is detected, the system triggers an alert, notifying the construction team of the specific crack type and its location.
- Visualization: The system highlights the detected crack in the image, marking the region of interest, which helps construction teams to easily locate and address the defect.

E. Deployment and System Integration

Once the system is validated, it is integrated into the construction workflow

- Monitoring: The system continuously monitors the construction site through live images captured by cameras or drones.
- User Interface (UI): A simple, user-friendly interface is designed to display detected cracks, alerts, and reports. The UI helps the construction team to easily interpret the data and make informed decisions.
- Continuous Data Collection: As the system operates, additional data can be collected, expanding the dataset and allowing for the model to be retrained and improved over time.

IV. RESULTS AND ANALYSIS

A. Data Augmentation with Image Data Generator

Purpose of Augmentation: In image-based machine learning, having a robust dataset is crucial. Data augmentation increases the Diversity of the mentoring set without needing to collect more data. This is particularly beneficial when working with limited data, as in structural crack analysis, where gathering diverse and labelled crack images can be challenging.

Augmentation Techniques: The code applies several transformations to each image such as Rotation (up to 20 degrees), Width and Height Shifts (0.2), Shear and Zoom, Flips (Horizontal & Vertical), Normalization

B. Directory Structure and Class Labelling

Flow from Directory: The Image Data Generator utilizes the flow from directory method to load images and their corresponding labels automatically from folders organized by crack. This helps the model associate each folder (or crack type) with a specific label.

Automatic Labelling: The directory names serve as class labels, which is why class mode is set to 'categorical'. Each crack type (e.g., longitudinal, transverse) is assigned a unique index, enabling the model to treat this as a multi-class classification problem. The class indices dictionary generated here will map each folder name to a numeric label.

C. Input Dimensions and Batch Processing

Target Size: Each image is resized to a fixed 150x150 pixels. This uniformity is vital for deep learning models, which require consistent input sizes. While resizing may head to a minor loss in image detail, it's balanced by making the model training process feasible on typical hardware.

Batch Processing: The images are processed in batches of 32. Batching helps in efficient memory usage and accelerates the training by computing updates across multiple images simultaneously.

```
# Check the classes (label-wise folders should be automatically
print("Class labels:", train_generator.class_indices)

Found 1007 images belonging to 4 classes.
Class labels: {'Without crack': 0, 'longitudinal crack': 1, 'ob'
```

Figure 7. Batch Processing

D. Architecture Overview

This CNN is structured to progressively pull out increasingly complicated features from the input images, allowing it to learn and distinguish between distinct types of cracks.

E. Layer-by-Layer Breakdown

First Convolutional Block

Conv2D Layer: The first layer has 32 filters with a $3 \times 3 \times 33 \times 3$ kernel size and uses the ReLU (Rectified Linear Activation) function. This layer helps to detect basic features in the images.

MaxPooling2D Layer: Pooling reduces the spatial dimensions (width and height) of the feature maps, helping the model focus on the most prominent features and reducing computational load.

Second Convolutional Block

Conv2D Layer: The second convolutional layer has 64 filters, increasing the feature depth. The ReLU activation continues to enable non-linearity, helping the model capture more detailed and complex patterns specific to each crack type.

MaxPooling2D Layer: Reduces the spatial dimensions again, compressing the information while retaining key features from the image.

Third Convolutional Block

Conv2D Layer: This layer uses 128 filters, allowing the network to learn even more complex patterns. At this stage, the network is likely recognizing intricate details within cracks that differentiate one type from another (such as differences in crack direction or shape).

MaxPooling2D Layer: The pooling here reduces the scale of the feature maps, preserving the most essential features while further minimizing computational complexity.

Flatten Layer: After the convolutional and pooling layers, the 3D feature maps are "flattened" into a 1D vector, which prepares the data for the linked layers.

Dense Layers (Fully Connected Layers)

First Dense Layer (512 neurons): This compact layer with ReLU activation functions as a classifier, learning non-linear combinations of the traits extracted from the convolutional layers. It permits the model to form complex mappings between image features and crack types.

Output Layer: The final dense layer has 4 neurons (one for each crack type: longitudinal, transverse, diagonal, and shear) and uses the softmax enablement function, which provides probability distributions over the 4 classes. The model will predict the class with the topmost probability.

F. Compilation of the Model

Optimizer (Adam): The Adam optimizer is well-suited for this classification task due to its adaptive learning rate, which makes it effective for tasks with noisy gradients or high data variability.

Loss Function (Categorical Cross entropy): Since this is a multi-class classification problem with jointly exclusive classes, categorical crossentropy is an appropriate choice. It calculates the glitch between the estimated and actual class distributions, guiding the model to minimize this error during training.

Metrics (Accuracy): Accuracy is the chosen metric here, as it measures the percentage of correct predictions, which is intuitive and suitable for balanced classification tasks.

Model: "sequential_3"			31/31 - 23s - 746ms/step - accuracy: 0.9744 - loss: 0.0673	
Layer (type)	Output Shape	Param #		
conv2d_9 (Conv2D)	(None, 148, 148, 32)	800	Epoch 36/50	
max_pooling2d_9 (MaxPooling2D)	(None, 74, 74, 32)	0	31/31 - 1s - 23ms/step - accuracy: 0.9688 - loss: 0.0475	
conv2d_10 (Conv2D)	(None, 72, 72, 64)	18,400	Epoch 37/50	
max_pooling2d_10 (MaxPooling2D)	(None, 36, 36, 64)	0	31/31 - 23s - 749ms/step - accuracy: 0.9662 - loss: 0.0893	
conv2d_11 (Conv2D)	(None, 34, 34, 128)	73,856	Epoch 38/50	
max_pooling2d_11 (MaxPooling2D)	(None, 17, 17, 128)	0	31/31 - 1s - 26ms/step - accuracy: 0.9688 - loss: 0.0612	
Flatten_3 (Flatten)	(None, 36992)	0	Epoch 39/50	
dense_6 (Dense)	(None, 512)	19,940,416	31/31 - 23s - 731ms/step - accuracy: 0.9692 - loss: 0.0912	
dense_7 (Dense)	(None, 4)	2,052	Epoch 40/50	
Total params: 19,940,736 (72.62 MB)			31/31 - 1s - 22ms/step - accuracy: 0.9375 - loss: 0.1245	
Trainable params: 19,939,736 (72.62 MB)			Epoch 41/50	
Non-trainable params: 0 (0.00 B)			31/31 - 24s - 765ms/step - accuracy: 0.9692 - loss: 0.0772	
			Epoch 42/50	
			31/31 - 1s - 26ms/step - accuracy: 0.9375 - loss: 0.0911	

Figure 8. Layer-by-Layer Breakdown and Accuracy

G. Image Loading and Preprocessing

Image Loading: The image.load_img function loads the test image and resizes it to the target size of 150×150150 \times 150X150X150 pixels to match the input dimensions required by the model.

Image Conversion: The loaded image is converted to a NumPy array using image.img_to_array, transforming it into a format compatible with the model's input shape.

Normalization: The image array values are divided by 255 to normalize the pixel values to the range [0, 1]. This normalization is consistent with the training data, ensuring that the test image is processed in the same way.

Expanding Dimensions: By adding an extra dimension with np.expand_dims, the code adjusts the shape of the image array to (1, 150, 150, 3). This shape reflects a batch of one image, which is essential since models trained in Keras typically expect batch dimensions for input.

H. Prediction Process

Model Prediction: The model's predict function returns a set of probabilities for each class. This array indicates the model's confidence in each crack type for the given image.

Class Identification: Using np.argmax (predictions, axis=-1), the code identifies the index of the class with the maximum probability, representing the predicted crack type.

I. Mapping to Crack Type Labels

Class Labels: The trained generator class indices dictionary provides a mapping of class labels to numerical indices. By listing its keys, the code creates an ordered list of class names.

Predicted Crack Type: Using the predicted class index, the code retrieves the corresponding class label (e.g., "longitudinal", "transverse") and stores it as predicted crack type.

J. Visualization




Figure 9. predicted crack type

Matplotlib Visualization: The code uses matplotlib.pyplot to display the genuine test image along with the predicted crack type as the title. This visual output is particularly useful for verifying the model's predictions against actual crack images.

Removing Axis: plt.axis('off') hides the axis for a cleaner presentation, focusing attention on the image and the predicted label.

Accuracy

The plot training history function visually presents the training progress of your CNN model by plotting both accuracy and loss over each epoch. This provides intrinsic insights into the model's learning patterns and helps identify untapped issues like overfitting or underfitting. Here's an explanation of each part of the function:

Plotting Accuracy

- Subplot for Accuracy: plt.subplot (1, 2, 1) creates a subplot for accuracy, placing it in a 1x2 grid on the left.
- Training Accuracy: plt.plot (history.history ['accuracy']) plots the precision values recorded for each epoch from the model's history.
- Labeling: Adding titles, labels, and a legend helps interpret the graph easily. For example, the x-axis represents the number of epochs, and the y-axis shows accuracy, with a legend indicating it's training accuracy.
- Insights: This plot shows the model's ability to correctly classify images during training. A consistently increasing trend in accuracy indicates effective learning.

Plotting Loss

- Subplot for Loss: plt.subplot (1, 2, 2) designates a second subplot on the right for the loss values.
- Training Loss: plt.plot (history.history ['loss']) displays the loss values over epochs, representing the model's error during training. Lower loss values indicate a better fit between the model's predictions and the true labels.
- Labelling: Titles, labels, and legends provide context, with the y-axis representing the loss value.
- Insights: Ideally, the loss should decrease steadily as the model acquires from the training data. If the loss starts increasing after initially decreasing, it might signal overfitting, where the model is learning patterns specific to the training data and not generalizing well.
- Overall Layout and Display: plt.tight_layout(): This method adjusts the spacing between subplots for a cleaner, more organized presentation, making it easier to view both graphs side-by-side.

plt.show(): This command displays the plot, allowing a quick visual analysis of the model's training progression




Fig 10. Graph.1. Training and Validation Accuracy



Fig 11. Graph 2. Training and Validation Loss

V. CONCLUSION

The Automated Construction Defect Monitoring System utilizing image processing and CNN presents a transformative approach to monitoring and maintaining construction quality. By leveraging deep learning, the system effectively detects and classifies crack types, including oblique, horizontal, transverse, and non-crack surfaces, ensuring a robust defect identification mechanism. The integration of real-time image capture, preprocessing, and predictive analytics enhances efficiency, reducing manual inspection errors and improving overall structural safety.

This system significantly contributes to the construction industry by providing accurate, fast, and automated defect detection, minimizing human intervention while ensuring reliability. Future enhancements may include

multi-class segmentation for precise crack localization, incorporation with IoT sensors for up- to-the-minute monitoring, and enhanced AI models to improve detection accuracy. With continuous advancements, this AI-driven approach has the potential to modernize construction quality control, making infrastructure safer and more durable.

FUTURE SCOPE

- Incorporation with Building Information Modelling (BIM): Future developments can integrate the quality control system with BIM platforms, enhancing coordination between the digital design and real-time construction quality assessments.
- Expansion to Other Construction Areas: The system can be adapted to detect defects in other parts of construction, such as structural steelwork, electrical installations, and plumbing systems.
- Use of Advanced Deep Learning Models: planned initiatives can integrate more advanced deep learning algorithms, such as convolutional neural networks (CNNs), for even better accuracy in defect classification.
- Integration with Internet of Things (IoT): The system can be extended to work with IoT sensors for on-the-fly monitoring of environmental conditions (temperature, humidity, etc.) that can affect construction quality.
- Enhanced Reporting and Analytics: Future versions of the system can include advanced analytics features, allowing users to track defect patterns and anticipate potential quality issues before they arise.
- Application in Different Construction Types: The system can be adapted to handle different types of construction projects, including residential, commercial, and industrial buildings.

LIMITATIONS

- Dependency on Image Quality: The exactness of defect detection is highly reliant on the quality of the images captured. Poor lighting, resolution, or camera angles can affect the system's performance.
- Limited Defect Types: While the system can identify common defects such as cracks and surface irregularities, it may struggle to detect more complex or subtle issues like internal structural damage without additional sensors or equipment.
- Environmental Constraints: The system may be less effective in outdoor construction environments where lighting and weather conditions are constantly changing, leading to variations in image quality.
- Initial Setup Costs: Implementing an automated system may require significant initial endowment in high-quality cameras, hardware, and software development, which could be a hurdle for smaller construction firms.
- Training Requirements: For optimal performance, the system may require extensive training on various construction types, defects, and conditions, which could increase the time and struggle required for deployment.
- Limited to Visible Defects: The system relies on visual inspection, meaning it cannot detect defects that are not visible on the surface, such as internal cracks or issues within layers of materials.

REFERENCES

- [1] Ahmed Mansour, Osama Kassem "Defect Detection in Construction Work Using Image Processing Techniques", Journal of Civil Engineering and Technology, 2020.
- [2] Ali Akbari, Daniel L. Petros, "AI-Driven Construction Quality Monitoring Using Visual Data", AI in Civil Engineering, 2021
- [3] Anil Gupta, Rajeev Bansal, "Application of Image Processing in Construction Quality Control", Journal of Construction Engineering and Management, 2019
- [4] Ashish Kulkarni: "Emerging Software Techniques in Construction Industry "Computer Integrated Manufacturing Systems, 2023
- [5] Harish S. Raj, Anjali Prakash, "Image-Based Monitoring for Construction Quality Control Using Machine Learning", Engineering Applications of Artificial Intelligence, 2022
- [6] Himanshu Yadav, Arvind S. Kumar, "Construction Defects Detection Using Machine Vision: Applications in Quality Control", Automation and Robotics in Civil Engineering, 2020
- [7] Hongjun Liu, Xuan Zhang, "A Novel Approach to Defect Detection in Construction Projects Using Deep Learning and Image Processing", Journal of Construction and Building Materials, 2022
- [8] John L. Williams, Mark O'Connor, "Image Processing for Monitoring Structural Integrity in Building Construction", Journal of Structural Engineering, 2021
- [9] Krishna R. Patel, Vinayak M. Desai, "Image Processing for Automated Concrete Quality Control: A Case Study" Journal of Concrete Technology and Innovation, 2021

- [10] Kunal S. Sharma, Ramesh K. Agarwal, "Automated Quality Control System in Construction Using Image Processing and Deep Learning", Journal of Civil and Environmental Engineering, 2023
- [11] Mohd Ali, Shubham Gupta, "Vision-Based Monitoring System for Real-Time Quality Control in Construction", Journal of Construction Science and Technology, 2020
- [12] N. S. Patel, M. Sharma, "Real-Time Automated Inspection for Construction Projects Using Vision Systems" International Journal of Automation and Computing, 2021
- [13] R. Srinivasan, N. Murugan, Real-Time Quality Assurance System for Construction Site Using Computer Vision", Automation in Construction, 2021
- [14] Rajat Verma, Arun Kumar, "Construction Defect Detection Using Hybrid Image Processing and Neural Networks" Journal of Civil Engineering Technology, 2021
- [15] Wei Xu, Li Yang, "Smart Construction Quality Control with Automated Image Analysis", Automation in Construction, 2023